PolvOne

MATERIAL SAFETY DATA SHEET ANSP SL GREEN 562

Version Number 1.2 Revision Date 10/01/2007

Page 1 of 7 Print Date 12/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:		Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	ANSP SL GREEN 562
Product code	:	FO20006390
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Azodicarbonamide	123-77-3	1 - 5
Miscellaneous Zinc Compounds	Not Available	1 - 5
Titanium dioxide	13463-67-7	0.1 - 1
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **ANSP SL GREEN 562**

Version Number 1.2 Revision Date 10/01/2007 Page 2 of 7 Print Date 12/1/2011

Medical Conditions Aggravated by Exposure:	: None known.	
	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.	of
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If e irritation persists, seek medical attention.	eye
Skin	: Wash off with soap and plenty of water. If skin irritation persists so medical attention.	eel
	5. FIRE-FIGHTING MEASURES	
Flash point	: No data available	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 No data available No data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. 	
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positiv pressure mode should be worn to prevent inhalation of airborne contaminants.	'e
Unusual Fire/Explosion Hazards	 May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) und fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxid of nitrogen (NOx), other hazardous materials, and smoke are all possible. 	
	6. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: The product should not be allowed to enter drains, water courses or soil. Should not be released into the environment.	the
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid bind universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for prope disposal methods.	

PolyOne.

MATERIAL SAFETY DATA SHEET **ANSP SL GREEN 562**

Version Number 1.2 Revision Date 10/01/2007 Page 3 of 7 Print Date 12/1/2011

		7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilatio fume condensates may contain combustible or toxic r Periodically clean hoods, ducts, and other surfaces to accumulation of these materials.	
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXP	OSUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practic Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit		MX OEL
		(STEL):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average	as Ti	MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
		(STEL):		

9. PHYSICAL AND CHEMICAL PROPERTIES

PolyOne.

MATERIAL SAFETY DATA SHEET **ANSP SL GREEN 562**

Version Number 1.2 Revision Date 10/01/2007

Form Appearance Color Odour Melting point/range Boiling Point: Water solubility	 liquid Viscous, liquid GREEN Very faint Not applicable Not applicable Immiscible 	Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH	 Not established Not determined Not applicable Not determined Not determined Not applicable
	10. STABILITY AN	DREACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from o decomposition, do	oxidizing agents and open floor not overheat.	ame. To avoid thermal
Incompatible Materials	-	strong acids and oxidizing olymers and acetal copolyr	•
Hazardous decomposition products	(NOx), hydrogen o smoke are all poss degradation. As a after one hour at 1	202), carbon monoxide (CC chloride (HCl), other hazard ible. Prolonged heating ma general rule of thumb, deg 77 °C (350 °F), after 10 min tes at 232 °C (450 °F).	dous materials, and ay result in product radation begins to occur

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
123-77-3	Azodicarbonamide	sensitizer	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-N	0.	Chemical Name	Route	Value	Species
123-77-3		Azodicarbonamide	LC50	200 mg/l	rat
			Oral LD50	> 6,400 mg/kg	rat
			Dermal LD50	> 2,000 mg/kg	rabbit

Carcinogenicity

MATERIAL SAFETY DATA SHEET ANSP SL GREEN 562

Version Number 1.2 Revision Date 10/01/2007 Page 5 of 7 Print Date 12/1/2011

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Azodicarbonamide 123-77-3 Sensitizer to the respiratory system with repeated minimal inhalation. While no chronic health problems have been identified, individuals with respiratory problems should avoid inhalation exposure to this material.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product Contaminated packaging	 Where possible recycling is preferred to disposal or incineration. Th generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.

5/7

PolyOne.

MATERIAL SAFETY DATA SHEET **ANSP SL GREEN 562**

Version Number 1.2 Revision Date 10/01/2007 Page 6 of 7 Print Date 12/1/2011

TSCA Status : Al Inv US. EPA CERCLA Hazardous Substand Not applicable California Proposition : No	assified as hazard ll components of t ventory. ces (40 CFR 302)	this product are	-		ot from the TSCA
TSCA Status : Al Inv US. EPA CERCLA Hazardous Substand Not applicable California Proposition : No	ll components of t ventory.	this product are	-		ot from the TSCA
Inv US. EPA CERCLA Hazardous Substand Not applicable California Proposition : No	ventory.	-	listed on c	or exemp	pt from the TSCA
Not applicable California Proposition : No	ces (40 CFR 302))			
California Proposition : No					
65	ot applicable				
SARA Title III Section 302 Extremely I	Hazardous Substa	ance			
Unless specific chemicals are identified	under this section	n this product i	is Not Apr	licable	under this regula
		, F			
SARA Title III Section 313 Toxic Chen	nicals:				
Unless specific chemicals are identified	under this section	n, this product i	is Not Apr	olicable	under this regula
Chemical Name		CAS-No	D.	Weight	%
ZINC COMPOUNDS		Not Avai	lable	1.00 - 5	5.00
Canadian Regulations: National Pollutant Release Inven Chemical Name		AS-No.	Weight	%	NPRI ID#
Phthalocyanine green		328-53-6	0.10 - 1		71
Miscellaneous Zinc Compounds		ot Available	1.00 - 5		241
Unless specific chemicals are identified			D.		%

PolyOne

MATERIAL SAFETY DATA SHEET ANSP SL GREEN 562

Version Number 1.2 Revision Date 10/01/2007 Page 7 of 7 Print Date 12/1/2011

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.