

MATERIAL SAFETY DATA SHEET **DB2800 SILVER**

Version Number 1.0 Revision Date 09/24/2003

Page 1 of 6 Print Date 11/12/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DB2800 SILVER
Product code	:	FO20006449
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Mica	12001-26-2	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion			
Acute exposure				
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.			
Ingestion	: May be harmful if swallowed.			
Eyes	: May cause eye/skin irritation.			
Skin	: Experience shows no unusual dermatitis hazard from routine handling.			
Chronic exposure	: Refer to Section 11 for Toxicological Information.			



MATERIAL SAFETY DATA SHEET **DB2800 SILVER**

Version Number 1.0 Revision Date 09/24/2003 Page 2 of 6 Print Date 11/12/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 No data available. No data available. Not applicable. Carbon dioxide blanket, water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



MATERIAL SAFETY DATA SHEET **DB2800 SILVER**

sion Date 09/24/2003			Print D	Page 2 Date 11/12/
	P		in combustible or toxic resicts, and other surfaces to minals.	
Storage		eep containers dry and tight contamination. Store in	tly closed to avoid moisture a cool dry place.	e absorption
8. E	XPOSURE	CONTROLS / PERSONA	AL PROTECTION	
Respiratory protection	: U	nder normal handling cond	itions a respirator may not	be required.
Eye/Face Protection	: S	afety glasses with side-shie	lds.	
Hand protection	: pr	rotective gloves		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: Sa	afety shoes.		
General Hygiene Considerations		andle in accordance with g Vash hands before breaks an	ood industrial hygiene and s nd at the end of workday.	afety practic
Engineering measures		eat only in areas with appropriate exhaust ventilati	opriate exhaust ventilation.	Provide
			-	
Exposure limit(s)				
Exposure limit(s) Components	Value	Exposure time	Exposure type	List:
	Value 20 mppcf	PEL:	Total dust.	List: OSHA
Components		*	Total dust.	OSHA
Components	20 mppcf 3 mg/m3	PEL: Time Weighted Average	Total dust. Respirable fraction.	OSHA
Components Mica	20 mppcf 3 mg/m3 9. PHYSIC	PEL: Time Weighted Average (TWA): CAL AND CHEMICAL P	Total dust. e Respirable fraction. ROPERTIES	OSHA ACGIH
Components Mica Form	20 mppcf 3 mg/m3 9. PHYSIC : liquid	PEL: Time Weighted Average (TWA): CAL AND CHEMICAL P d Eva	Total dust. e Respirable fraction. ROPERTIES uporation rate : Not	OSHA ACGIH established
Components Mica Form Appearance	20 mppcf 3 mg/m3 9. PHYSIC : liquid : Visco	PEL: Time Weighted Average (TWA): CAL AND CHEMICAL P d Eva bus, liquid Spe	Total dust. Respirable fraction. ROPERTIES aporation rate : Not scific Gravity	OSHA ACGIH established determined
Components Mica Form Appearance Color	20 mppcf 3 mg/m3 9. PHYSIC : liquid : Visco : GRE	PEL: Time Weighted Average (TWA): CAL AND CHEMICAL P d Eva bus, liquid Spec Y Bul	Total dust. Respirable fraction. ROPERTIES aporation rate : Not cific Gravity : Not k density : Not	OSHA ACGIH established determined applicable.
Components Mica Form Appearance Color Odor	20 mppcf 3 mg/m3 9. PHYSIC : liquid : Visco : GRE : Very	PEL: Time Weighted Average (TWA): CAL AND CHEMICAL P d Eva bus, liquid Spe Y Bul faint Vaj	Total dust. Respirable fraction. ROPERTIES uporation rate : Not cific Gravity : Not k density : Not por pressure : Not	OSHA ACGIH established determined applicable. determined
Components Mica Form Appearance Color Odor Melting point/range	20 mppcf 3 mg/m3 9. PHYSIC : liquid : Visco : GRE : Very : Not a	PEL: Time Weighted Average (TWA): CAL AND CHEMICAL P d Eva bus, liquid Spe Y Bul faint Vaj	Total dust. Respirable fraction. ROPERTIES uporation rate : Not crific Gravity : Not k density : Not por pressure : Not pour density : Not	OSHA ACGIH established determined applicable. determined determined
Components Mica Form Appearance Color Odor	20 mppcf 3 mg/m3 9. PHYSIC : liquid : Visco : GRE : Very : Not a : Not a	PEL: Time Weighted Average (TWA): CAL AND CHEMICAL P d Eva ous, liquid Spe Y Bul faint Vaj applicable Vaj	Total dust. Respirable fraction. ROPERTIES uporation rate : Not crific Gravity : Not k density : Not por pressure : Not pour density : Not	OSHA ACGIH established determined applicable. determined
Components Mica Form Appearance Color Odor Melting point/range Boiling Point:	20 mppcf 3 mg/m3 9. PHYSIC : liquid : Visco : GRE : Very : Not a : Not a : Immi	PEL: Time Weighted Average (TWA): CAL AND CHEMICAL P d Eva ous, liquid Spe Y Bul faint Vaj applicable Vaj applicable pH	Total dust. Respirable fraction. ROPERTIES aporation rate : Not cific Gravity : Not k density : Not poor pressure : Not cour density : Not	OSHA ACGIH established determined applicable. determined determined
Components Mica Form Appearance Color Odor Melting point/range Boiling Point:	20 mppcf 3 mg/m3 9. PHYSIC : liquid : Visco : GRE : Very : Not a : Immi 10. S	PEL: Time Weighted Average (TWA): CAL AND CHEMICAL P d Eva bus, liquid Spector Y Bultor faint Vaj applicable Vaj applicable pH iscible	Total dust. Respirable fraction. ROPERTIES aporation rate : Not cific Gravity : Not k density : Not poor pressure : Not cour density : Not	OSHA ACGIH established determined applicable. determined determined



MATERIAL SAFETY DATA SHEET DB2800 SILVER

Version Number 1.0 Revision Date 09/24/2003	Page / Print Date 11/12/	
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid therma decomposition, do not overheat.	l
Incompatible Materials	: Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.	
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occu after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F and within 5 minutes at 232 °C (450 °F).	
	11. TOXICOLOGICAL INFORMATION	
	11. TOXICOLOGICAL INFORMATION ated as a whole for health effects. Exposure effects listed are based on ex mponents which comprise the mixture.	is

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.		ical Name	Effect	Target Organ
12001-26-2	Aica		Systemic effects	Respiratory system.
	12	. ECOLOGICA	L INFORMATION	
Persistence and degradab	ility :	Not readily biod	degradable.	
Environmental Toxicity	:	Environmental whole.	toxicity has not been	established for this mixture as a
Bioaccumulation Potentia	ıl :	No data availab	le.	
Additional advice	:	No data availab	le.	
	13	3. DISPOSAL C	ONSIDERATIONS	
Product	:	generator of wa classification, tr	ste material has the r	d to disposal or incineration. Th esponsibility for proper waste posal in accordance with nd local regulations.
Contaminated packaging	:	has the responsi	bility for proper was accordance with appl	The generator of waste materia te classification, transportation icable federal, state/provincial
	1	4. TRANSPOR	FINFORMATION	



MATERIAL SAFETY DATA SHEET
DB2800 SILVER

sion Number 1.0 ision Date 09/24/2003		Page 5 of Print Date 11/12/20
U.S. DOT Classification	:	Refer to specific regulation.
ICAO/IATA (air)	:	Refer to specific regulation.
IMO / IMDG (maritime)	:	Refer to specific regulation.
	15	S. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.
		California to cause cancer.
65		California to cause cancer.
65 SARA Title III Section 302 Ext	rem	California to cause cancer. ely Hazardous Substance
65 SARA Title III Section 302 Ext Not applicable	rem	California to cause cancer. ely Hazardous Substance
65 SARA Title III Section 302 Ext Not applicable SARA Title III Section 313 Tox Not applicable	rem kic C	California to cause cancer. ely Hazardous Substance Chemicals:
65 SARA Title III Section 302 Ext Not applicable SARA Title III Section 313 Tox Not applicable Canadian Regulations:	rem kic C	California to cause cancer. ely Hazardous Substance Chemicals:
65 SARA Title III Section 302 Ext Not applicable SARA Title III Section 313 Tox Not applicable Canadian Regulations: National Pollutant Relea	rem kic C	California to cause cancer. ely Hazardous Substance Chemicals:
65 SARA Title III Section 302 Ext Not applicable SARA Title III Section 313 Tox Not applicable Canadian Regulations: National Pollutant Relea Not applicable	rem kic C se Ir	California to cause cancer. ely Hazardous Substance Chemicals:
65 SARA Title III Section 302 Ext Not applicable SARA Title III Section 313 Tox Not applicable Canadian Regulations: National Pollutant Relea Not applicable WHMIS Classification	rem kic C se Ir	California to cause cancer. ely Hazardous Substance Chemicals: nventory (NPRI) Not controlled. All components of this product are on the Canadian Domestic
65 SARA Title III Section 302 Ext Not applicable SARA Title III Section 313 Tox Not applicable Canadian Regulations: National Pollutant Relea Not applicable WHMIS Classification DSL	rem kic C se Ir	California to cause cancer. ely Hazardous Substance Chemicals: nventory (NPRI) Not controlled. All components of this product are on the Canadian Domestic
65 SARA Title III Section 302 Ext Not applicable SARA Title III Section 313 Tox Not applicable Canadian Regulations: National Pollutant Relea Not applicable WHMIS Classification DSL National Inventories:	rem kic C se Ir :	California to cause cancer. ely Hazardous Substance Chemicals: nventory (NPRI) Not controlled. All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

POLYONE	CORPORATION	



MATERIAL SAFETY DATA SHEET **DB2800 SILVER**

Version Number 1.0 Revision Date 09/24/2003

Page 6 of 6 Print Date 11/12/2011

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.