## MATERIAL SAFETY DATA SHEET **PX-11503-A PLASTISOL**

Version Number 1.1 Revision Date 04/26/2005

Page 1 of 6 Print Date 11/17/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PX-11503-A PLASTISOL
Product code	:	FO20006510
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES



# MATERIAL SAFETY DATA SHEET **PX-11503-A PLASTISOL**

sion Number 1.1 ision Date 04/26/2005	Page 2 Print Date 11/17/2
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	<ul> <li>Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.</li> </ul>
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>No data available</li> <li>No data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or th soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize

# MATERIAL SAFETY DATA SHEET PX-11503-A PLASTISOL

Version Number 1.1 Revision Date 04/26/2005 Page 3 of 6 Print Date 11/17/2011

accumulation of these materials. Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION : No personal respiratory protective equipment normally required. Respiratory protection Eye/Face Protection Safety glasses with side-shields. : Hand protection Protective gloves. : Skin and body protection Long sleeved clothing. : Additional Protective Safety shoes. : Measures General Hygiene Handle in accordance with good industrial hygiene and safety practice. : Considerations Wash hands before breaks and at the end of workday.

Exposure limit(s)

Engineering measures

There are no known hazardous components above regulatory thresholds in this product.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form:Appearance:Color:Odor:Melting point/range:Boiling Point::Water solubility:

liquid
Viscous, liquid
WHITE
Very faint
Not applicable
Not applicable
Immiscible

Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH

: Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

Not established
Not determined
Not applicable
Not determined
Not determined
Not applicable

10. STABILITY AND REACTIVITY		
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.	
Incompatible Materials	: Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.	

PolyOne

## MATERIAL SAFETY DATA SHEET **PX-11503-A PLASTISOL**

Version Number 1.1 Revision Date 04/26/2005 Page 4 of 6 Print Date 11/17/2011

Hazardous decomposition products
Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

### 11. TOXICOLOGICAL INFORMATION

There are no known hazardous components above regulatory thresholds in this product.

ator of waste material has the responsibility for proper waste fication, transportation and disposal in accordance with able federal, state/provincial and local regulations.
ta available ta available <b>POSAL CONSIDERATIONS</b> e possible recycling is preferred to disposal or incineration. The ator of waste material has the responsibility for proper waste fication, transportation and disposal in accordance with able federal, state/provincial and local regulations. ling is preferred when possible. The generator of waste materia e responsibility for proper waste classification, transportation sposal in accordance with applicable federal, state/provincial
ta available <b>POSAL CONSIDERATIONS</b> e possible recycling is preferred to disposal or incineration. The tor of waste material has the responsibility for proper waste fication, transportation and disposal in accordance with able federal, state/provincial and local regulations. ding is preferred when possible. The generator of waste materia e responsibility for proper waste classification, transportation sposal in accordance with applicable federal, state/provincial
POSAL CONSIDERATIONS e possible recycling is preferred to disposal or incineration. The ator of waste material has the responsibility for proper waste fication, transportation and disposal in accordance with able federal, state/provincial and local regulations. Using is preferred when possible. The generator of waste materia e responsibility for proper waste classification, transportation sposal in accordance with applicable federal, state/provincial
e possible recycling is preferred to disposal or incineration. The ator of waste material has the responsibility for proper waste fication, transportation and disposal in accordance with able federal, state/provincial and local regulations. ling is preferred when possible. The generator of waste materia e responsibility for proper waste classification, transportation sposal in accordance with applicable federal, state/provincial
fication, transportation and disposal in accordance with able federal, state/provincial and local regulations. ling is preferred when possible. The generator of waste materia e responsibility for proper waste classification, transportation sposal in accordance with applicable federal, state/provincial
e responsibility for proper waste classification, transportation sposal in accordance with applicable federal, state/provincial
NSPORT INFORMATION
to specific regulation.
to specific regulation.
to specific regulation.
ULATORY INFORMATION

<u>PolyOne</u>

## MATERIAL SAFETY DATA SHEET **PX-11503-A PLASTISOL**

Version Number 1.1 Revision Date 04/26/2005 Page 5 of 6 Print Date 11/17/2011

TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
California Proposition 65	: Not applicable
SARA Title III Section 302 Extr Not applicable	remely Hazardous Substance
SARA Title III Section 313 Tox	ic Chemicals:
Not applicable Canadian Regulations:	
National Pollutant Releas	se Inventory (NPRI)
Not applicable	
WHMIS Classification	: Not controlled.
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined
	16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.

PolyOne.

MATERIAL SAFETY DATA SHEET **PX-11503-A PLASTISOL** 

Version Number 1.1 Revision Date 04/26/2005 Page 6 of 6 Print Date 11/17/2011