



POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

910 CLEAR HOT PEEL BASE

Version Number 1.6
Revision Date 01/05/2007

Page 1 of 7
Print Date 11/25/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION
8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone : Product Stewardship (770) 590-3500 x.3563
Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure
number : or accident).

Product name : 910 CLEAR HOT PEEL BASE
Product code : FO20006579
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
1,2-Benzenedicarboxylic acid, butyl phenylmethylester	85-68-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation : Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion : May be harmful if swallowed.
Eyes : May cause eye/skin irritation.
Skin : Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure : Refer to Section 11 for Toxicological Information.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

910 CLEAR HOT PEEL BASE

Version Number 1.6
Revision Date 01/05/2007

Page 2 of 7
Print Date 11/25/2011

Medical Conditions : None known.
Aggravated by Exposure:

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : No data available

Flammable Limits
Upper explosion limit : No data available
Lower explosion limit : No data available

Autoignition temperature : Not applicable

Suitable extinguishing media : Carbon dioxide blanket, water spray, dry powder, foam.

Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.

Unusual Fire/Explosion Hazards : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

910 CLEAR HOT PEEL BASE

Version Number 1.6
Revision Date 01/05/2007

Page 3 of 7
Print Date 11/25/2011

- Handling : Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
- Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Respiratory protection : No personal respiratory protective equipment normally required.
- Eye/Face Protection : Safety glasses with side-shields.
- Hand protection : Protective gloves.
- Skin and body protection : Long sleeved clothing.
- Additional Protective Measures : Safety shoes.
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
- Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Silica, amorphous, fumed, crystal-free	20 mppcf	PEL:	Total dust.	Z3
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- | | | | |
|---------------------|-------------------|-------------------|-------------------|
| Form | : liquid | Evaporation rate | : Not established |
| Appearance | : Viscous, liquid | Specific Gravity: | : Not determined |
| Color | : NO PIGMENT | Bulk density | : Not applicable |
| Odor | : Very faint | Vapor pressure | : Not determined |
| Melting point/range | : Not applicable | Vapour density | : Not determined |
| Boiling Point: | : Not applicable | pH | : Not applicable |
| Water solubility | : Immiscible | | |

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

910 CLEAR HOT PEEL BASE

Version Number 1.6
Revision Date 01/05/2007

Page 4 of 7
Print Date 11/25/2011

10. STABILITY AND REACTIVITY

- Stability : Stable.
- Hazardous Polymerization : Will not occur.
- Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
- Incompatible Materials : Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
- Hazardous decomposition products : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
112945-52-5	Silica, amorphous, fumed, crystal-free	Irritant	Eyes, Respiratory system.
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Irritant	Eyes, Skin.
		Systemic effects	Liver, reproductive system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
112945-52-5	Silica, amorphous, fumed, crystal-free	Oral LD50	3,160 mg/kg	rat
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Oral LD50 Dermal LD50	2,330 mg/kg > 10 gm/kg	rat rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****910 CLEAR HOT PEEL BASE**Version Number 1.6
Revision Date 01/05/2007Page 5 of 7
Print Date 11/25/2011

CAS-No.	Chemical Name	OSHA	IARC	NTP
---------	---------------	------	------	-----

IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

- Persistence and degradability : Not readily biodegradable.
- Environmental Toxicity : Environmental toxicity has not been established for this mixture as a whole.
- Bioaccumulation Potential : No data available
- Additional advice : No data available

13. DISPOSAL CONSIDERATIONS

- Product : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
- Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

- U.S. DOT Classification : Refer to specific regulation.
- ICAO/IATA (air) : Refer to specific regulation.
- IMO / IMDG (maritime) : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

- OSHA Status : Classified as hazardous based on components.
- TSCA Status : All components of this product are listed on or exempt from the TSCA

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

910 CLEAR HOT PEEL BASE

Version Number 1.6
Revision Date 01/05/2007

Page 6 of 7
Print Date 11/25/2011

Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component	RQ for Mixture/Product
1,2-Benzenedicarb oxylic acid, butyl phenylmethylester	85-68-7	100 lbs	289 LB

California Proposition : WARNING! This product contains a chemical known to the State of
65 California to cause birth defects or other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
1,2-Benzenedicarboxylic acid, butyl phenylmethylester	85-68-7	30.00 - 60.00	37

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.
112945-52-5
85-68-7

DSL : All components of this product are on the Canadian Domestic
Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Not determined

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

910 CLEAR HOT PEEL BASE

Version Number 1.6
Revision Date 01/05/2007

Page 7 of 7
Print Date 11/25/2011

China IECS : Not determined
Europe EINECS : Listed
Japan ENCS : Not determined
Korea KECI : Not determined
Philippines PICCS : Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.