## MATERIAL SAFETY DATA SHEET PX-19308-C TRANSPARENT BLUE PLASTISOL

Version Number 1.5 Revision Date 02/06/2008 Page 1 of 6 Print Date 12/3/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PX-19308-C TRANSPARENT BLUE PLASTISOL
Product code	:	FO20006769
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
2,6-Di-tert-butyl-p-cresol	128-37-0	0.1 - 1

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne

# MATERIAL SAFETY DATA SHEET **PX-19308-C TRANSPARENT BLUE PLASTISOL**

Version Number 1.5 Revision Date 02/06/2008 Page 2 of 6 Print Date 12/3/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ol> <li>No data available</li> <li>No data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ol>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing

MX OEL

### MATERIAL SAFETY DATA SHEET PX-19308-C TRANSPARENT BLUE PLASTISOL

Version Number 1.5 Page 3 of 6 Print Date 12/3/2011 Revision Date 02/06/2008 fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. Storage Keep containers dry and tightly closed to avoid moisture absorption : and contamination. Store in a cool dry place. 8. EXPOSURE CONTROLS/PERSONAL PROTECTION Respiratory protection No personal respiratory protective equipment normally required. : Eye/Face Protection : Safety glasses with side-shields Hand protection : Protective gloves Skin and body protection : Long sleeved clothing Additional Protective Safety shoes : Measures General Hygiene Handle in accordance with good industrial hygiene and safety : Considerations practice. Wash hands before breaks and at the end of workday. : Heat only in areas with appropriate exhaust ventilation. Provide Engineering measures appropriate exhaust ventilation at machinery. Exposure limit(s) Components Value Exposure time Exposure type List: Time Weighted Average 2,6-Di-tert-butyl-p-2 mg/m3 Inhalable fraction and ACGIH cresol (TWA): vapor 10 mg/m3 Time Weighted Average MX OEL (TWA):

	9. PHYSICAL AND CHEN	IICAL PROPERTIES	
Form Appearance Color Odour Melting point/range Boiling Point: Water solubility	<ul> <li>liquid</li> <li>Viscous, liquid</li> <li>TRANSPARENT</li> <li>Very faint</li> <li>Not applicable</li> <li>Not applicable</li> <li>Immiscible</li> </ul>	Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH	<ul><li>Not determined</li><li>Not applicable</li></ul>
	10. STABILITY ANI	<b>REACTIVITY</b>	
Stability	: Stable.		

Short Term Exposure Limit

20 mg/m3

olyOne

## MATERIAL SAFETY DATA SHEET PX-19308-C TRANSPARENT BLUE PLASTISOL

Version Number 1.5 Revision Date 02/06/2008 Page 4 of 6 Print Date 12/3/2011

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

**Toxicity Overview** 

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
128-37-0	2,6-Di-tert-butyl-p-cresol	Systemic effects	Eyes, Skin.
		Irritant	Eyes, Skin.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
128-37-0	2,6-Di-tert-butyl-p-cresol	Oral LD50	890 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
128-37-0	2,6-Di-tert-butyl-p-cresol	no	3	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

PolyOne

# MATERIAL SAFETY DATA SHEET **PX-19308-C TRANSPARENT BLUE PLASTISOL**

Version Number 1.5 Revision Date 02/06/2008 Page 5 of 6 Print Date 12/3/2011

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
	: Not applicable

## MATERIAL SAFETY DATA SHEET **PX-19308-C TRANSPARENT BLUE PLASTISOL**

Version Number 1.5 Revision Date 02/06/2008 Page 6 of 6 Print Date 12/3/2011

65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name			CAS-No.	Weight %	NPRI ID#
2,6-Di-tert-butyl-p-cresol			128-37-0	0.10 - 1.00	81
WHMIS Classification	:	All components	of this product a (DSL) or are exe	are on the Canadia mpt.	n Domestic
National Inventories:					
Australia AICS	:	Not determined			
China IECS	:	Not determined			
Europe EINECS	:	Not determined			
Japan ENCS	:	Not determined			
Korea KECI	:	Not determined			
Philippines PICCS	:	Not determined			
		16. OTHER IN	FORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.