

## MATERIAL SAFETY DATA SHEET

## DB3759 BLACK

Version Number 1.0 Revision Date 12/11/2003

Page 1 of 6 Print Date 11/12/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DB3759 BLACK
Product code	:	FO20007067
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Calcium carbonate	1317-65-3	5 - 10

## 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

## POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



## MATERIAL SAFETY DATA SHEET DB3759 BLACK

Version Number 1.0 Revision Date 12/11/2003

Page 2 of 6 Print Date 11/12/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>No data available</li> <li>No data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foamnone.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



# MATERIAL SAFETY DATA SHEET **DB3759 BLACK**

ision Date 12/11/2003				Print D	Page 3 Date 11/12/2
Handling	fun Pei	ne condensates ma	y contain com ods, ducts, and	exhaust ventilation. bustible or toxic resi other surfaces to m	idue.
Storage		ep containers dry a l contamination. S		ed to avoid moistur dry place.	e absorption
8. I	EXPOSURE C	CONTROLS / PE	RSONAL PRO	OTECTION	
Respiratory protection	: Un	der normal handlin	ng conditions a	respirator may not	be required.
Eye/Face Protection	: Saf	ety glasses with si	ide-shields.		
Hand protection	: Pro	otective gloves.			
Skin and body protection	: Lo	ng sleeved clothing	g.		
Additional Protective Measures	: Saf	ety shoes.			
General Hygiene Considerations		ndle in accordance ish hands before b		ustrial hygiene and s e end of workday.	afety practice
Engineering measures Exposure limit(s)		at only in areas wi propriate exhaust v		exhaust ventilation. achinery.	Provide
Components	Value	Exposure ti	me	Exposure type	L ist:
Components Calcium carbonate	Value	Exposure tin		Exposure type	List:
Components Calcium carbonate	5 mg/m3	PEL:		espirable fraction.	OSHA Z1
Calcium carbonate	5 mg/m3 15 mg/m3	PEL: PEL:		espirable fraction. Total dust.	OSHA Z1 OSHA Z1
<u> </u>	5 mg/m3	PEL:		espirable fraction.	OSHA Z1
Calcium carbonate	5 mg/m3 15 mg/m3 20 mppcf 20 mppcf	PEL: PEL: PEL:	R	espirable fraction. Total dust. Total dust. Total dust.	OSHA Z1 OSHA Z1 OSHA
Calcium carbonate Silica, amorphous	5 mg/m3 15 mg/m3 20 mppcf 20 mppcf 9. PHYSIC	PEL: PEL: PEL: PEL:	CAL PROPE	espirable fraction. Total dust. Total dust. Total dust. RTIES	OSHA Z1 OSHA Z1 OSHA Z3
Calcium carbonate Silica, amorphous Form	5 mg/m3 15 mg/m3 20 mppcf 20 mppcf 9. PHYSICA : liquid	PEL: PEL: PEL: PEL: AL AND CHEMI	CAL PROPE Evaporatic	espirable fraction. Total dust. Total dust. Total dust. RTIES on rate : Not	OSHA Z1 OSHA Z1 OSHA Z3
Calcium carbonate Silica, amorphous Form Appearance	5 mg/m3 15 mg/m3 20 mppcf 20 mppcf 9. PHYSICA : liquid : Viscou	PEL: PEL: PEL: PEL: AL AND CHEMI	CAL PROPE Evaporatic Specific G	espirable fraction. Total dust. Total dust. Total dust. <b>RTIES</b> on rate : Not ravity: : Not	OSHA Z1 OSHA Z1 OSHA Z3
Calcium carbonate Silica, amorphous Form Appearance Color	5 mg/m3 15 mg/m3 20 mppcf 20 mppcf 9. PHYSICA : liquid : Viscou : BLAC	PEL: PEL: PEL: PEL: AL AND CHEMI	CAL PROPE Evaporatio Specific G Bulk densi	espirable fraction. Total dust. Total dust. Total dust. <b>RTIES</b> on rate : Not ravity: : Not ty : Not	OSHA Z1 OSHA Z1 OSHA Z3 established determined applicable
Calcium carbonate Silica, amorphous Form Appearance Color Odor	5 mg/m3 15 mg/m3 20 mppcf 20 mppcf 9. PHYSICA : liquid : Viscou : BLAC : Very f	PEL: PEL: PEL: PEL: AL AND CHEMI	CAL PROPE Evaporatic Specific G Bulk densi Vapor pres	espirable fraction. Total dust. Total dust. Total dust. <b>RTIES</b> on rate : Not ravity: : Not ty : Not ssure : Not	OSHA Z1 OSHA Z1 OSHA Z3 established determined applicable determined
Calcium carbonate Silica, amorphous Form Appearance Color Odor Melting point/range	5 mg/m3 15 mg/m3 20 mppcf 20 mppcf 9. PHYSICA : liquid : Viscou : BLAC : Very f : Not ap	PEL: PEL: PEL: PEL: AL AND CHEMI	CAL PROPE Evaporatic Specific G Bulk densi Vapor pres Vapour de	espirable fraction. Total dust. Total dust. Total dust. RTIES PARTIES	OSHA Z1 OSHA Z1 OSHA Z3 Z3 established determined applicable determined determined
Calcium carbonate Silica, amorphous Form Appearance Color Odor	5 mg/m3 15 mg/m3 20 mppcf 20 mppcf 9. PHYSICA : liquid : Viscou : BLAC : Very f	PEL: PEL: PEL: PEL: AL AND CHEMI Is, liquid K aint plicable plicable	CAL PROPE Evaporatic Specific G Bulk densi Vapor pres	espirable fraction. Total dust. Total dust. Total dust. RTIES PARTIES	OSHA Z1 OSHA Z1 OSHA Z3 Z3 established determined applicable determined
Calcium carbonate Silica, amorphous Form Appearance Color Odor Melting point/range Boiling Point:	5 mg/m3 15 mg/m3 20 mppcf 20 mppcf 9. PHYSICA : liquid : Viscou : BLAC : Very f : Not ap : Not ap : Immis	PEL: PEL: PEL: PEL: AL AND CHEMI Is, liquid K aint plicable plicable	CAL PROPE Evaporatic Specific G Bulk densi Vapor pres Vapour de pH	espirable fraction. Total dust. Total dust. Total dust. <b>RTIES</b> on rate : Not ravity: : Not ty : Not ssure : Not nsity : Not	OSHA Z1 OSHA Z1 OSHA Z3 Z3 established determined applicable determined determined
Calcium carbonate Silica, amorphous Form Appearance Color Odor Melting point/range Boiling Point:	5 mg/m3 15 mg/m3 20 mppcf 20 mppcf 9. PHYSICA : liquid : Viscou : BLAC : Very f : Not ap : Not ap : Immis 10. ST	PEL: PEL: PEL: PEL: AL AND CHEMI Is, liquid K aint plicable plicable cible	CAL PROPE Evaporatic Specific G Bulk densi Vapor pres Vapour de pH	espirable fraction. Total dust. Total dust. Total dust. <b>RTIES</b> on rate : Not ravity: : Not ty : Not ssure : Not nsity : Not	OSHA Z1 OSHA Z1 OSHA Z1 Z3 established determined applicable determined determined
Calcium carbonate         Silica, amorphous         Silica, amorphous         Form         Appearance         Color         Odor         Melting point/range         Boiling Point:         Water solubility	5 mg/m3 15 mg/m3 20 mppcf 20 mppcf 9. PHYSICA : liquid : Viscou : BLAC : Very f : Not ap : Not ap : Immis 10. ST	PEL: PEL: PEL: PEL: AL AND CHEMI Is, liquid K aint oplicable cible CABILITY AND	CAL PROPE Evaporatic Specific G Bulk densi Vapor pres Vapour de pH	espirable fraction. Total dust. Total dust. Total dust. <b>RTIES</b> on rate : Not ravity: : Not ty : Not ssure : Not nsity : Not	OSHA Z1 OSHA Z1 OSHA Z3 established determined applicable determined determined



# MATERIAL SAFETY DATA SHEET **DB3759 BLACK**

Version Number 1.0 Revision Date 12/11/2003

Page 4 of 6 Print Date *11/12/2011* 

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

## 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

## Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

## 12. ECOLOGICAL INFORMATION

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.



## MATERIAL SAFETY DATA SHEET DB3759 BLACK

Version Number 1.0 Revision Date 12/11/2003 Page 5 of 6 Print Date 11/12/2011

and local regulations.				
	14. TRANSPORT INFORMATION			
U.S. DOT Classification :	Refer to specific regulation.			
ICAO/IATA (air) :	Refer to specific regulation.			
IMO / IMDG (maritime) :	Refer to specific regulation.			
1	5. REGULATORY INFORMATION			
US Regulations:				
OSHA Status :	Classified as hazardous based on components.			
TSCA Status :	All components of this product are listed on or exempt from the TSCA Inventory.			
US. EPA CERCLA Hazardous Sub	ostances (40 CFR 302)			
Not applicable				
California Proposition : 65	WARNING! This product contains a chemical known to the State of California to cause cancer.			
SARA Title III Section 302 Extrem	nely Hazardous Substance			
Not applicable				
SARA Title III Section 313 Toxic	SARA Title III Section 313 Toxic Chemicals:			
Not applicable Canadian Regulations:				
National Pollutant Release Inventory (NPRI)				
Not applicable				
WHMIS Classification :	WHMIS Classification : D2B			
WHMIS Ingredient Disclos	ure List			
CAS-No. 7631-86-9				



# MATERIAL SAFETY DATA SHEET **DB3759 BLACK**

Version Number 1.0 Revision Date 12/11/2003 Page 6 of 6 Print Date 11/12/2011

DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined
		16 OTHER INFORMATION

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.