MATERIAL SAFETY DATA SHEET **WB-10536-A RED ATH COATING**

Version Number 1.5 Revision Date 10/04/2006 Page 1 of 6 Print Date 11/24/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	WB-10536-A RED ATH COATING
Product code	:	FO20007068
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Iron oxide	1309-37-1	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. In addition, heating or processing this material may result in product degradation or byproduct formation creating additional hazards. See Sections 8 and 11 for additional details.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Skin contact, Inhalation, Ingestion		
Acute exposure			
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.		
Ingestion	: No known effects.		
Eyes	: Vapour during processing may be irritating to the respiratory tract and to the eyes.		
Skin	: May cause eye or skin irritation with susceptible persons.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		

PolyOne.

MATERIAL SAFETY DATA SHEET WB-10536-A RED ATH COATING

Version Number 1.5 Revision Date 10/04/2006 Page 2 of 6 Print Date 11/24/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of vapors or fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Obtain medical attention. Never give anything by mouth to an unconscious person.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If every irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Greater than 400 °F (204.4 °C)
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available No data available No data available carbon dioxide (CO2), water, foam, dry chemical. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Cool closed containers exposed to fire with water spray Do not allow run-off from fire fighting to enter drains or water courses Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Ensure response personnel are properly protected (see section 8 for respiratory or other protection guidelines.) Use caution as floors may be slippery.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Sweep up and shovel into suitable containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Use only in area provided with appropriate exhaust ventilation. Prolonged heating may result in product degradation. Material may

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET WB-10536-A RED ATH COATING

sion Number 1.5 /ision Date 10/04/2006	Page 3 Print Date 11/24/2	
	settle during storage. Careful mixing without introduction of air may be necessary before use.	
Storage	: Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool place. Keep from freezing and temperature extremes.	
8. EXF	POSURE CONTROLS / PERSONAL PROTECTION	
Respiratory protection	: A respirator is normally not required for routine handling of product i areas of good general ventilation and adequate local exhaust at processing equipment during routine operation.	
Eye/Face Protection	: Safety glasses with side-shields. Wear goggles or face shield during operations that present a splash potential.	
Hand protection	: Impervious gloves such as rubber or PVC	
Skin and body protection	: Long sleeved shirts and long pants are adequate for normal handli Where operations present a splash or spill potential, employees sh wear chemically resistant clothing, boots, apron, gloves, and eye/f protection.	
Additional Protective Measures	: Safety shoes.	
General Hygiene Considerations	: Wash hands before breaks and immediately after handling the produc Handle in accordance with good industrial hygiene and safety practices.	
Engineering measures	: Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.	
Exposure limit(s)		

Components	Value	Exposure time	Exposure type	List:
Iron oxide	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH

	9. PHYSICAL AND C	CHEMICAL PROPERTIES	
Form	: liquid	Evaporation rate	: Slower than Buty Acetate
Appearance	: liquid	Specific Gravity:	: Not determined

PolyOne

MATERIAL SAFETY DATA SHEET WB-10536-A RED ATH COATING

Version Number 1.5 Revision Date 10/04/2006 Page 4 of 6 Print Date 11/24/2011

	Color Odor Melting point/range Boiling Point: Water solubility	:	RED Slight Not applicable No data available Completely miscibi	Bulk densit Vapor press Vapour den pH le	sure : sity :	Not applicable Not established Heavier than air. Not determined	
	10. STABILITY AND REACTIVITY						
	Stability		: Stable.				
	Hazardous Polymerizati	on	: Will not occur.	Will not occur.			
	Conditions to avoid : Extre			emes of temperature and direct sunlight. Keep from freezing.			
	Incompatible Materials : Acids, metal sal			lts, and solvents			
	Hazardous decomposition products:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.						
	11. TOXICOLOGICAL INFORMATION						
	This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture. <u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:						
	CAS-No.		emical Name	Effect	Ta	rget Organ	
	1309-37-1	Iron oxic	le	Systemic effects	Respiratory	system.	
				L INFORMATION	1		
	12. ECOLOGICAL INFORMATION						
	Persistence and degradability : No data available						
Environmental Toxicity : No data available							
	Bioaccumulation Potent	ial	: No data available				
	Additional advice		: No data availab	le			
			13. DISPOSAL C	ONSIDERATIONS			

: Where possible recycling is preferred to dispos

and disposal in accordance with applicable federal, state/provincial

PolyOne.

MATERIAL SAFETY DATA SHEET WB-10536-A RED ATH COATING

Version Number 1.5 Revision Date 10/04/2006 Page 5 of 6 Print Date 11/24/2011

	14. TRANS	SPORT INFORMATI	ON		
U.S. DOT Classification	: Refer to	specific regulation.			
ICAO/IATA (air) : Refer to specific regulation.					
IMO / IMDG (maritime) : Refer to specific regulation.					
	15. REGUL	ATORY INFORMAT	ION		
US Regulations:					
OSHA Status	: Classifie	d as hazardous based or	a components.		
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.					
US. EPA CERCLA Hazardo	us Substances (40) CFR 302)			
Not applicable					
California Proposition 65 SARA Title III Section 302 I Not applicable					
SARA Title III Section 313 Not applicable Canadian Regulations:	Foxic Chemicals:				
National Pollutant Re	lease Inventory (1		XXZ 1 (0/		
Chemical Name Poly(oxy-1,2-ethanediyl), .alpha(nonylphenyl)om	egahydroxy-	CAS-No. 9016-45-9	Weight % 0.10 - 1.00	NPRI ID# 178	
WHMIS Classification	on : Not cont	rolled.			

PolyOne.

MATERIAL SAFETY DATA SHEET **WB-10536-A RED ATH COATING**

Version Number 1.5 Revision Date 10/04/2006 Page 6 of 6 Print Date 11/24/2011

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.