PolvOne

MATERIAL SAFETY DATA SHEET ELECTROSTATIC SPRAY STANDARD BLACK

Version Number 1.2 Revision Date 03/30/2007 Page 1 of 6 Print Date 11/27/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone : Emergency telephone : number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	ELECTROSTATIC SPRAY STANDARD BLACK
Product code	:	FO20007167
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous, precipitated and gel	112926-00-8	1 - 5
Calcium carbonate	1317-65-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne

MATERIAL SAFETY DATA SHEET ELECTROSTATIC SPRAY STANDARD BLACK

Version Number 1.2 Revision Date 03/30/2007 Page 2 of 6 Print Date 11/27/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit		Not applicable
Lower explosion limit	:	Not applicable
Autoignition temperature	:	Not relevant
Suitable extinguishing media	:	
Suitable extinguishing media	•	Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne
Unusual Fire/Explosion		contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under
Hazards	·	fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume



MATERIAL SAFETY DATA SHEET ELECTROSTATIC SPRAY STANDARD BLACK

Version Number 1.2 Revision Date 03/30/2007 Page 3 of 6 Print Date 11/27/2011

condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. Storage Keep containers dry and tightly closed to avoid moisture absorption : and contamination. Keep in a dry, cool place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION No personal respiratory protective equipment normally required. If Respiratory protection : dusty conditions occur wear appropriate respiratory protection. **Eye/Face Protection** : Safety glasses with side-shields Hand protection Protective gloves : Skin and body protection : Long sleeved clothing Additional Protective Safety shoes : Measures General Hygiene Handle in accordance with good industrial hygiene and safety practice. : Considerations Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Silica, amorphous, precipitated and gel	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.8 mg/m3	Time Weighted Average (TWA):		Z3

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odour Melting point/range Boiling Point: Solid
powder, granular
BLACK
Very faint
Not determined
Not applicable

Evaporation rate Specific Gravity: Bulk density Vapour pressure Vapour density pH Not applicable
Not determined
Not applicable
Not applicable
Not applicable
Not applicable

PolyOne

MATERIAL SAFETY DATA SHEET ELECTROSTATIC SPRAY STANDARD BLACK

Version Number 1.2 Revision Date 03/30/2007

Page 4 of 6 Print Date *11/27/2011*

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: To avoid thermal decomposition, do not overheat. Keep away from oxidizing agents and open flame.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
112926-00-8	Silica, amorphous,	Irritant	Respiratory system, Eyes.
	precipitated and gel		
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eves, Skin, Respiratory system.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use
Bioaccumulation Potential	: no data available
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with

PolyOne.

MATERIAL SAFETY DATA SHEET ELECTROSTATIC SPRAY STANDARD BLACK

rsion Number 1.2 evision Date 03/30/2007		Page 5 of 6 Print Date <i>11/27/2011</i>
		applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA (air)	:	Not regulated for transportation.
IMO / IMDG (maritime)	:	Not regulated for transportation.
	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status		Classified as hazardous based on components.
TSCA Status		All components of this product are listed on or exempt from the TSCA
ISCA Status	•	Inventory.
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	Not applicable
05		
SARA Title III Section 302 Ex	trem	ely Hazardous Substance
Unless specific chemicals are i	denti	fied under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 To	oxic (Chemicals:
		fied under this section, this product is Not Applicable under this regulation
Canadian Regulations:		, , , , , , , , , , , , , , , , , , ,
National Pollutant Relea	ase Iı	iventory (NPRI)
	11 June	CAS-No. Weight % NPRI ID#

MATERIAL SAFETY DATA SHEET ELECTROSTATIC SPRAY STANDARD BLACK

Version Number 1.2 Revision Date 03/30/2007

_

Page 6 of 6 Print Date 11/27/2011

P<u>olyOne</u>

IIS Classification	:	D2B All of the components of this product are listed on the Canadian Inventories or are exempt. However, at least one component of this
	:	
		product is on the Canadian Non-Domestic Substances List (NDSL) Quantity use in Canada is restricted by regulations.
ntories:		
alia AICS	:	Not determined
IECS	:	Not determined
e EINECS	:	Not determined
ENCS	:	Not determined
KECI	:	Not determined
pines PICCS	:	Not determined
	KECI	KECI :

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.