

MATERIAL SAFETY DATA SHEET PX-19341-G OCEAN SPRAY 52P 0.015 HEX

Version Number 1.1 Revision Date 04/19/2004

Page 1 of 6 Print Date 11/14/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PX-19341-G OCEAN SPRAY 52P 0.015 HEX
Product code	:	FO20007616
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES



MATERIAL SAFETY DATA SHEET **PX-19341-G OCEAN SPRAY 52P 0.015 HEX**

ion Number 1.1 sion Date 04/19/2004	Page 2 Print Date 11/14/2
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 No data available No data available Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all
	possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or th soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize



MATERIAL SAFETY DATA SHEET PX-19341-G OCEAN SPRAY 52P 0.015 HEX

Version Number 1.1 Revision Date 04/19/2004 Page 3 of 6 Print Date 11/14/2011

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

accumulation of these materials.

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

There are no known hazardous components above regulatory thresholds in this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: liquidAppearance: ViscouColor: GREYOdor: Very fMelting point/range: Not apBoiling Point:: Not apWater solubility: Immis

: Viscous, liquid
: GREY
: Very faint
: Not applicable
: Not applicable
: Immiscible

Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH Not establishedNot determinedNot applicableNot determinedNot determined

: Not applicable

	10. STABILITY AND REACTIVITY	
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thern decomposition, do not overheat.	nal
Incompatible Materials	: Incompatible with strong acids and oxidizing agents. Avoid conta with acetal homopolymers and acetal copolymers during processing	



MATERIAL SAFETY DATA SHEET PX-19341-G OCEAN SPRAY 52P 0.015 HEX

Version Number 1.1 Revision Date 04/19/2004 Page 4 of 6 Print Date 11/14/2011

Hazardous decomposition products
Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

There are no known hazardous components above regulatory thresholds in this product.

of waste material has the responsibility for proper waste tion, transportation and disposal in accordance with e federal, state/provincial and local regulations.
vailable vailable AL CONSIDERATIONS ssible recycling is preferred to disposal or incineration. The of waste material has the responsibility for proper waste tion, transportation and disposal in accordance with e federal, state/provincial and local regulations. g is preferred when possible. The generator of waste materia sponsibility for proper waste classification, transportation sal in accordance with applicable federal, state/provincial
vailable AL CONSIDERATIONS ssible recycling is preferred to disposal or incineration. The of waste material has the responsibility for proper waste tion, transportation and disposal in accordance with e federal, state/provincial and local regulations. g is preferred when possible. The generator of waste materia sponsibility for proper waste classification, transportation sal in accordance with applicable federal, state/provincial
AL CONSIDERATIONS ssible recycling is preferred to disposal or incineration. The of waste material has the responsibility for proper waste tion, transportation and disposal in accordance with e federal, state/provincial and local regulations. g is preferred when possible. The generator of waste materia sponsibility for proper waste classification, transportation sal in accordance with applicable federal, state/provincial
ssible recycling is preferred to disposal or incineration. The of waste material has the responsibility for proper waste tion, transportation and disposal in accordance with e federal, state/provincial and local regulations. g is preferred when possible. The generator of waste materia sponsibility for proper waste classification, transportation sal in accordance with applicable federal, state/provincial
tion, transportation and disposal in accordance with e federal, state/provincial and local regulations. g is preferred when possible. The generator of waste materia sponsibility for proper waste classification, transportation sal in accordance with applicable federal, state/provincial
sponsibility for proper waste classification, transportation sal in accordance with applicable federal, state/provincial
PORT INFORMATION
pecific regulation.
pecific regulation.
pecific regulation.
ATORY INFORMATION

MATERIAL SAFETY DATA SHEET **PX-19341-G OCEAN SPRAY 52P 0.015 HEX**

Version Number 1.1 Revision Date 04/19/2004 Page 5 of 6 Print Date 11/14/2011

TSCA Status All components of this product are listed on or exempt from the TSCA : Inventory. US. EPA CERCLA Hazardous Substances (40 CFR 302) Not applicable California Proposition WARNING! This product contains a chemical known to the State of : California to cause cancer. 65 SARA Title III Section 302 Extremely Hazardous Substance Not applicable SARA Title III Section 313 Toxic Chemicals: Not applicable Canadian Regulations: National Pollutant Release Inventory (NPRI) Chemical Name CAS-No. Weight % NPRI ID# 7429-90-5 0.12 Aluminum 12 WHMIS Classification : Not controlled. DSL DSL status has not been determined. Quantity use in Canada may be : restricted by regulations. National Inventories: Australia AICS Not determined : China IECS Not determined : Europe EINECS Not determined : Japan ENCS Not determined : Korea KECI Not determined : : Not determined **Philippines PICCS 16. OTHER INFORMATION**



MATERIAL SAFETY DATA SHEET PX-19341-G OCEAN SPRAY 52P 0.015 HEX

Version Number 1.1 Revision Date 04/19/2004 Page 6 of 6 Print Date 11/14/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.