PolvOne

MATERIAL SAFETY DATA SHEET VBX3390LC LT CYPRESS WSB-M98D22-BGAA

Version Number 1.2 Revision Date 11/06/2009 Page 1 of 6 Print Date 1/9/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Product name:VBX3390LC LT CYPRESS WSB-M98D22-BGAAProduct code:FO20007837Chemical Name:MixtureCAS-No.:Mixture	Telephone Emergency telephone	 Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposu or accident). 	ıre
Chemical Name:MixtureCAS-No.:Mixture	Product name	: VBX3390LC LT CYPRESS WSB-M98D22-BGAA	
CAS-No. : Mixture	Product code	: FO20007837	
	Chemical Name	: Mixture	
	CAS-No.	: Mixture	
Product Use : Industrial Applications	Product Use	: Industrial Applications	

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET VBX3390LC LT CYPRESS WSB-M98D22-BGAA

Version Number 1.2 Revision Date 11/06/2009 Page 2 of 6 Print Date 1/9/2012

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: not applicable
Flammable Limits	
Upper explosion limit	: not applicable
Lower explosion limit	: not applicable
Autoignition temperature	: Not relevant
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne
Unuquel Fire/Explosion	contaminants.May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde
Unusual Fire/Explosion Hazards	fire conditions. Carbon dioxide (CO2), carbon monoxide (CO),
	oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET VBX3390LC LT CYPRESS WSB-M98D22-BGAA

Version Number 1.2 Revision Date 11/06/2009		Page 3 of 6 Print Date <i>1/9/2012</i>
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXPOS	SUI	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average	Total dust.	OSHA Z1A
		(TWA):		
	10 mg/m3	Time Weighted Average	as Ti	MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
		(STEL):		

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range
- solid
 powder, granular
 TAN
 very faint
 Not determined
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density
- Not applicable
 Not determined
 Not determined
 not applicable
 not applicable

MATERIAL SAFETY DATA SHEET VBX3390LC LT CYPRESS WSB-M98D22-BGAA

Version Number 1.2 Revision Date 11/06/2009 Page 4 of 6 Print Date 1/9/2012

PolyOne

Boiling Point: Water solubility		ot applicable soluble	рН	: not applicable
	1(). STABILITY	AND REACTIVITY	
Stability	:	Stable		
Hazardous Polymerization	:	Will not occur.		
Conditions to avoid	:		al decomposition, do no as and open flame.	t overheat. Keep away from
Incompatible Materials	:	-	-	dizing agents., Avoid contact opolymers during processing.
Hazardous decomposition products	:	(NOx), hydroge smoke are all p or more) above °C) may result	en chloride (HCl), other ossible. Prolonged heat 392 °F (200 °C) or shor	de (CO), oxides of nitrogen hazardous materials, and ing (approximately 30 minutes rt term heating at 482 °F (250 on and evolution of carbon

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

PolyOne

MATERIAL SAFETY DATA SHEET VBX3390LC LT CYPRESS WSB-M98D22-BGAA

Version Number 1.2 Revision Date 11/06/2009 Page 5 of 6 Print Date 1/9/2012

: Not readily biodegradable.
: Adverse ecological impact is not known or expected under normal use.
: no data available
: no data available
13. DISPOSAL CONSIDERATIONS
: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
14. TRANSPORT INFORMATION
: Not regulated for transportation.
: Not regulated for transportation.
: Not regulated for transportation.
15. REGULATORY INFORMATION
: Classified as hazardous based on components.
: All components of this product are listed on or exempt from the TSCA Inventory.
ubstances (40 CFR 302)
: WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
ı

MATERIAL SAFETY DATA SHEET VBX3390LC LT CYPRESS WSB-M98D22-BGAA

Version Number 1.2 Revision Date 11/06/2009

Page 6 of 6 Print Date 1/9/2012

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

Chemical Name			CAS-No.	Weight	NPRI ID#
Miscellaneous Zinc Compoun	ds		Not Available	0.10 - 1.00	241
WHMIS Classification DSL	:		s of this product are (DSL) or are exem		n Domestic
ational Inventories:					
Australia AICS	:	Not determined			
China IECS	:	Not determined			
Europe EINECS	:	Listed			
Japan ENCS	:	Not determined			
Korea KECI	:	Not determined			
Philippines PICCS	:	Not determined			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.