### MATERIAL SAFETY DATA SHEET DB3809 CLEAR FLAME RETARDANT

Version Number 1.0 Revision Date 04/27/2004 Page 1 of 6 Print Date 11/14/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone <b>Emergency telephone number</b>	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DB3809 CLEAR FLAME RETARDANT
Product code	:	FO20008156
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Triphenyl phosphate	115-86-6	1 - 5

#### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



## MATERIAL SAFETY DATA SHEET DB3809 CLEAR FLAME RETARDANT

Version Number 1.0 Revision Date 04/27/2004 Page 2 of 6 Print Date 11/14/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
<b>F</b> 1	
Flammable Limits Upper explosion limit	: No data available
sower explosion limit	: No data available
Autoignition temperature	: Not applicable
Suitable extinguishing media	**
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne
	contaminants.
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



## MATERIAL SAFETY DATA SHEET DB3809 CLEAR FLAME RETARDANT

Version Number 1.0 Revision Date 04/27/2004 Page 3 of 6 Print Date 11/14/2011

		fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXPOS	UR	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(a)		

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Triphenyl phosphate	3 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	3 mg/m3	PEL:	Dust.	OSHA Z1

9.	PHYSICAL AND CHEM	IICAL PROPERTIES	
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	<ul> <li>liquid</li> <li>Viscous, liquid</li> <li>TRANSPARENT</li> <li>Very faint</li> <li>Not applicable</li> <li>Not applicable</li> <li>Immiscible</li> </ul>	Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH	<ul> <li>Not established</li> <li>Not determined</li> <li>Not applicable</li> <li>Not determined</li> <li>Not determined</li> <li>Not applicable</li> </ul>
	10. STABILITY AND	REACTIVITY	
Stability	: Stable.		
	: Will not occur.		



### MATERIAL SAFETY DATA SHEET DB3809 CLEAR FLAME RETARDANT

Version Number 1.0 Revision Date 04/27/2004 Page 4 of 6 Print Date *11/14/2011* 

Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
115-86-6	Triphenyl phosphate	Systemic effects	Respiratory system, blood and blood forming system, central
			nervous system (CNS).

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
115-86-6	Triphenyl phosphate	Oral LD50	3,500 mg/kg	rat
		Dermal LD50	> 7,900 mg/kg	rabbit

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.



## MATERIAL SAFETY DATA SHEET DB3809 CLEAR FLAME RETARDANT

Version Number 1.0 Revision Date 04/27/2004 Page 5 of 6 Print Date 11/14/2011

Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.						
	1	4. TRANSPORT INF	ORMATION			]
U.S. DOT Classification	:	Refer to specific regul				
ICAO/IATA (air)	:	Refer to specific regul	lation.			
IMO / IMDG (maritime)	:	Refer to specific regul	lation.			
	15	. REGULATORY IN	FORMATION			
US Regulations:						
OSHA Status	:	Classified as hazardou	is based on compo	nents.		
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.					
US. EPA CERCLA Hazardous S	Subs	stances (40 CFR 302)				
Not applicable						
California Proposition 65	:	WARNING! This pro California to cause ca		emical know	on to the State of	
SARA Title III Section 302 Extr	em	ely Hazardous Substand	ce			
Not applicable						
SARA Title III Section 313 Tox	ic C	Chemicals:				
Not applicable Canadian Regulations:						
National Pollutant Releas	e Ir	ventory (NPRI)	CAS No	Weight 0/		
misc00031 - Misc Zinc Cpd	1's		CAS-No. Not Available	Weight % 0.17	NPRI ID# 241	

POLYONE CORPORAT	FI(	ON PolyOr	<u>10</u> .
MATERIAL SAFETY DATA SHEET			
DB3809 CLEAR FLAM	EI	RETARDANT	
Version Number 1.0 Revision Date 04/27/2004		Print Date	Page 6 of 6 11/14/2011
WHMIS Classification	:	D2B	
WHMIS Ingredient Disc	losu	ire List	
CAS-No. 115-86-6			
DSL	:	All of the components of this product are listed on the Cana Inventories or are exempt. However, at least one component product is on the Canadian Non-Domestic Substances List ( Quantity use in Canada is restricted by regulations.	t of this
National Inventories:			
Australia AICS	:	Not determined	
China IECS	:	Not determined	
Europe EINECS	:	Listed	
Japan ENCS	:	Not determined	
Korea KECI	:	Not determined	
Philippines PICCS	:	Not determined	
16. OTHER INFORMATION			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.