

MATERIAL SAFETY DATA SHEET

DB3565A BLACK

Version Number 1.0 Revision Date 05/06/2004 Page 1 of 7 Print Date *11/14/2011*

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DB3565A BLACK
Product code	:	FO20008263
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Antimony trioxide	1309-64-4	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET **DB3565A BLACK**

Version Number 1.0 Revision Date 05/06/2004 Page 2 of 7 Print Date 11/14/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature Suitable extinguishing media	 No data available No data available Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



MATERIAL SAFETY DATA SHEET **DB3565A BLACK**

sion Number 1.0 ision Date 05/06/2004				Print D	Page ate 11/14
	Р	ume condensates may con eriodically clean hoods, d ccumulation of these mate	lucts, and other sur		
Storage		Leep containers dry and tig nd contamination. Store i			absorption
8. E	XPOSURE	CONTROLS / PERSON	NAL PROTECTI	ON	
Respiratory protection	: N	lo personal respiratory pro	otective equipment	t normally r	equired.
Eye/Face Protection	: S	afety glasses with side-sh	iields.		
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		landle in accordance with Vash hands before breaks			afety practi
Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.					
Exposure limit(s)					
Components	Value	Exposure time	Exposu	re type	List:
Antimony trioxide	0.5 mg/m3	PEL:	as		OSHA Z
	0.5 mg/m3	Time Weighted Avera (TWA):	as s	Sb	ACGIH
	9. PHYSIC	CAL AND CHEMICAL	PROPERTIES		
Form	: liqui	A F	vaporation rate	· Not	established
Appearance			pecific Gravity:		determined
Color	: BLA		Sulk density		applicable
Odor	: Very		apor pressure		determined
Melting point/range			apour density		determined
Boiling Point:			H	: Not	applicable
Water solubility	: Imm	iscible			
			CTIVITY		
	10. 5	STABILITY AND REA			
Stability		table.			



MATERIAL SAFETY DATA SHEET **DB3565A BLACK**

Version Number 1.0 Page 4 of 7 Revision Date 05/06/2004 Print Date 11/14/2011 Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible Materials : Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing. Hazardous decomposition Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen : (NOx), hydrogen chloride (HCl), other hazardous materials, and products smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1309-64-4	Antimony trioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:



MATERIAL SAFETY DATA SHEET **DB3565A BLACK**

Version Number 1.0 Revision Date 05/06/2004

Page 5 of 7 Print Date 11/14/2011

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

Persistence and degradability	: Not re	adily biodegradabl	le.	
Environmental Toxicity	: Enviro whole.	•	as not been establishe	d for this mixture as a
Bioaccumulation Potential	: No dat	ta available		
Additional advice	: No dat	ta available		
	13. DISP	OSAL CONSIDE	ERATIONS	
Product	genera classif	tor of waste mater ication, transporta	g is preferred to dispos ial has the responsibil tion and disposal in ac provincial and local re	cordance with
Contaminated packaging	has the and di	e responsibility for	hen possible. The gen proper waste classific ce with applicable fed	
	14. TRA	NSPORT INFOR	RMATION	
	Defe	······		
U.S. DOT Classification		to specific regulati		
ICAO/IATA (air)	: Refer	to specific regulati	lon.	
IMO / IMDG (maritime)	: Refer	to specific regulati	on.	
	15. REGU	JLATORY INFO	RMATION	
US Regulations:				
OSHA Status	: Classi	fied as hazardous t	based on components.	
TSCA Status	: All co Invent	1 1	product are listed on or	exempt from the TSC
US. EPA CERCLA Hazardo	us Substances	(40 CFR 302)		
Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product



MATERIAL SAFETY DATA SHEET **DB3565A BLACK**

Version Number 1.0 Revision Date 05/06/2004

Page 6 of 7 Print Date 11/14/2011

		1	WARNING! This product contains a chemical known to the State of California to cause cancer., WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
--	--	---	--

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
ANTIMONY COMPOUNDS	1309-64-4	3.99

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Antimony trioxide	1309-64-4	3.99	17

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
1309-64-4	

DSL

: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined



MATERIAL SAFETY DATA SHEET

DB3565A BLACK

Version Number 1.0 Revision Date 05/06/2004 Page 7 of 7 Print Date 11/14/2011

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.