## MATERIAL SAFETY DATA SHEET STAN-TONE MB-25848 GREY

Version Number 1.0 Revision Date 02/03/2005

Page 1 of 6 Print Date 11/17/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	STAN-TONE MB-25848 GREY
Product code	:	FO20008980
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

## 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	1 - 5
Iron oxide	1309-37-1	1 - 5
Stearic acid	57-11-4	1 - 5
Kaolin	1332-58-7	5 - 10
Titanium dioxide	13463-67-7	30 - 60

## **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

## POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> </ul>
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

## MATERIAL SAFETY DATA SHEET STAN-TONE MB-25848 GREY

Version Number 1.0 Revision Date 02/03/2005 Page 2 of 6 Print Date 11/17/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ol> <li>Not applicable</li> <li>Not applicable</li> <li>Not relevant</li> <li>water spray, dry powder, foam, carbon dioxide (CO2).</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ol>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat

<u>PolyOne</u>

# MATERIAL SAFETY DATA SHEET STAN-TONE MB-25848 GREY

Version Number 1.0 Revision Date 02/03/2005

\_\_\_\_

Page 3 of 6 Print Date 11/17/2011

Sto	rage	:	only in areas with appropriate exhaust ventilation. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
	8. EXPOS	UR	RE CONTROLS / PERSONAL PROTECTION
Res	spiratory protection	:	No personal respiratory protective equipment normally required when handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this material.
Eye	e/Face Protection	:	Safety glasses with side-shields.
Har	nd protection	:	Protective gloves.
Ski	n and body protection	:	Long sleeved clothing.
	ditional Protective asures	:	Safety shoes.
	neral Hygiene nsiderations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Eng	gineering measures	:	Heat only in areas with appropriate exhaust ventilation. Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Iron oxide	5 mg/m3	Time Weighted Average (TWA):	Dust and fume. as Fe	ACGIH
Kaolin	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	2 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
Stearic acid	10 mg/m3	Time Weighted Average (TWA):	Total dust. as stearates	ACGIH
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance SolidPellets, Slabs, sheets

Evaporation rate Specific Gravity: Not applicableNot determined

## MATERIAL SAFETY DATA SHEET STAN-TONE MB-25848 GREY

Version Number 1.0 Revision Date 02/03/2005 Page 4 of 6 Print Date 11/17/2011

Color Odor Melting point/range Boiling Point: Water solubility	: GREYBulk density: Not established: Characteristic rubber odorVapor pressure: Not applicable: Not determinedVapour density: Not applicable: Not applicablepH: Not applicable: Insoluble: Not applicable	
	10. STABILITY AND REACTIVITY	
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.	
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.	
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.	

## 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
57-11-4	Stearic acid	Irritant	Eyes, Skin.
1332-58-7	Kaolin	Systemic effects	Respiratory system, digestive
			system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
57-11-4	Stearic acid			
		Dermal LD50	> 5 gm/kg	rabbit

## 12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.

polymer matrix.

:

Environmental Toxicity

Chemicals are not readily available as they are bound within the

vironinentai roxicity

4/6

PolyOne

# MATERIAL SAFETY DATA SHEET **STAN-TONE MB-25848 GREY**

Version Number 1.0 Revision Date 02/03/2005 Page 5 of 6 Print Date 11/17/2011

	polymer matrix.
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. T generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste mater has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Not regulated for transportation.
IMO / IMDG (maritime)	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSC Inventory.
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)
Not applicable	
California Proposition 65	n : This product does not contain a substance listed by California Prop
SARA Title III Section 302 I Not applicable	Extremely Hazardous Substance
SARA Title III Section 313 7	Coxic Chemicals:

PolyOne

# MATERIAL SAFETY DATA SHEET STAN-TONE MB-25848 GREY

Version Number 1.0 Revision Date 02/03/2005 Page 6 of 6 Print Date 11/17/2011

Not applicable Canadian Regulations:	
National Pollutant Relea	ase Inventory (NPRI)
Not applicable	
WHMIS Classification	: D2A
WHMIS Ingredient Disc	closure List
CAS-No. 1309-37-1 57-11-4	
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS	: Listed
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Listed
Philippines PICCS	: Listed
	16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.