

**POLYONE CORPORATION****MATERIAL SAFETY DATA SHEET****STAN-TONE MB-17429 BROWN**Version Number 1.3  
Revision Date 03/17/2014Page 1 of 7  
Print Date 3/19/2014**1. PRODUCT AND COMPANY IDENTIFICATION****POLYONE CORPORATION**  
8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone : 1 (440) 930-1000 or 1 (866) POLYONE  
Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure  
number or accident).

Product name : STAN-TONE MB-17429 BROWN  
Product code : FO20008985  
Chemical Name : Mixture  
CAS-No. : Mixture  
Product Use : Industrial Applications

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

Components	CAS-No.	Weight percent
Silica, amorphous	7631-86-9	1 - 5
Iron oxide	1309-37-1	5 - 10
Calcium carbonate	471-34-1	10 - 30

**3. HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

**POTENTIAL HEALTH EFFECTS****Routes of Exposure:** : Inhalation, Ingestion, Skin contact**Acute exposure**

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.

Ingestion : May be harmful if swallowed.

Eyes : Resin particles, like other inert materials, are mechanically irritating to eyes.

Skin : Experience shows no unusual dermatitis hazard from routine handling.

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**STAN-TONE MB-17429 BROWN**

Version Number 1.3  
Revision Date 03/17/2014

Page 2 of 7  
Print Date 3/19/2014

**Chronic exposure** : Refer to Section 11 for Toxicological Information.

**Medical Conditions  
Aggravated by Exposure:** : None known.

**4. FIRST AID MEASURES**

- Inhalation** : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
- Ingestion** : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
- Eyes** : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
- Skin** : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

**5. FIREFIGHTING MEASURES**

- Flash point** : not applicable
- Flammable Limits**
- Upper explosion limit** : not applicable
  - Lower explosion limit** : not applicable
- Auto-ignition temperature** : Not relevant
- Suitable extinguishing media** : Water spray, Dry powder, Foam, Carbon dioxide (CO<sub>2</sub>).
- Special Fire Fighting Procedures** : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
- Unusual Fire/Explosion Hazards** : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), other hazardous materials, and smoke are all possible.

**6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions** : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
- Environmental precautions** : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
- Methods for cleaning up** : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

**7. HANDLING AND STORAGE**

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**STAN-TONE MB-17429 BROWN**

Version Number 1.3  
Revision Date 03/17/2014

Page 3 of 7  
Print Date 3/19/2014

- Handling : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
- Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

- Respiratory protection : No personal respiratory protective equipment normally required when handling the product itself. See "Engineering Measures" section below for precautions to be taken when heating or processing this material.
- Eye/Face Protection : Safety glasses with side-shields
- Hand protection : Protective gloves
- Skin and body protection : Long sleeved clothing
- Additional Protective Measures : Safety shoes
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
- Engineering measures : Heat only in areas with appropriate exhaust ventilation. Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.

Exposure limit(s)

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**STAN-TONE MB-17429 BROWN**

Version Number 1.3

Revision Date 03/17/2014

Page 4 of 7

Print Date 3/19/2014

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	OSHA Z1A
	15 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
	5 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	10 mg/m3	Recommended exposure limit (REL):	Total	NIOSH
Iron oxide	10 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
Silica, amorphous	6 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Form	: solid	Evaporation rate	: Not applicable
Appearance	: pellets, Slabs, sheets	Specific Gravity	: Not determined
Colour	: BROWN	Bulk density	: Not established
Odour	: Characteristic rubber odor	Vapour pressure	: not applicable
Melting point/range	: Not determined	Vapour density	: not applicable
Boiling Point:	: not applicable	pH	: not applicable
Water solubility	: insoluble		

**10. STABILITY AND REACTIVITY**

Stability	: Stable
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**STAN-TONE MB-17429 BROWN**

Version Number 1.3  
Revision Date 03/17/2014

Page 5 of 7  
Print Date 3/19/2014

Incompatible Materials : Incompatible with strong acids and oxidizing agents.

Hazardous decomposition products : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), other hazardous materials, and smoke are all possible.

**11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
471-34-1	Calcium carbonate	Irritant	Eyes, Skin.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
471-34-1	Calcium carbonate	Oral LD50Oral LD50Oral LD50	6,450 mg/kg6,450 mg/kg6,450 mg/kg	ratratmouse

**12. ECOLOGICAL INFORMATION**

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Chemicals are not readily available as they are bound within the polymer matrix.

Bioaccumulation Potential : Chemicals are not readily available as they are bound within the polymer matrix.

Additional advice : not applicable

**13. DISPOSAL CONSIDERATIONS**

Product : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal,



**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**STAN-TONE MB-17429 BROWN**

Version Number 1.3  
Revision Date 03/17/2014

Page 6 of 7  
Print Date 3/19/2014

state/provincial and local regulations.

**14. TRANSPORT INFORMATION**

U.S. DOT Classification : Not regulated for transportation.  
ICAO/IATA : Not regulated for transportation.  
IMO/IMDG (maritime) : Not regulated for transportation.

**15. REGULATORY INFORMATION**

US Regulations:

OSHA Status : Classified as hazardous based on components.  
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition : Not applicable  
65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

not applicable

WHMIS Classification : Not controlled.  
DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**STAN-TONE MB-17429 BROWN**

Version Number 1.3  
Revision Date 03/17/2014

Page 7 of 7  
Print Date 3/19/2014

National Inventories:

Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

**16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.