MATERIAL SAFETY DATA SHEET STAN-TONE HCC-25927 BLACK

Version Number 1.0 Revision Date 08/05/2004

Page 1 of 6 Print Date 11/15/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:number	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	STAN-TONE HCC-25927 BLACK
Product code :	FO20009581
Chemical Name :	Mixture
CAS-No.	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	10 - 30
Carbon black	1333-86-4	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET STAN-TONE HCC-25927 BLACK

Version Number 1.0 Revision Date 08/05/2004 Page 2 of 6 Print Date 11/15/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. Seek medical attention if necessary.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature Suitable extinguishing media	 No data available No data available Not applicable Carbon dioxide blanket, water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
Hazards	(NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Prolonged heating may result in product degradation.



MATERIAL SAFETY DATA SHEET STAN-TONE HCC-25927 BLACK

Version Number 1.0 Revision Date 08/05/2004 Page 3 of 6 Print Date 11/15/2011

Storage		: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.				
8. I	EXPOSURE	CONTROLS / PERSONAL	L PROTECTION			
Respiratory protection	: U	nder normal handling condit	ions a respirator may not b	e required.		
Eye/Face Protection : Safety glasses with side-shields.						
Hand protection	: P	rotective gloves.				
Skin and body protection	: L	ong sleeved clothing.				
Additional Protective : Safety shoes. Measures						
General Hygiene Considerations		andle in accordance with goo Vash hands before breaks and		afety practice.		
F · · ·	. ц	[• • • • • • • •	D '1		
Engineering measures		ppropriate exhaust ventilation	priate exhaust ventilation.	Provide		
Engineering measures Exposure limit(s)				Provide		
Exposure limit(s)		ppropriate exhaust ventilation	n at machinery.	List:		
	aı Value		at machinery.			
Exposure limit(s) Components	aı Value 5 mg/m3	ppropriate exhaust ventilation Exposure time	n at machinery.	List:		
Exposure limit(s) Components	aı Value	Exposure time PEL: PEL: Time Weighted Average	at machinery. Exposure type Respirable fraction.	List: OSHA Z1		
Exposure limit(s) Components Calcium carbonate	Value 5 mg/m3 15 mg/m3	ppropriate exhaust ventilation Exposure time PEL: PEL:	at machinery. Exposure type Respirable fraction. Total dust. Total dust. as carbon	List: OSHA Z1 OSHA Z1		
Exposure limit(s) Components Calcium carbonate	ap Value 5 mg/m3 15 mg/m3 3.5 mg/m3 3.5 mg/m3	Exposure time PEL: PEL: Time Weighted Average (TWA):	at machinery. Exposure type Respirable fraction. Total dust. Total dust. as carbon black Total dust. as carbon black	List: OSHA Z1 OSHA Z1 ACGIH		
Exposure limit(s) Components Calcium carbonate Carbon black	44 Value 5 mg/m3 15 mg/m3 3.5 mg/m3 3.5 mg/m3 9. PHYSIC	Exposure time PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR	 Exposure type Respirable fraction. Total dust. Total dust. as carbon black Total dust. as carbon black 	List: OSHA Z1 OSHA Z1 ACGIH OSHA Z1		
Exposure limit(s) Components Calcium carbonate Carbon black Form	ap Value 5 mg/m3 15 mg/m3 3.5 mg/m3 3.5 mg/m3 9. PHYSIC : liquio	Exposure time PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR d Evap	Exposure type Respirable fraction. Total dust. Total dust. as carbon black Total dust. as carbon black	List: OSHA Z1 OSHA Z1 ACGIH OSHA Z1 established		
Exposure limit(s) Components Calcium carbonate Carbon black	ap Value 5 mg/m3 15 mg/m3 3.5 mg/m3 3.5 mg/m3 9. PHYSIC : liquid : liquid	Exposure time PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR d Evap d, Viscous liquid Spec	Exposure type Respirable fraction. Total dust. Total dust. as carbon black Total dust. as carbon black OPERTIES oration rate : Not	List: OSHA Z1 OSHA Z1 ACGIH OSHA Z1		
Exposure limit(s) Components Calcium carbonate Carbon black Form Appearance	ap Value 5 mg/m3 15 mg/m3 3.5 mg/m3 3.5 mg/m3 3.5 mg/m3 9. PHYSIC : liquid : liquid dispe	Exposure time PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR d Evap d, Viscous liquid Spectors	Exposure type Respirable fraction. Total dust. Total dust. as carbon black Total dust. as carbon black OPERTIES oration rate : Not ific Gravity: : Not	List: OSHA Z1 OSHA Z1 ACGIH OSHA Z1 established determined		
Exposure limit(s) Components Calcium carbonate Carbon black Form Appearance Color	ap Value 5 mg/m3 15 mg/m3 3.5 mg/m3 3.5 mg/m3 3.5 mg/m3 9. PHYSIC : liquid dispe : BLA	Exposure time PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR d Evap d, Viscous liquid Spec ersion CK Bulk	Exposure type Respirable fraction. Total dust. Total dust. as carbon black Total dust. as carbon black OPERTIES OPERTIES ific Gravity: : Not	List: OSHA Z1 OSHA Z1 ACGIH OSHA Z1 established		
Exposure limit(s) Components Calcium carbonate Carbon black Form Appearance Color Odor	ap Value 5 mg/m3 15 mg/m3 3.5 mg/m3 3.5 mg/m3 3.5 mg/m3 9. PHYSIC : liquid dispe : BLA : Very	Exposure time PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR d Evap d, Viscous liquid Spec ersion CK Bulk faint Vapo	Exposure type Respirable fraction. Total dust. Total dust. as carbon black Total dust. as carbon black OPERTIES oration rate : Not ific Gravity: : Not density : Not or pressure : Not	List: OSHA Z1 OSHA Z1 ACGIH OSHA Z1 established determined applicable		
Exposure limit(s) Components Calcium carbonate Carbon black Form Appearance Color	ap Value 5 mg/m3 15 mg/m3 3.5 mg/m3 3.5 mg/m3 3.5 mg/m3 9. PHYSIC : liquid dispe : BLA : Very : Not a	Exposure time PEL: PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR d Evap d, Viscous liquid Spec ersion CK Bulk faint Vapo	Exposure type Respirable fraction. Total dust. Total dust. as carbon black Total dust. as carbon black OPERTIES oration rate : Not ific Gravity: density : Not or pressure wordensity : Not or density	List: OSHA Z1 OSHA Z1 ACGIH OSHA Z1 established determined applicable determined		

10. STABILITY AND REACTIVITY

Stability

: Stable.

Hazardous Polymerization

: Will not occur.

MATERIAL SAFETY DATA SHEET STAN-TONE HCC-25927 BLACK

Version Number 1.0 Revision Date 08/05/2004 Page 4 of 6 Print Date 11/15/2011

Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	:	No data available

PolyOne

MATERIAL SAFETY DATA SHEET STAN-TONE HCC-25927 BLACK

Version Number 1.0 Revision Date 08/05/2004 Page 5 of 6 Print Date 11/15/2011

Additional advice	:	No data available
	13	. DISPOSAL CONSIDERATIONS
Product	:	Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Refer to specific regulation.
ICAO/IATA (air)	:	Refer to specific regulation.
IMO / IMDG (maritime)	:	Refer to specific regulation.
	15.	REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous Su	ıbs	tances (40 CFR 302)
Not applicable		
California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 Extre	me	ely Hazardous Substance
Not applicable		
SARA Title III Section 313 Toxic	c C	hemicals:
Not applicable Canadian Regulations:		

PolyOne

MATERIAL SAFETY DATA SHEET STAN-TONE HCC-25927 BLACK

Version Number 1.0 Revision Date 08/05/2004 Page 6 of 6 Print Date 11/15/2011

National Pollutant Release Inventory (NPRI)				
Not applicable				
WHMIS Classification	:	D2A		
WHMIS Ingredient Disc	losu	re List		
CAS-No. 1333-86-4				
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.		
National Inventories:				
Australia AICS	:	Listed		
China IECS	:	Listed		
Europe EINECS	:	Listed		
Japan ENCS	:	Not determined		
Korea KECI	:	Listed		
Philippines PICCS	:	Listed		
		16. OTHER INFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.