MATERIAL SAFETY DATA SHEET

DB3825 BLACK

Version Number 1.0 Revision Date 08/18/2004 Page 1 of 6 Print Date 11/15/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DB3825 BLACK
Product code	:	FO20009647
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Misc00032 - Miscellaneous Irriant	Not Available	1 - 5
Vinyl acetate	108-05-4	0.1 - 1

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET **DB3825 BLACK**

Version Number 1.0 Revision Date 08/18/2004 Page 2 of 6 Print Date 11/15/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature Suitable extinguishing media	 No data available No data available Not applicable Carbon dioxide blanket, water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



MATERIAL SAFETY DATA SHEET **DB3825 BLACK**

sion Date 08/18/2004			Print D	Page Date 11/15
	F	ume condensates may contain Periodically clean hoods, ducts accumulation of these material	s, and other surfaces to m	
Storage		Keep containers dry and tightly and contamination. Store in a		e absorptior
8. E	XPOSURE	CONTROLS / PERSONAI	PROTECTION	
Respiratory protection	: 1	No personal respiratory protec	tive equipment normally	required.
Eye/Face Protection	: \$	afety glasses with side-shield	s.	
Hand protection	: F	Protective gloves.		
Skin and body protection	: I	long sleeved clothing.		
Additional Protective Measures	: 5	Safety shoes.		
General Hygiene Considerations		Handle in accordance with goo Wash hands before breaks and		safety practi
Engineering measures		Heat only in areas with approp ppropriate exhaust ventilatior		Provide
Exposure limit(s)			-	
Components	Value	Exposure time	Exposure type	List:
Components Vinyl acetate	Value 10 ppm	Exposure time Time Weighted Average (TWA):	Exposure type	
		Time Weighted Average		ACGIH
	10 ppm 15 ppm	Time Weighted Average (TWA): Short Term Exposure Limit		ACGIH
Vinyl acetate	10 ppm 15 ppm 9. PHYSI : liqui	Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR	OPERTIES oration rate : Not	ACGIH ACGIH
Vinyl acetate	10 ppm 15 ppm 9. PHYSI : liqui	Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR id Evap cous, liquid Speci	OPERTIES Dration rate : Not fic Gravity: : Not	ACGIH ACGIH t established t determined
Vinyl acetate Form Appearance	10 ppm 15 ppm 9. PHYSI : liqui : Visc : BLA	Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR id Evap cous, liquid Special ACK Bulk	OPERTIES oration rate : Not fic Gravity: : Not density : Not	ACGIH ACGIH t established t determined t applicable
Vinyl acetate Form Appearance Color Odor Melting point/range	10 ppm 15 ppm 9. PHYSI : liqui : Visc : BLA : Ver : Not	Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR id Evap id Speci ACK Bulk y faint Vapo applicable Vapo	OPERTIES Diration rate : Not fic Gravity: : Not density : Not r pressure : Not ur density : Not	ACGIE ACGIE t established t determined t determined t determined t determined
Vinyl acetate Form Appearance Color Odor Melting point/range Boiling Point:	10 ppm 15 ppm 9. PHYSI : liqui : Visc : BLA : Very : Not : Not	Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR id Evap cous, liquid Speci ACK Bulk y faint Vapo applicable pH	OPERTIES Diration rate : Not fic Gravity: : Not density : Not r pressure : Not ur density : Not	ACGIH ACGIH t established t determined t applicable t determined
Vinyl acetate Form Appearance Color Odor Melting point/range	10 ppm 15 ppm 9. PHYSI : liqui : Visc : BLA : Very : Not : Not	Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR id Evap id Speci ACK Bulk y faint Vapo applicable Vapo	OPERTIES Diration rate : Not fic Gravity: : Not density : Not r pressure : Not ur density : Not	ACGIE ACGIE t established t determined t determined t determined t determined
Vinyl acetate Form Appearance Color Odor Melting point/range Boiling Point:	10 ppm 15 ppm 9. PHYSI : liqui : Visc : BLA : Very : Not : Not : Imm	Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR id Evap cous, liquid Speci ACK Bulk y faint Vapo applicable pH	OPERTIES Diration rate : Not fic Gravity: : Not density : Not r pressure : Not ur density : Not : Not	ACGIH ACGIH t established t determined t applicable t determined t determined
Vinyl acetate Form Appearance Color Odor Melting point/range Boiling Point:	10 ppm 15 ppm 9. PHYSI : liqui : Visc : BLA : Very : Not : Not : Imm 10. 5	Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PR id Evap cous, liquid Special ACK Bulk y faint Vapo applicable pH niscible Vapo	OPERTIES Diration rate : Not fic Gravity: : Not density : Not r pressure : Not ur density : Not : Not	ACGIH ACGIH t established t determined t applicable t determined t determined



MATERIAL SAFETY DATA SHEET **DB3825 BLACK**

Version Number 1.0 Revision Date 08/18/2004		Page 4 of 6 Print Date <i>11/15/2011</i>
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
Not Available	Misc00032 -	sensitizer	Skin.
	Miscellaneous Irriant		
		Irritant	Eyes, Skin.
108-05-4	Vinyl acetate	Irritant	Eyes, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
108-05-4	Vinyl acetate	LC50	11400 mg/m3	rat
		Oral LD50	2,920 mg/kg	rat
		Dermal LD50	2,335 mg/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.			IARC	NTP
108-05-4	Vinyl acetate	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

PolyOne.

MATERIAL SAFETY DATA SHEET **DB3825 BLACK**

Version Number 1.0 Revision Date 08/18/2004 Page 5 of 6 Print Date 11/15/2011

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. Th generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	

MATERIAL SAFETY DATA SHEET **DB3825 BLACK**

Version Number 1.0 Revision Date 08/18/2004

Page 6 of 6 Print Date 11/15/2011

California Proposition:WARNING! This product contains a chemical known to the State of
California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
VINYL ACETATE MONOMERVINYL ACETATE	108-05-4	0.19

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight %	NPRI ID#
Vinyl acetate	108-05-4	0.19	237

WHMIS Classification : D1B

DSL

: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.