# MATERIAL SAFETY DATA SHEET

# FB455A NEUTRAL

Version Number 1.0 Revision Date 08/25/2004

Page 1 of 6 Print Date 11/15/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	FB455A NEUTRAL
Product code	:	FO20009713
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

# 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Azodicarbonamide	123-77-3	1 - 5
Magnesium carbonate	546-93-0	1 - 5
Calcium carbonate	1317-65-3	10 - 30

### **3. HAZARDS IDENTIFICATION**

### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



# MATERIAL SAFETY DATA SHEET

# FB455A NEUTRAL

Version Number 1.0 Revision Date 08/25/2004 Page 2 of 6 Print Date 11/15/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>No data available</li> <li>No data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



# MATERIAL SAFETY DATA SHEET FB455A NEUTRAL

sion Number 1.0 ision Date 08/25/2004			Print D	Page 3 ate 11/15/2		
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.					
Storage		eep containers dry and tightly nd contamination. Store in a c		e absorption		
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION			
Respiratory protection	: N	o personal respiratory protecti	ve equipment normally r	required.		
Eye/Face Protection	: S	afety glasses with side-shields				
Hand protection	: P	: Protective gloves.				
Skin and body protection	: Long sleeved clothing.					
Additional Protective Measures	: Safety shoes.					
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.					
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.					
Exposure limit(s)						
Components	Value	Exposure time	Exposure type	List:		
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1		
	15 mg/m3	PEL:	Total dust.	OSHA Z1		
Magnesium carbonate	10 mg/m3	Time Weighted Average (TWA):	Dust.	ACGIH		
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1		
	15 mg/m3	PEL:	Total dust.	OSHA Z1		

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility

# liquid Viscous, liquid NO PIGMENT Very faint Not applicable Not applicable Immiscible

Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH Not established
Not determined
Not applicable
Not determined
Not determined
Not applicable

# **10. STABILITY AND REACTIVITY**

**POLYONE CORPORATION** 



# MATERIAL SAFETY DATA SHEET FB455A NEUTRAL

Version Number 1.0 Revision Date 08/25/2004

Page 4 of 6 Print Date 11/15/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

## 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
123-77-3	Azodicarbonamide	sensitizer	Respiratory system.
546-93-0	Magnesium carbonate	Irritant	Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
123-77-3	Azodicarbonamide	LC50	200 mg/l	rat
		Oral LD50	> 6,400 mg/kg	rat
		Dermal LD50	> 2,000 mg/kg	rabbit

### Additional Health Hazard Information:

Azodicarbonamide 123-77-3 Sensitizer to the respiratory system with repeated minimal inhalation. While no chronic health problems have been identified, individuals with respiratory problems should avoid inhalation exposure to this material.

# **12. ECOLOGICAL INFORMATION**

Persistence and degradability

: Not readily biodegradable.



# MATERIAL SAFETY DATA SHEET FB455A NEUTRAL

Version Number 1.0 Revision Date 08/25/2004 Page 5 of 6 Print Date 11/15/2011

Environmental Toxicity	Environmental toxicity has not been e whole.	stablished for this mixture as a
Bioaccumulation Potential	No data available	
Additional advice	No data available	
	3. DISPOSAL CONSIDERATIONS	
Product	Where possible recycling is preferred generator of waste material has the re- classification, transportation and disp applicable federal, state/provincial and	sponsibility for proper waste osal in accordance with
Contaminated packaging	Recycling is preferred when possible. has the responsibility for proper waste and disposal in accordance with appli- and local regulations.	e classification, transportation
	14. TRANSPORT INFORMATION	
U.S. DOT Classification	Refer to specific regulation.	
ICAO/IATA (air)	Refer to specific regulation.	
IMO / IMDG (maritime)	Refer to specific regulation.	
	5. REGULATORY INFORMATION	
US Regulations:		
OSHA Status	Classified as hazardous based on com	ponents.
TSCA Status	All components of this product are lis Inventory.	ted on or exempt from the TSCA
US. EPA CERCLA Hazardou	ostances (40 CFR 302)	
Not applicable		
California Proposition 65	WARNING! This product contains a California to cause cancer.	chemical known to the State of
SARA Title III Section 302 E	nely Hazardous Substance	
Not applicable		

PolyOne.

# MATERIAL SAFETY DATA SHEET FB455A NEUTRAL

Version Number 1.0		
Revision Date 08/25/2004		

Page 6 of 6 Print Date 11/15/2011

SARA Title III Section 313 Toxic Chemicals:			
Not applicable Canadian Regulations:			
National Pollutant Relea	se Iı	nventory (NPRI)	
Not applicable			
WHMIS Classification	:	D2A	
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
National Inventories:			
Australia AICS	:	Not determined	
China IECS	:	Not determined	
Europe EINECS	:	Not determined	
Japan ENCS	:	Not determined	
Korea KECI	:	Not determined	
Philippines PICCS	:	Not determined	

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.