## MATERIAL SAFETY DATA SHEET 99994CBA PLAST-O-CELL- OBSH - 25.5

Version Number 1.1 Revision Date 02/15/2005

Page 1 of 6 Print Date 11/17/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	99994CBA PLAST-O-CELL- OBSH - 25.5
Product code	:	FO20009880
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

## 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Diphenyloxide-4,4'-disulfohydrazide	80-51-3	10 - 30

## 3. HAZARDS IDENTIFICATION

## **EMERGENCY OVERVIEW**

May release high amount of nitrogen if inadvertenly heated above 50°C (122°F) or stored incorrectly. Pressure inside the container can increase and cause its rupture. This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Eyes, Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation Ingestion Eyes Skin	<ul> <li>At process temperatures, product emissions may cause irritation.</li> <li>May be harmful if swallowed.</li> <li>May cause eye/skin irritation.</li> <li>Experience shows no unusual dermatitis hazard from routine handling.</li> </ul>		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		

PolyOne

# MATERIAL SAFETY DATA SHEET 99994CBA PLAST-O-CELL- OBSH - 25.5

Version Number 1.1 Revision Date 02/15/2005 Page 2 of 6 Print Date 11/17/2011

	4. FIRST AID MEASURES
Inhalation	: Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. When symptoms persist or in all cases of doub seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water.
	5. FIRE-FIGHTING MEASURES
Flash point	: Greater than 200 °F (93 °C)
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>No data available</li> <li>No data available</li> <li>No data available</li> <li>No data available</li> <li>waterfoam.</li> </ul> Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Cool closed containers exposed to fire with water spra. If inadvertent heating of product results in smoke production, spray immediately and thoroughly with water. May release high amount on nitrogen if inadvertenly heated above 50°C (122°F) or stored incorrectly. Pressure inside the container can increase and cause its rupture. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May release high amount of nitrogen if inadvertently. Pressure inside the container can increase and cause its rupture.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Contain and collect spillage with non-combustible absorbent materia (e.g. sand, earth, diatomaceus earth, vermiculite) and place in container for disposal according to local / national regulations (see

PolyOne.

# MATERIAL SAFETY DATA SHEET 99994CBA PLAST-O-CELL- OBSH - 25.5

Version Number 1.1 Revision Date 02/15/2005 Page 3 of 6 Print Date 11/17/2011

	7.	HANDLING AND STORAG	<b>JE</b>		
Handling	b	Wear personal protective equipment. Take measures to prevent the build up of electrostatic charge. Provide for appropriate exhaust ventilation and dust collection at machinery.			
Storage	K re (1	: Keep away from open flames, hot surfaces and sources of ignition. Keep away from direct sunlight. Keep in a dry, cool place. May release high amount of nitrogen if inadvertenly heated above 50°C (122°F) or stored incorrectly. Pressure inside the container can increase and cause its rupture.			
8. E	EXPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	n re	When workers are facing concern nust use appropriate certified re espirators must be properly train pplicable regulations such as C	espirators. Employees us ined. Employers must fo	sing Illow	
Eye/Face Protection	: S	Safety glasses with side-shields.			
Hand protection	: P	: Protective gloves.			
Skin and body protection	V W	: Long sleeved shirts and long pants are adequate for normal handling. Where operations present a splash or spill potential, employees should wear chemically resistant clothing, boots, apron, gloves, and eye/face protection.			
Additional Protective Measures	: V	When using, do not eat, drink or smoke.			
General Hygiene Considerations		: Do not breathe dust or spray mist. Handle in accordance with good industrial hygiene and safety practices.			
Engineering measures	: Adequate ventilation and/or appropriate respiratory protection may also be necessary to minimize employee exposure to processing vapors.				
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Diphenyloxide-4,4'-dis ulfohydrazide	0.1 mg/m3	Time Weighted Average (TWA):	Inhalable fraction.	ACGIH	
	9. PHYSI	CAL AND CHEMICAL PRO	PERTIES		
Form	: liqui	1 <b>D</b>	ration rate : Not	applicable	



# MATERIAL SAFETY DATA SHEET 99994CBA PLAST-O-CELL- OBSH - 25.5

Version Number 1.1 Revision Date 02/15/2005

Page 4 of 6 Print Date 11/17/2011

Appearance Color Odor Melting point/range Boiling Point: Water solubility	<ul> <li>Viscous liquid dispersion</li> <li>NOT APPLICABLE</li> <li>Very faint</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Negligible</li> </ul>			
	10. STABILITY AND REACTIVITY			
Stability	: Stable.			
Hazardous Polymerization	: Will not occur.			
Conditions to avoid	: Heat, flames and sparks.			
Incompatible Materials	: Reacts with water or acids to form carbon dioxide (CO2)			
Hazardous decomposition products	<ul> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> <li>Ammonia May release high amount of nitrogen if inadvertenly heated above 50°C (122°F) or stored incorrectly. Pressure inside the container can increase and cause its rupture.</li> </ul>			

### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
	Diphenyloxide-4,4'-disulfo hydrazide	Irritant	Eyes, Skin.
	12. ECOLOGICA	L INFORMATIO	DN
Persistence and degradal	oility : No data availab	le	
Environmental Toxicity : No data availabl		le	
Bioaccumulation Potential : No data available		le	
Additional advice	: No data availab	le	
	13. DISPOSAL C	ONSIDERATION	NS
Product	: The generator of waste material has the responsibility for proper wa classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		

	PolyOne.
POLYONE CORPORAT	ΓΙΟΝ
MATERIAL SAFETY DATA SHE	CET
99994CBA PLAST-O-C	CELL- OBSH - 25.5
Version Number 1.1 Revision Date 02/15/2005	Page 5 of 6 Print Date 11/17/2011
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
California Proposition 65	: This product does not contain a substance listed by California Prop 65.
SARA Title III Section 302 Ext Not applicable	remely Hazardous Substance
SARA Title III Section 313 Top	xic Chemicals:
Not applicable Canadian Regulations:	
National Pollutant Relea	se Inventory (NPRI)
Not applicable	
WHMIS Classification	: D2B
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

5/6

PolyOne.

## MATERIAL SAFETY DATA SHEET 99994CBA PLAST-O-CELL- OBSH - 25.5

Version Number 1.1 Revision Date 02/15/2005 Page 6 of 6 Print Date 11/17/2011

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Listed
Korea KECI	:	Listed
Philippines PICCS	:	Listed

## **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.