### MATERIAL SAFETY DATA SHEET STAN-TONE HCC-9266 BLACK

Version Number 1.0 Revision Date 05/06/2005

Page 1 of 6 Print Date 11/17/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	STAN-TONE HCC-9266 BLACK
Product code	:	FO20011543
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Di(2-ethylhexyl)phthalate	117-81-7	30 - 60

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne

# MATERIAL SAFETY DATA SHEET **STAN-TONE HCC-9266 BLACK**

Version Number 1.0 Revision Date 05/06/2005 Page 2 of 6 Print Date 11/17/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. Seek medical attention if necessary.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>No data available</li> <li>No data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foam.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Prolonged heating may result in product degradation.

PolyOne

# MATERIAL SAFETY DATA SHEET STAN-TONE HCC-9266 BLACK

#### Version Number 1.0 Revision Date 05/06/2005

Page 3 of 6 Print Date 11/17/2011

Storage		Keep containers dry and contamination. St		closed to avoid moisture ool dry place.	e absorption
8. E	XPOSURE	CONTROLS / PER	SONAL	PROTECTION	
Respiratory protection	: U	Jnder normal handlin	g conditio	ons a respirator may not	be required.
Eye/Face Protection	: \$	Safety glasses with sic	le-shields.		
Hand protection	: F	Protective gloves.			
Skin and body protection	: I	long sleeved clothing			
Additional Protective Measures	: S	Safety shoes.			
General Hygiene Considerations				l industrial hygiene and s at the end of workday.	afety practice.
Engineering measures		Heat only in areas with appropriate exhaust ve		iate exhaust ventilation. at machinery.	Provide
Exposure limit(s) Components Di(2-ethylhexyl)phthal	Value 5 mg/m3	Exposure tin PEL:	ne	Exposure type Vapor.	List: OSHA Z1
ate	5 mg/m3	r EL.		vapor.	USIIA ZI
	9. PHYSI	CAL AND CHEMI	CAL PRO	<b>DPERTIES</b>	
Form Appearance		id id, Viscous liquid ersion			established determined
Color	: BLA		Bulk d	ensity : Not	applicable
Odor	: Very		Vapor	pressure : Not	determined
Melting point/range	: Not applicable Vapour density : Heavier than at : Not applicable pH : Not determined				
Boiling Point: Water solubility		niscible	рп	: 100	uetermined
	10.	STABILITY AND R	REACTIV	ITY	
Stability	: 5	Stable.			
Stability Hazardous Polymerization		Stable. Will not occur.			
Hazardous Polymerization	n : V : F	Will not occur.		ts and open flame. To a	woid thermal
-	n : V : H d	Will not occur. Keep away from oxidi	overheat.		woid thermal

## MATERIAL SAFETY DATA SHEET STAN-TONE HCC-9266 BLACK

#### Version Number 1.0 Revision Date 05/06/2005

Page 4 of 6 Print Date 11/17/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

**Toxicity Overview** 

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
117-81-7	Di(2-ethylhexyl)phthalate	Systemic effects	Eyes, Respiratory system, Liver, central nervous system (CNS), Skin, digestive system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
117-81-7	Di(2-ethylhexyl)phthalate	Oral LD50	30 gm/kg	rat
		Dermal LD50	25 gm/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

	CAS-No.	Chemical Name	OSHA	IARC	NTP
--	---------	---------------	------	------	-----

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### Additional Health Hazard Information:

Di(2-ethylhexyl)phthalate 117-81-7 There is sufficient evidence for the carcinogenicity of di (2-ethylhexyl) phthalate in experimental animals. Administered in the feed this chemical caused an increase incidence of liver cancer in male and female rats and mice. The relevance of this finding to humans is uncertain.

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability: Not readily biodegradable.Environmental Toxicity: Environmental toxicity has not been established for this mixture as a

PolyOne

# MATERIAL SAFETY DATA SHEET STAN-TONE HCC-9266 BLACK

Version Number 1.0 Revision Date 05/06/2005 Page 5 of 6 Print Date 11/17/2011

Bioaccumulation Po	tential	:	No data	available			
Additional advice		:	No data	available			
		1.	3. DISPO	SAL CONSIDERAT	TIONS		
Product		:	generato classifica	ossible recycling is pr r of waste material ha ation, transportation a le federal, state/provin	s the responsibilind disposal in ac	ity for j cordan	proper waste ce with
Contaminated packa	ging	:	has the r and disp	ng is preferred when poesponsibility for proposial in accordance will regulations.	er waste classifi	cation, t	ransportation
		1	4. TRAN	SPORT INFORMA	ΓΙΟΝ		
U.S. DOT Classifica	tion	:	Refer to	specific regulation.			
ICAO/IATA (air)		:	Refer to	specific regulation.			
IMO / IMDG (marit	ime)	:	Refer to	specific regulation.			
		15	. REGUL	ATORY INFORMA	TION		
US Regulations:							
OSHA Statu	5	:	Classifie	ed as hazardous based	on components.		
TSCA Status		:	All com Inventor	ponents of this produc y.	et are listed on or	exemp	t from the TSC.
US. EPA CERCLA	Hazardous	Sub	stances (4	0 CFR 302)			
Chemical Nat	ne C.	AS-N	No.	RQ for component	RQ for		1
Di(2-ethylhex thalate		7-81		100 lbs	Mixture/Prod 200 LB	uct	-
California Pr 65	oposition	:	Californ	NG! This product con ia to cause cancer., W l known to the State o	ARNING! This	produc	t contains a

# MATERIAL SAFETY DATA SHEET STAN-TONE HCC-9266 BLACK

Version Number 1.0 Revision Date 05/06/2005 Page 6 of 6 Print Date 11/17/2011

SARA Title III Section 302 Extremely Hazardous Substance Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
DI(2-ETHYLHEXYL)PHTHALATE (DEHP)	117-81-7	50.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Di(2-ethylhexyl)phthalate	117-81-7	50.00	25

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

:

[	CAS-No.
	117-81-7

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Listed
Korea KECI	:	Listed
Philippines PICCS	:	Listed

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.