PolvOne

MATERIAL SAFETY DATA SHEET FB466 EMERALD GREEN SLT FOAM

Version Number 1.3 Revision Date 10/26/2007 Page 1 of 7 Print Date 12/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

| Telephone Emergency telephone | : | Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
|----------------------------------|---|--|
| Product name | : | FB466 EMERALD GREEN SLT FOAM |
| Product code | : | FO20011584 |
| Chemical Name | : | Mixture |
| CAS-No. | : | Mixture |
| Product Use | : | Industrial Applications |
| | | |

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

| Components | CAS-No. | Weight % |
|-------------------|------------|----------|
| Azodicarbonamide | 123-77-3 | 1 - 5 |
| Quartz | 14808-60-7 | 0.1 - 1 |
| Calcium carbonate | 1317-65-3 | 10 - 30 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Skin contact, Ingestion | | |
|----------------------------|--|--|--|
| Acute exposure | | | |
| Inhalation | : Inhalation of airborne droplets may cause irritation of the respiratory tract. | | |
| Ingestion | : May be harmful if swallowed. | | |
| Eyes | : May cause eye/skin irritation. | | |
| Skin | : Experience shows no unusual dermatitis hazard from routine handling. | | |
| Chronic exposure | : Refer to Section 11 for Toxicological Information. | | |

PolyOne

MATERIAL SAFETY DATA SHEET FB466 EMERALD GREEN SLT FOAM

Version Number 1.3 Revision Date 10/26/2007 Page 2 of 7 Print Date 12/2/2011

| Medical Conditions Aggravated by Exposure: | : None known. |
|--|---|
| | 4. FIRST AID MEASURES |
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. |
| Eyes | : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention. |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists see medical attention. |
| | 5. FIRE-FIGHTING MEASURES |
| Flash point | : No data available |
| Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards | No data available No data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible. |
| | 6. ACCIDENTAL RELEASE MEASURES |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. |
| Environmental precautions | : The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment. |
| Methods for cleaning up | : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods. |
| | 7. HANDLING AND STORAGE |

PolyOne.

MATERIAL SAFETY DATA SHEET FB466 EMERALD GREEN SLT FOAM

| rsion Number 1.3 vision Date 10/26/2007 | | Page 3 of Print Date 12/2/201 |
|--|------|---|
| Handling | : | Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. |
| Storage | : | Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place. |
| 8. EXF | OSUI | RE CONTROLS / PERSONAL PROTECTION |
| Respiratory protection | : | No personal respiratory protective equipment normally required. |
| Eye/Face Protection | : | Safety glasses with side-shields |
| Hand protection | : | Protective gloves |
| Skin and body protection | : | Long sleeved clothing |
| Additional Protective Measures | : | Safety shoes |
| General Hygiene Considerations | : | Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. |
| Engineering measures | : | Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. |
| Exposure limit(s) | | |

| Components | Value | Exposure time | Exposure type | List: |
|-------------------|----------------|-----------------------------------|----------------------|---------|
| Calcium carbonate | 5 mg/m3 | PEL: | Respirable fraction. | OSHA Z1 |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| | 10 mg/m3 | Time Weighted Average (TWA): | | MX OEL |
| | 20 mg/m3 | Short Term Exposure Limit (STEL): | | MX OEL |
| Quartz | 0.025 mg/m3 | Time Weighted Average (TWA): | Respirable fraction. | ACGIH |
| | 0.1 mg/m3 | Time Weighted Average (TWA): | Respirable. | Z3 |
| | 0.3 mg/m3 | Time Weighted Average (TWA): | Total dust. | Z3 |
| | 0.1 mg/m3 | Time Weighted Average (TWA): | | MX OEL |

9. PHYSICAL AND CHEMICAL PROPERTIES

Form

Evaporation rate

: Not established

MATERIAL SAFETY DATA SHEET FB466 EMERALD GREEN SLT FOAM

: Viscous, liquid

: Not applicable

: Not applicable

: GREEN

: Very faint

: Immiscible

Version Number 1.3 F

| | 01 1.0 |
|---------------|------------|
| Revision Date | 10/26/2007 |
| | |
| | |

| Appearance |
|---------------------|
| Color |
| Odour |
| Melting point/range |
| Boiling Point: |
| Water solubility |

| | | - |
|--|--|---|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

| Stability | : | Stable. |
|----------------------------------|---|---|
| Hazardous Polymerization | : | Will not occur. |
| Conditions to avoid | : | Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. |
| Incompatible Materials | : | Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing. |
| Hazardous decomposition products | : | Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F). |

10. STABILITY AND REACTIVITY

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|------------|-------------------|------------------|---------------------------------|
| 123-77-3 | Azodicarbonamide | sensitizer | Respiratory system. |
| 14808-60-7 | Quartz | Systemic effects | Eyes, Respiratory system. |
| 1317-65-3 | Calcium carbonate | Irritant | Eyes, Skin. |
| | | Systemic effects | Eyes, Skin, Respiratory system. |

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No. | Chemical Name | Route | Value | Species |
|----------|------------------|-------------|---------------|---------|
| 123-77-3 | Azodicarbonamide | LC50 | 200 mg/l | rat |
| | | Oral LD50 | > 6,400 mg/kg | rat |
| | | Dermal LD50 | > 2,000 mg/kg | rabbit |

Carcinogenicity

:

:

Specific Gravity

Vapour pressure

Vapour density

Bulk density

pН

Page 4 of 7 Print Date 12/2/2011

Not determined

Not applicable

: Not determined

: Not determined

: Not applicable

MATERIAL SAFETY DATA SHEET FB466 EMERALD GREEN SLT FOAM

Version Number 1.3 Revision Date 10/26/2007 Page 5 of 7 Print Date 12/2/2011

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|------------|---------------|------|------|-----|
| 14808-60-7 | Quartz | no | 1 | no |

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Azodicarbonamide 123-77-3 Sensitizer to the respiratory system with repeated minimal inhalation. While no chronic health problems have been identified, individuals with respiratory problems should avoid inhalation exposure to this material.

Additional Health Hazard Information:

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation. Long-term exposure may cause coughing, chest pain, diminished chest expansion and possibly silicosis, which is a scarring of the lungs.

| Persistence and degradability | : Not readily biodegradable. |
|-------------------------------|---|
| Environmental Toxicity | : Environmental toxicity has not been established for this mixture as a whole. |
| Bioaccumulation Potential | : No data available |
| Additional advice | : No data available |
| | 13. DISPOSAL CONSIDERATIONS |
| Product | : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| Contaminated packaging | : Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| | 14. TRANSPORT INFORMATION |

PolyOne.

MATERIAL SAFETY DATA SHEET FB466 EMERALD GREEN SLT FOAM

| Version Number 1.3 | | | |
|----------------------|------------|--|--|
| Revision Date | 10/26/2007 | | |
| | | | |

Page 6 of 7 Print Date 12/2/2011

| U.S. DOT Classification | . Refer to s | specific regulation. | | |
|--|-------------------------|-----------------------------|---------------------|--------------------|
| ICAO/IATA (air) | : Refer to s | specific regulation. | | |
| IMO / IMDG (maritime) | : Refer to s | specific regulation. | | |
| | 15. REGUL | ATORY INFORMATIO | ON | |
| US Regulations: | | | | |
| OSHA Status | : Classified | d as hazardous based on c | components. | |
| TSCA Status | : All comp Inventory | ponents of this product are | e listed on or exer | npt from the TSC |
| US. EPA CERCLA Hazardo | us Substances (40 |) CFR 302) | | |
| Not applicable | | | | |
| SARA Title III Section 302 I Unless specific chemicals are | - | | is Not Applicabl | e under this regul |
| SARA Title III Section 313 Unless specific chemicals are Canadian Regulations: | | this section, this product | is Not Applicabl | e under this regul |
| | lease Inventory () | , | XX : 1 / 0/ | |
| National Pollutant Re | icase inventory (1 | | Weight % | NPRI ID# |
| Chemical Name | | CAS-No. | 10.10.100 | 13 |
| Chemical Name Aluminum oxide | | 1344-28-1 | 0.10 - 1.00 | 13 |
| Chemical Name Aluminum oxide Bisphenol A | | | 0.10 - 1.00 | 143 |
| Chemical Name Aluminum oxide | | 1344-28-1 80-05-7 | | |

PolyOne

MATERIAL SAFETY DATA SHEET FB466 EMERALD GREEN SLT FOAM

Version Number 1.3 Revision Date 10/26/2007 Page 7 of 7 Print Date 12/2/2011

| DSL | : | All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt. |
|-----------------------|---|--|
| National Inventories: | | |
| Australia AICS | : | Not determined |
| China IECS | : | Not determined |
| Europe EINECS | : | Listed |
| Japan ENCS | : | Not determined |
| Korea KECI | : | Not determined |
| Philippines PICCS | : | Not determined |
| | | 16. OTHER INFORMATION |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.