PolvOne

MATERIAL SAFETY DATA SHEET

FB468 Yellow SL

Version Number 1.1 Revision Date 10/26/2007 Page 1 of 6 Print Date 12/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	FB468 Yellow SL
Product code	:	FO20011821
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Azodicarbonamide	123-77-3	1 - 5
Miscellaneous Zinc Compounds	Not Available	1 - 5
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.		
Ingestion	: May be harmful if swallowed.		
Eyes	: May cause eye/skin irritation.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		

PolyOne.

MATERIAL SAFETY DATA SHEET **FB468 Yellow SL**

Version Number 1.1 Revision Date 10/26/2007 Page 2 of 6 Print Date 12/2/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET FB468 Yellow SL

ion Number 1.1 sion Date 10/26/2007					Print	Page 3 Date 12/2/2
Handling	ft P	leat only in areas ume condensates eriodically clean ccumulation of th	may contain o hoods, ducts,	combustible or t and other surface	oxic resi	due.
Storage		Leep containers dr nd contamination			moisture	e absorption
8. H	EXPOSURE	CONTROLS / P	PERSONAL	PROTECTION	N	
Respiratory protection	: N	lo personal respira	atory protecti	ve equipment no	ormally 1	required.
Eye/Face Protection	: S	afety glasses with	side-shields			
Hand protection	: P	rotective gloves				
Skin and body protection	: L	ong sleeved cloth	ing			
Additional Protective Measures	: S	afety shoes				
General Hygiene Considerations		Iandle in accordar Vash hands before				afety practice
Engineering measures Exposure limit(s)		leat only in areas ppropriate exhaus			tilation.	Provide
Components	Value	Exposure	time	Exposure t	vpe	List:
Calcium carbonate	5 mg/m3	PEL		Respirable fra		OSHA Z1
	15 mg/m3	PEL		Total du		OSHA Z1
	10 mg/m3	Time Weighte (TWA	-			MX OEL
	20 mg/m3	Short Term Exp (STEI				MX OEL
	9. PHYSI	CAL AND CHEN	MICAL PRO	PERTIES		
Form Appearance Color Odour Melting point/range	: YEL : Very : Not	ous, liquid LOW 7 faint applicable applicable	Specifi Bulk d Vapou	ration rate c Gravity ensity r pressure r density	: Not : Not : Not : Not	established determined applicable determined determined applicable
Boiling Point: Water solubility	: Imm	iscible				
Boiling Point:		STABILITY AN	D REACTIV	TTY		
Boiling Point:			D REACTIV	TTY		

MATERIAL SAFETY DATA SHEET **FB468 Yellow SL**

Version Number 1.1 Revision Date 10/26/2007 Page 4 of 6 Print Date 12/2/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
123-77-3	Azodicarbonamide	sensitizer	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
123-77-3	Azodicarbonamide	LC50	200 mg/l	rat
		Oral LD50	> 6,400 mg/kg	rat
		Dermal LD50	> 2,000 mg/kg	rabbit

Additional Health Hazard Information:

Azodicarbonamide 123-77-3 Sensitizer to the respiratory system with repeated minimal inhalation. While no chronic health problems have been identified, individuals with respiratory problems should avoid inhalation exposure to this material.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.

PolyOne.

MATERIAL SAFETY DATA SHEET **FB468 Yellow SL**

Version Number 1.1 Revision Date 10/26/2007 Page 5 of 6 Print Date 12/2/2011

Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
Not applicable	
California Proposition 65	: Not applicable
SARA Title III Section 302 E	xtremely Hazardous Substance

PolvOne

MATERIAL SAFETY DATA SHEET FB468 Yellow SL

Version Number	er 1.1
Revision Date	10/26/2007

Page 6 of 6 Print Date 12/2/2011

SARA Title III Section 313 Toxic Chemicals:

U	Inless specific chemicals are identified under this section, this	s product is Not Ap	plicable under this	regulation
	Chemical Name	CAS-No.	Weight %	
	ZINC COMPOUNDS	Not Available	1.00 - 5.00	

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Miscellaneous Zinc Compounds	Not Available	1.00 - 5.00	241

	WHMIS Classification	:	D2A All components of this product are on the Canadian Domestic	
Natio	nal Inventories:		Substances List (DSL) or are exempt.	
	Australia AICS	:	Not determined	
	China IECS	:	Not determined	
	Europe EINECS	:	Listed	
	Japan ENCS	:	Not determined	
	Korea KECI	:	Not determined	
	Philippines PICCS	:	Not determined	
16. OTHER INFORMATION				

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.