

MATERIAL SAFETY DATA SHEET

AQUAMIX 172

Version Number 1.2 Page 1 of 7
Revision Date 03/30/2014 Print Date 4/9/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION

8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone : 1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : AQUAMIX 172
Product code : FO20011899
Chemical Name : Mixture
CAS-No. : Mixture

Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent	
Sulfur	7704-34-9	30 - 60	
Ethyl alcohol	64-17-5	0.1 - 1	

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This product is a water based mixture with an ammonia odor. The mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. The product is not combustible, but it will burn if involved in a fire, releasing hydrocarbon products of combustion. Inhalation of the ammonia from this product may cause respiratory irritation, coughing, sore throat, and labored breathing.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Skin contact, Inhalation, Ingestion

Acute exposure

Inhalation : Symptoms of breathing ammonia vapor concentrated from this product

may include laryngitis, tracheitis, pulmonary edema, dyspnea, bronchospasms, and chest pains or pneumonitis. Symptoms are

typically reversible.

Ingestion : May be harmful if swallowed.

Eyes : Liquid, aerosol, or vapors of this product are irritating and may cause

tearing, reddening, and swelling accompanied by a stinging sensation

and/or a feeling like that of fine dust in the eyes.

Skin : Skin contact may cause redness, irritation, and burns.



MATERIAL SAFETY DATA SHEET

AQUAMIX 172

 Version Number 1.2
 Page 2 of 7

 Revision Date 03/30/2014
 Print Date 4/9/2014

Chronic exposure : Refer to Section 11 for Toxicological Information.

Medical Conditions Aggravated by Exposure:

: None known.

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of vapors or fumes

from overheating or combustion. When symptoms persist or in all

cases of doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. Never give anything

by mouth to an unconscious person. Seek medical attention if

necessary.

Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye

irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists

seek medical attention.

5. FIREFIGHTING MEASURES

Flash point : no data available

Flammable Limits

Upper explosion limit : no data available
Lower explosion limit : no data available
Auto-ignition temperature : no data available

Suitable extinguishing media : Carbon dioxide (CO2), Water, Foam, Dry chemical.

Special Fire Fighting

Procedures

Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water

courses.

Unusual Fire/Explosion

Hazards

: Burning dry latex produces dense black smoke with the possibility of toxic vapors. Residual latex material contained in empty drums may

decompose when burned producing toxic or irritating fumes. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx),

other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Ensure response personnel are properly protected (see section 8 for

respiratory or other protection guidelines.) Use caution as floors may

be slippery.



MATERIAL SAFETY DATA SHEET

AQUAMIX 172

Version Number 1.2 Page 3 of 7
Revision Date 03/30/2014 Print Date 4/9/2014

Environmental precautions : The product should not be allowed to enter drains, water courses or

the soil.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid

binder, universal binder, sawdust). Sweep up and shovel into suitable

containers for disposal.

7. HANDLING AND STORAGE

Handling : Use only in area provided with appropriate exhaust ventilation.

Prolonged heating may result in product degradation. Material may settle during storage. Careful mixing without introduction of air may

be necessary before use.

Storage : Containers which are opened must be carefully resealed and kept

upright to prevent leakage. Keep in a dry, cool place. Keep from

freezing and temperature extremes.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection : A respirator is normally not required for routine handling of product

in areas of good general ventilation and adequate local exhaust at processing equipment during routine operation. If using a cartridge respirator, an ammonia cartridge is required to filter out potential

excess ammonia vapors.

Eye/Face Protection : Safety glasses with side-shields Wear goggles or face shield during

operations that present a splash potential.

Hand protection : Impervious gloves such as rubber or PVC

Skin and body protection : Long sleeved shirts and long pants are adequate for normal handling.

Where operations present a splash or spill potential, employees should wear chemically resistant clothing, boots, apron, gloves, and

eye/face protection.

Additional Protective

Measures

: Safety shoes

General Hygiene

Considerations

Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and

safety practices.

Engineering measures : Adequate ventilation and/or appropriate respiratory protection may

also be necessary to minimize employee exposure to processing

vapors.

Exposure limit(s)



MATERIAL SAFETY DATA SHEET

AQUAMIX 172

Page 4 of 7 Print Date 4/9/2014 Version Number 1.2 Revision Date 03/30/2014

Components	Value	Exposure time	Exposure type	List:
Ethyl alcohol	1,000 ppm	PEL:		OSHA Z1
	1,900			
	mg/m3			
	1,000 ppm	Time Weighted Average		MX OEL
	1,900	(TWA):		
	mg/m3			
	1,000 ppm	Short Term Exposure Limit		ACGIH
		(STEL):		

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : liquid Evapouration rate : Slower than Butyl

Acetate

Specific Gravity Not determined Appearance : liquid Colour NO PIGMENT Bulk density Not applicable Odour Slight ammonia Vapour pressure Not established Melting point/range : not applicable Vapour density Heavier than air. **Boiling Point:** : Not established pН Not determined

Water solubility : completely miscible

10. STABILITY AND REACTIVITY

Stability The product is stable if stored and handled as prescribed.

Hazardous Polymerization Will not occur.

Conditions to avoid Extremes of temperature and direct sunlight. Keep from freezing.

Incompatible Materials Acids, metal salts, and solvents

Hazardous decomposition Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen products

(NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ	
7704-34-9	Sulfur	Irritant	Eyes, Skin, Respiratory	
			system.	
64-17-5	Ethyl alcohol	Systemic effects	Liver, heart or circulatory	
			system, central nervous system	
			(CNS), reproductive system.	

LC50 / LD50



MATERIAL SAFETY DATA SHEET

AQUAMIX 172

 Version Number 1.2
 Page 5 of 7

 Revision Date 03/30/2014
 Print Date 4/9/2014

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
64-17-5	Ethyl alcohol	LC50	20000 ppm	rat
		LC50		rat
		Oral	3,450	mousemouse
		LD50Oral	mg/kg3,450	
		LD50	mg/kg	

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP

IARC Carcinogen Classifications:

- 1 The component is carcinogenic to humans.
- 2A The component is probably carcinogenic to humans.
- 2B The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability : no data available

Environmental Toxicity : no data available

Bioaccumulation Potential : no data available

Additional advice : no data available

13. DISPOSAL CONSIDERATIONS

Product : Where possible recycling is preferred to disposal or incineration. The

generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste

material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal,

state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Refer to specific regulation.



MATERIAL SAFETY DATA SHEET

AQUAMIX 172

 Version Number 1.2
 Page 6 of 7

 Revision Date 03/30/2014
 Print Date 4/9/2014

ICAO/IATA : Refer to specific regulation.

IMO/IMDG (maritime) : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the

TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition :

: Not applicable

65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

not applicable

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No. 64-17-5

DSL : All components of this product are on the Canadian Domestic

Substances List (DSL) or are exempt.

National Inventories:



MATERIAL SAFETY DATA SHEET

AQUAMIX 172

Version Number 1.2 Page 7 of 7
Revision Date 03/30/2014 Print Date 4/9/2014

Australia AICS : Not determined

China IECS : Not determined

Europe EINECS : Not determined

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.