PolvOne

# MATERIAL SAFETY DATA SHEET (CHINA ONLY) 15000Q1 QuantumOne BASE

Version Number 1.2 Revision Date 01/31/2008

Page 1 of 6 Print Date 12/3/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	(CHINA ONLY) 15000Q1 QuantumOne BASE
Product code	:	FO20012381
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

## 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Calcium carbonate	471-34-1	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne

# MATERIAL SAFETY DATA SHEET (CHINA ONLY) 15000Q1 QuantumOne BASE

Version Number 1.2 Revision Date 01/31/2008 Page 2 of 6 Print Date 12/3/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>No data available</li> <li>No data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



# MATERIAL SAFETY DATA SHEET (CHINA ONLY) 15000Q1 QuantumOne BASE

/ersion Number 1.2 Revision Date 01/31/2008		Page 3 of 6 Print Date 12/3/2011
		fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	10 mg/m3 Time Weighted Average			ACGIH
		(TWA):		
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit		MX OEL
	_	(STEL):		
Silica, amorphous,	0.8 mg/m3	Time Weighted Average		Z3
fumed, crystal-free		(TWA):		
	10 mg/m3	Time Weighted Average	Inhalable particulate.	MX OEL
	_	(TWA):	-	
	3 mg/m3	Time Weighted Average	Respirable dust.	MX OEL
	_	(TWA):		

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color : liquid: Viscous, liquid: NO PIGMENT

Evaporation rate Specific Gravity Bulk density Not establishedNot determinedNot applicable



# MATERIAL SAFETY DATA SHEET (CHINA ONLY) 15000Q1 QuantumOne BASE

Version Number 1.2 Revision Date 01/31/2008

\_

Page 4 of 6 Print Date 12/3/2011

Odour Melting point/range Boiling Point: Water solubility	<ul><li>Very faint</li><li>Not applicable</li><li>Not applicable</li><li>Immiscible</li></ul>	Vapour pressure Vapour density pH	<ul><li>Not determined</li><li>Not determined</li><li>Not applicable</li></ul>
	10. STABILITY AN	D REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from o decomposition, do	xidizing agents and open f not overheat.	lame. To avoid thermal
Incompatible Materials		strong acids and oxidizing olymers and acetal copoly	
Hazardous decomposition products	(NOx), hydrogen of smoke are all poss degradation. As a after one hour at 1	O2), carbon monoxide (CC chloride (HCl), other hazar ible. Prolonged heating m general rule of thumb, deg 77 °C (350 °F), after 10 mi ninutes at 232 °C (450 °F).	dous materials, and ay result in product gradation begins to occur inutes at 204 °C (400

## **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
112945-52-5	Silica, amorphous, fumed, crystal-free	Irritant	Eyes, Respiratory system.
471-34-1	Calcium carbonate	Irritant	Eyes, Skin.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
112945-52-5	Silica, amorphous, fumed, crystal-free	Oral LD50	3,160 mg/kg	rat
471-34-1	Calcium carbonate	Oral LD50	6,450 mg/kg	rat

## **12. ECOLOGICAL INFORMATION**

Persistence and degradability

: Not readily biodegradable.

Environmental Toxicity

: Environmental toxicity has not been established for this mixture as a

PolyOne

# MATERIAL SAFETY DATA SHEET (CHINA ONLY) 15000Q1 QuantumOne BASE

Version Number 1.2 Revision Date 01/31/2008 Page 5 of 6 Print Date 12/3/2011

<b>Bioaccumulation Potential</b>	: No data available		
Additional advice : No data available			
	13. DISPOSAL CONSIDERATIONS		
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
	14. TRANSPORT INFORMATION		
U.S. DOT Classification	: Refer to specific regulation.		
ICAO/IATA (air)	: Refer to specific regulation.		
IMO / IMDG (maritime)	: Refer to specific regulation.		
	15. REGULATORY INFORMATION		
US Regulations:			
OSHA Status	: Classified as hazardous based on components.		
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.		
US. EPA CERCLA Hazardou	us Substances (40 CFR 302)		
Not applicable			
California Proposition 65	n : Not applicable		
SARA Title III Section 302 E	Seture la Harradana Subatanan		

PolyOne

# MATERIAL SAFETY DATA SHEET (CHINA ONLY) 15000Q1 QuantumOne BASE

Version Number 1.2 Revision Date 01/31/2008

Page 6 of 6 Print Date 12/3/2011

SARA	SARA Title III Section 313 Toxic Chemicals:					
Unless	specific chemicals are ide	entif	fied under this section, this product is Not Applicable under this regulation			
Canadia	an Regulations:					
]	National Pollutant Release	e In	iventory (NPRI)			
Not	applicable					
	WHMIS Classification	:	Not controlled.			
	DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.			
Nationa	al Inventories:					
	Australia AICS	:	Not determined			
	China IECS	:	Not determined			
	Europe EINECS	:	Listed			
	Japan ENCS	:	Not determined			
	Korea KECI	:	Not determined			
	Philippines PICCS	:	Not determined			

**16. OTHER INFORMATION** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.