PolvOne

MATERIAL SAFETY DATA SHEET S1400NP NYLON PLUS SCARLET

Version Number 1.5 Revision Date 01/25/2010 Page 1 of 7 Print Date 1/10/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	S1400NP NYLON PLUS SCARLET
Product code	:	FO20012758
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Calcium carbonate	471-34-1	5 - 10
Titanium dioxide	13463-67-7	1 - 5
Alkenes, C12-24, chloro	68527-02-6	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye and skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET S1400NP NYLON PLUS SCARLET

Version Number 1.5 Revision Date 01/25/2010 Page 2 of 7 Print Date 1/10/2012

	N7 1			
Medical Conditions : None known. Aggravated by Exposure: : None known.				
	4. FIRST AID MEASURES			
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.			
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.			
	5. FIRE-FIGHTING MEASURES			
Flash point	: no data available			
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 no data available no data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. 			
Special Fire Fighting Procedures Unusual Fire/Explosion	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under 			
Hazards	fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.			
	6. ACCIDENTAL RELEASE MEASURES			
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.			
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.			

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET S1400NP NYLON PLUS SCARLET

Version Number 1.5 Revision Date 01/25/2010 Page 3 of 7 Print Date 1/10/2012

	7.	HANDLING AND STORAG	řE	
Handling	fi P	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.		
Storage		Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.		
8.]	EXPOSURE	CONTROLS/PERSONAL I	PROTECTION	
Respiratory protection	: N	lo personal respiratory protectiv	ve equipment normally	required.
Eye/Face Protection	: S	afety glasses with side-shields		
Hand protection	: P	rotective gloves		
Skin and body protection	: L	Long sleeved clothing		
Additional Protective Measures	: S	Safety shoes		
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	_ ••	ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

(STEL):

- Form Appearance Colour Odour
- : liquid: viscous, liquid: RED: very faint

Evaporation rate Specific Gravity Bulk density Vapour pressure Not establishedNot determinedNot applicableNot determined

MATERIAL SAFETY DATA SHEET S1400NP NYLON PLUS SCARLET

Version Number 1.5 Revision Date 01/25/2010

_

Melting point/range Boiling Point: Water solubility	not applicablenot applicableimmiscible	Vapour density pH	Not determinedNot applicable
	10. STABILITY ANI	D REACTIVITY	
Stability	: Stable		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from or decomposition, do	xidizing agents and open to not overheat.	flame. To avoid thermal
Incompatible Materials	-	strong acids and oxidizing olymers and acetal copoly	
Hazardous decomposition products	(NOx), hydrogen c smoke are all possi degradation. As a after one hour at 17	O2), carbon monoxide (C hloride (HCl), other hazar ble. Prolonged heating m general rule of thumb, deg 77 °C (350 °F), after 10 m hinutes at 232 °C (450 °F)	rdous materials, and hay result in product gradation begins to occur inutes at 204 °C (400

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
471-34-1	Calcium carbonate	Irritant	Eyes, Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
471-34-1	Calcium carbonate	Oral	6,450	ratrat
		LD50Oral	mg/kg6,450	
		LD50	mg/kg	

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

Page 4 of 7 Print Date 1/10/2012

PolyOne

MATERIAL SAFETY DATA SHEET S1400NP NYLON PLUS SCARLET

Version Number 1.5 Revision Date 01/25/2010 Page 5 of 7 Print Date 1/10/2012

IARC Carcinogen Classifications:1 - The component is carcinogenic to humans.2A - The component is probably carcinogenic to humans.2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: no data available
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)

MATERIAL SAFETY DATA SHEET S1400NP NYLON PLUS SCARLET

Version Number 1.5 Revision Date 01/25/2010 Page 6 of 7 Print Date 1/10/2012

not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

not applicable

 WHMIS Classification
 : D2A

 DSL
 : All components of this product

: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

		16 OTHED INFORMATION
Philippines PICCS	:	Not determined
Korea KECI	:	Not determined
Japan ENCS	:	Not determined
Ionon ENCS		Not determined
Europe EINECS	:	Listed
Chilla IECS	·	Not determined
China IECS	•	Not determined
Australia AICS	:	Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The

PolyOne.

MATERIAL SAFETY DATA SHEET S1400NP NYLON PLUS SCARLET

Version Number 1.5 Revision Date 01/25/2010 Page 7 of 7 Print Date 1/10/2012

information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.