PolvOne

MATERIAL SAFETY DATA SHEET **S1900NP NYLON PLUS BLACK**

Version Number 1.1 Revision Date 02/15/2007 Page 1 of 7 Print Date 11/26/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	S1900NP NYLON PLUS BLACK
Product code	:	FO20012894
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Vinyl acetate	108-05-4	0.1 - 1
Calcium carbonate	471-34-1	10 - 30
Poly(Vinyl Acetate-co-Vinyl Chloride)	9003-22-9	10 - 30
Alkenes, C12-24, chloro	68527-02-6	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **S1900NP NYLON PLUS BLACK**

Version Number 1.1 Revision Date 02/15/2007 Page 2 of 7 Print Date 11/26/2011

Medical Conditions Aggravated by Exposure:	: None known.	
	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.	s of
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If irritation persists, seek medical attention.	eye
Skin	: Wash off with soap and plenty of water. If skin irritation persists so medical attention.	eel
	5. FIRE-FIGHTING MEASURES	
Flash point	: No data available	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 No data available No data available Not applicable Carbon dioxide blanket, water spray, dry powder, foam. 	
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positiv pressure mode should be worn to prevent inhalation of airborne contaminants.	ve
Unusual Fire/Explosion Hazards	 May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) und fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxi of nitrogen (NOx), other hazardous materials, and smoke are all possible. 	
	6. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: The product should not be allowed to enter drains, water courses or soil. Should not be released into the environment.	the
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid bind universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for prope disposal methods.	

<u>PolyOne</u>.

MATERIAL SAFETY DATA SHEET **S1900NP NYLON PLUS BLACK**

Version Number 1.1 Revision Date 02/15/2007

_

_

Page 3 of 7 Print Date 11/26/2011

	7.	HANDLING AND STORAG	ŕE	
Handling	fı P	: Heat only in areas with appropriate exhaust ventilation. Processi fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.		idue.
Storage		Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.		
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	lo personal respiratory protecti	ve equipment normally	required.
Eye/Face Protection	: S	: Safety glasses with side-shields.		
Hand protection	: P	Protective gloves.		
Skin and body protection	: L	: Long sleeved clothing.		
Additional Protective Measures	: S	: Safety shoes.		
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	10 mg/m3	Time Weighted Average (TWA):		MX OEL

	10 mg/m3	Time Weighted Average	MX OEL
		(TWA):	
	20 mg/m3	Short Term Exposure Limit	MX OEL
		(STEL):	
Vinyl acetate	10 ppm	Time Weighted Average	ACGIH
		(TWA):	
	15 ppm	Short Term Exposure Limit	ACGIH
		(STEL):	

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color : liquid: Viscous, liquid: BLACK

Evaporation rate Specific Gravity: Bulk density Not establishedNot determinedNot applicable

Keep away from oxidizing agents and open flame. To avoid thermal

Incompatible with strong acids and oxidizing agents., Avoid contact

with acetal homopolymers and acetal copolymers during processing.

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

(NOx), hydrogen chloride (HCl), other hazardous materials, and

smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F),

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

11. TOXICOLOGICAL INFORMATION

and within 5 minutes at 232 °C (450 °F).

CAS-No.	Chemical Name	Effect	Target Organ
108-05-4	Vinyl acetate	Irritant	Eyes, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.
471-34-1	Calcium carbonate	Irritant	Eyes, Skin.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
108-05-4	Vinyl acetate	LC50	11400 mg/m3	rat
		Oral LD50	2,920 mg/kg	rat
		Dermal LD50	2,335 mg/kg	rabbit
471-34-1	Calcium carbonate	Oral LD50	6,450 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

POLYONE CORPORATION

: Very faint

: Immiscible

: Not applicable

: Not applicable

Stable.

Will not occur.

decomposition, do not overheat.

:

:

·

:

:

MATERIAL SAFETY DATA SHEET S1900NP NYLON PLUS BLACK

Version Number 1.1 Revision Date 02/15/2007

Melting point/range

Hazardous Polymerization

Conditions to avoid

Incompatible Materials

Hazardous decomposition

Boiling Point:

Water solubility

Odor

Stability

products

Very faint Not applicable Not applicable Immiscible	Vapor pressure Vapour density pH	:	Not determined Not determined Not applicable	_
10. STABILITY AND REACTIVITY				

Page 4 of 7 Print Date 11/26/2011

PolyOne.

MATERIAL SAFETY DATA SHEET **S1900NP NYLON PLUS BLACK**

Version Number 1.1 Revision Date 02/15/2007 Page 5 of 7 Print Date 11/26/2011

CAS-No.	Chemical Name	OSHA	IARC	NTP
108-05-4	Vinyl acetate	no	2B	no
2B - The component is po NTP Carcinogen Classifi 1 - The component is kno	cinogenic to humans. robably carcinogenic to h ossibly carcinogenic to hu	umans. ogen.		
	12. ECOLOGIO	CAL INFORMATION		
Persistence and degradab	ility : Not readily b	iodegradable.		
Environmental Toxicity	: Environmenta whole.	al toxicity has not been	established for this	s mixture as a
Bioaccumulation Potentia	al : No data avail	able		
Additional advice	: No data avail	able		
	13. DISPOSAL	CONSIDERATIONS		
Product	generator of v classification	ble recycling is preferred waste material has the re , transportation and disp deral, state/provincial an	esponsibility for pr posal in accordance	oper waste with
Contaminated packaging	has the respon	preferred when possible nsibility for proper wast in accordance with applulations.	e classification, tra	ansportation
	14. TRANSPO	RT INFORMATION		
U.S. DOT Classification	: Refer to spec	ific regulation.		
ICAO/IATA (air)	: Refer to spec	ific regulation.		
IMO / IMDG (maritime)	: Refer to spec	ific regulation.		
	15. REGULATO	ORY INFORMATION	[
US Regulations:				
OSHA Status	: Classified as	hazardous based on con	nonents	
OSHA Status	: Classified as	hazardous based on con	nonents	

PolvOne

MATERIAL SAFETY DATA SHEET S1900NP NYLON PLUS BLACK

Version Number 1.1 Revision Date 02/15/2007 Page 6 of 7 Print Date 11/26/2011

TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Not applicable

WHMIS Classification	:	D1B
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
17		

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

PolyOne

MATERIAL SAFETY DATA SHEET S1900NP NYLON PLUS BLACK

Version Number 1.1 Revision Date 02/15/2007 Page 7 of 7 Print Date 11/26/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.