PolvOne

MATERIAL SAFETY DATA SHEET 10457TFXNX EPIC-TFNX TRANSFLEX BASE

Version Number 1.3 Revision Date 02/15/2007 Page 1 of 7 Print Date 11/26/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	10457TFXNX EPIC-TFNX TRANSFLEX BASE
Product code	:	FO20013647
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Quartz	14808-60-7	0.1 - 1
Calcium carbonate	1317-65-3	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	Exposure: : Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.		
Ingestion	: May be harmful if swallowed.		
Eyes	: May cause eye/skin irritation.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		

PolyOne

MATERIAL SAFETY DATA SHEET 10457TFXNX EPIC-TFNX TRANSFLEX BASE

Version Number 1.3 Revision Date 02/15/2007 Page 2 of 7 Print Date 11/26/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available Not applicable Carbon dioxide blanket, water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	5. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or th soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binde universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET 10457TFXNX EPIC-TFNX TRANSFLEX BASE

Version Number 1.3 Revision Date 02/15/2007	Page 3 of 7 Print Date <i>11/26/2011</i>
Storage :	fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXPOSU	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection :	No personal respiratory protective equipment normally required.
Eye/Face Protection :	Safety glasses with side-shields.
Hand protection :	Protective gloves.
Skin and body protection :	Long sleeved clothing.
Additional Protective : Measures	Safety shoes.
General Hygiene : Considerations	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures :	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit		MX OEL
		(STEL):		
Quartz	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	0.1 mg/m3	Time Weighted Average	Respirable.	Z3
		(TWA):		
	0.3 mg/m3	Time Weighted Average	Total dust.	Z3
		(TWA):		
	0.1 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
	0.025	Time Weighted Average	Respirable fraction.	ACGIH
	mg/m3	(TWA):		

9. PHYSICAL AND CHEMICAL PROPERTIES

Form

Evaporation rate : Not established

MATERIAL SAFETY DATA SHEET 10457TFXNX EPIC-TFNX TRANSFLEX BASE

: Viscous, liquid

: NO PIGMENT

Version Number 1.3 Revision Date 02/15/2007

Appearance

Color

Odor Melting point/range Boiling Point: Water solubility	Very faintNot applicableNot applicableImmiscible	Vapor pressure Vapour density pH	Not determinedNot determinedNot applicable
	10. STABILITY AN	D REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from o decomposition, do	xidizing agents and open to not overheat.	flame. To avoid thermal
Incompatible Materials	1	strong acids and oxidizing olymers and acetal copoly	
Hazardous decomposition products	(NOx), hydrogen of smoke are all poss degradation. As a after one hour at 1	O2), carbon monoxide (C chloride (HCl), other hazar ible. Prolonged heating m general rule of thumb, deg 77 °C (350 °F), after 10 m tes at 232 °C (450 °F).	rdous materials, and hay result in product gradation begins to occur

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
14808-60-7	Quartz	no	1	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.



Page 4 of 7 Print Date 11/26/2011

- Specific Gravity::Bulk density:Vapor pressure:
- Not determined Not applicable

PolyOne

MATERIAL SAFETY DATA SHEET 10457TFXNX EPIC-TFNX TRANSFLEX BASE

Version Number 1.3 Revision Date 02/15/2007 Page 5 of 7 Print Date 11/26/2011

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation. Long-term exposure may cause coughing, chest pain, diminished chest expansion and possibly silicosis, which is a scarring of the lungs.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
	: Classified as hazardous based on components.
OSHA Status	

olv0ne

MATERIAL SAFETY DATA SHEET 10457TFXNX EPIC-TFNX TRANSFLEX BASE

Version Number 1.3 Revision Date 02/15/2007

Page 6 of 7 Print Date 11/26/2011

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition 65 WARNING! This product contains a chemical known to the State of California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Not applicable

WHMIS Classification	:	D2A
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

: Not determined
: Not determined
: Listed
: Not determined
: Not determined
: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing,

PolyOne.

MATERIAL SAFETY DATA SHEET 10457TFXNX EPIC-TFNX TRANSFLEX BASE

Version Number 1.3 Revision Date 02/15/2007 Page 7 of 7 Print Date 11/26/2011

storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.