## MATERIAL SAFETY DATA SHEET 45400NPF MAROON

Version Number 1.6 Revision Date 12/16/2009

Page 1 of 6 Print Date 1/10/2012

## 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	45400NPF MAROON
Product code	:	FO20013876
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

## 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Isobutane	75-28-5	1 - 5
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5

### **3. HAZARDS IDENTIFICATION**

### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye and skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

## MATERIAL SAFETY DATA SHEET 45400NPF MAROON

Version Number 1.6 Revision Date 12/16/2009 Page 2 of 6 Print Date 1/10/2012

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: no data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>no data available</li> <li>no data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE

POLYONE CORPORATION



# MATERIAL SAFETY DATA SHEET **45400NPF MAROON**

ion Number 1.6 sion Date 12/16/2009				Print I	Page 3 Date 1/10/2
Handling	fu Pe	me condensates	may contain hoods, ducts	iate exhaust ventilation. combustible or toxic resion , and other surfaces to mist	due.
Storage		eep containers d		closed to avoid moisture cool dry place.	e absorption
8.1	EXPOSURE	CONTROLS/P	PERSONAL	PROTECTION	
Respiratory protection	: N	o personal respir	atory protect	ive equipment normally r	equired.
Eye/Face Protection	: Sa	afety glasses with	h side-shields	5	
Hand protection	: Pi	rotective gloves			
Skin and body protection	: L	ong sleeved clot	ning		
Additional Protective Measures	: Sa	afety shoes			
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures Exposure limit(s)		eat only in areas opropriate exhau		iate exhaust ventilation. at machinery.	Provide
~				-	
Components	Value	Exposure		Exposure type	List:
Silica, amorphous, fumed, crystal-free	0.8 mg/m3	Time Weighte (TWA			Z3
	10 mg/m3	Time Weighte (TWA		Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighte (TWA	-	Respirable dust.	MX OEL
	9. PHYSIC	CAL AND CHE	MICAL PRO	OPERTIES	
Form	: liquio				established
Appearance Colour	: viscous, liquid : RED			2	determined applicable
Odour	: RED : very faint				determined
Melting point/range	: not applicable				determined
Boiling Point:		pplicable	pH		applicable
Water solubility		scible	*		
	10. S	TABILITY AN	D REACTIV	VITY	

PolyOne.

## MATERIAL SAFETY DATA SHEET 45400NPF MAROON

Version Number 1.6 Revision Date 12/16/2009 Page 4 of 6 Print Date 1/10/2012

Stability	:	Stable
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

## 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
75-28-5	Isobutane	Irritant	Eyes, Respiratory system.
112945-52-5	Silica, amorphous, fumed, crystal-free	Irritant	Eyes, Respiratory system.

### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
112945-52-5	Silica, amorphous, fumed, crystal-free	Oral LD50	3,160 mg/kg	rat

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: no data available
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS

PolyOne.

# MATERIAL SAFETY DATA SHEET **45400NPF MAROON**

ersion Number 1.6	Page 5 of 6
evision Date 12/16/2009	Print Date 1/10/2012
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
not applicable	
not dpp.roue.c	
California Proposition 65	: Not applicable
SARA Title III Section 302 E	xtremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 T	oxic Chemicals:
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
Canadian Regulations:	

<u>PolyOne</u>

## MATERIAL SAFETY DATA SHEET 45400NPF MAROON

Version Number 1.6 Revision Date 12/16/2009

\_

Page 6 of 6 Print Date 1/10/2012

National Pollutant Release Inventory (NPRI)				
not applicable				
WHMIS Classification	:	A, B1		
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.		
National Inventories:				
Australia AICS	:	Not determined		
China IECS	:	Not determined		
Europe EINECS	:	Listed		
Japan ENCS	:	Not determined		
Korea KECI	:	Not determined		
Philippines PICCS	:	Not determined		
16. OTHER INFORMATION				

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.