PolvOne

MATERIAL SAFETY DATA SHEET **FB468 JUTE BROWN SL**

Version Number 1.3 Revision Date 11/19/2007

Page 1 of 6 Print Date 12/2/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	FB468 JUTE BROWN SL
Product code	:	FO20014340
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Azodicarbonamide	123-77-3	1 - 5
Miscellaneous Zinc Compounds	Not Available	1 - 5
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **FB468 JUTE BROWN SL**

Version Number 1.3 Revision Date 11/19/2007 Page 2 of 6 Print Date 12/2/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE

PolyOne.

MATERIAL SAFETY DATA SHEET FB468 JUTE BROWN SL

			Print I	Page (Date 12/2/
Handling	fı	leat only in areas with appropr ime condensates may contain o	combustible or toxic resid	due.
		eriodically clean hoods, ducts, ccumulation of these materials		nimize
Storage		eep containers dry and tightly nd contamination. Store in a c		e absorption
8. H	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	o personal respiratory protecti	ve equipment normally r	equired.
Eye/Face Protection	: S	afety glasses with side-shields		
Hand protection	: P	rotective gloves		
Skin and body protection	: L	ong sleeved clothing		
Additional Protective Measures	: S	afety shoes		
General Hygiene Considerations		andle in accordance with good Vash hands before breaks and a		afety practic
Engineering measures		leat only in areas with appropr ppropriate exhaust ventilation		Provide
Exposure limit(s)				
-	Value	Exposure time	Exposure type	List:
Components	Value 5 mg/m3	Exposure time PEL:	Exposure type Respirable fraction.	List: OSHA Z
-	5 mg/m3	Exposure time PEL: PEL:	Exposure type Respirable fraction. Total dust.	OSHA Z
Components		PEL:	Respirable fraction.	OSHA Z OSHA Z
Components	5 mg/m3 15 mg/m3	PEL: PEL: Time Weighted Average	Respirable fraction.	OSHA Z OSHA Z MX OEI
Components	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit	Respirable fraction. Total dust.	OSHA Z OSHA Z MX OEI
Components Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Respirable fraction. Total dust. DPERTIES	OSHA Z OSHA Z MX OEI MX OEI
Components Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liquio	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo	Respirable fraction. Total dust. DPERTIES ration rate : Not	OSHA Z OSHA Z MX OEL MX OEL
Components Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liquio	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo ous, liquid Specif	Respirable fraction. Total dust. DPERTIES ration rate : Not ic Gravity : Not	OSHA Z OSHA Z MX OEI MX OEI established determined
Components Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liquid : Visco : BRO	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo ous, liquid Specif WN Bulk d	Respirable fraction. Total dust. DPERTIES ration rate : Not ic Gravity : Not lensity : Not	OSHA Z OSHA Z MX OEI MX OEI established
Components Calcium carbonate Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liquid : Visco : BRO : Very : Not a	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapor ous, liquid Specif WN Bulk d faint Vapou applicable Vapou	Respirable fraction. Total dust. DPERTIES ration rate : Not ic Gravity : Not lensity : Not r pressure : Not r density : Not	OSHA Z OSHA Z MX OEI MX OEI MX OEI established determined applicable determined determined
Components Calcium carbonate Calcium carbonate Image: Calcium carbonate Form Appearance Color Odour	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liquid : Visco : BRO : Very : Not a : Not a	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo ous, liquid Specif WN Bulk d faint Vapou	Respirable fraction. Total dust. DPERTIES ration rate : Not ic Gravity : Not lensity : Not r pressure : Not r density : Not	OSHA Z OSHA Z MX OEI MX OEI established determined applicable determined
Components Calcium carbonate Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liquid : Visco : BRO : Very : Not a : Inmm	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo ous, liquid Specif WN Bulk d faint Vapou applicable PH	Respirable fraction. Total dust. DPERTIES ration rate : Not ic Gravity : Not lensity : Not ir density : Not : Not	OSHA Z OSHA Z MX OEL MX OEL MX OEL established determined applicable determined determined
Components Calcium carbonate Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liquid : Visco : BRO : Very : Not a : Inmm	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo: ous, liquid Specif WN Bulk d faint Vapou applicable pH scible pH	Respirable fraction. Total dust. DPERTIES ration rate : Not ic Gravity : Not lensity : Not ir density : Not : Not	OSHA Z OSHA Z MX OEL MX OEL MX OEL established determined applicable determined determined

MATERIAL SAFETY DATA SHEET **FB468 JUTE BROWN SL**

Version Number 1.3 Revision Date 11/19/2007 Page 4 of 6 Print Date 12/2/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
123-77-3	Azodicarbonamide	sensitizer	Respiratory system.
1317-65-3 Calcium carbonate		Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
123-77-3	Azodicarbonamide	LC50	200 mg/l	rat
		Oral LD50	> 6,400 mg/kg	rat
		Dermal LD50	> 2,000 mg/kg	rabbit

Additional Health Hazard Information:

Azodicarbonamide 123-77-3 Sensitizer to the respiratory system with repeated minimal inhalation. While no chronic health problems have been identified, individuals with respiratory problems should avoid inhalation exposure to this material.

12. ECOLOGICAL INFORMATION		
Persistence and degradability	: Not readily biodegradable.	
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.	

PolyOne.

MATERIAL SAFETY DATA SHEET **FB468 JUTE BROWN SL**

Version Number 1.3 Revision Date 11/19/2007 Page 5 of 6 Print Date 12/2/2011

Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materi has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSC Inventory.
US. EPA CERCLA Hazardo	as Substances (40 CFR 302)
Not applicable	
California Proposition 65	n : Not applicable
SARA Title III Section 302 F	Extremely Hazardous Substance
Unless specific chemicals are	

MATERIAL SAFETY DATA SHEET FB468 JUTE BROWN SL

Version Number 1.3 Revision Date 11/19/2007 Page 6 of 6 Print Date 12/2/2011

SARA Title III Section 313 Toxic Chemicals:

l	Inless specific chemicals are identified under this section, this	s product is Not Ap	plicable under this	regulation
	Chemical Name	CAS-No.	Weight %	
	ZINC COMPOUNDS	Not Available	1 00 - 5 00	

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Bisphenol A	80-05-7	0.10 - 1.00	143
Miscellaneous Zinc Compounds	Not Available	1.00 - 5.00	241

Substances List (DSL) or are exempt.

WHMIS Classification	:	D2A
----------------------	---	-----

DSL

: All components of this product are on the Canadian Domestic

National Inventories:

Not determined
Not determined
Listed
Not determined
Not determined
Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.