# MATERIAL SAFETY DATA SHEET DMX1026BK BLACK SM1217

Version Number 1.1 Revision Date 06/01/2007 Page 1 of 7 Print Date 11/29/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DMX1026BK BLACK SM1217
Product code	:	FO20014432
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

## 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
1,2-Benzenedicarboxylic acid, butyl	85-68-7	10 - 30
phenylmethylester		

## **3. HAZARDS IDENTIFICATION**

### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

## POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion			
Acute exposure				
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.			
Ingestion	: May be harmful if swallowed.			
Eyes	: May cause eye/skin irritation.			
Skin	: Experience shows no unusual dermatitis hazard from routine handling.			
Chronic exposure	: Refer to Section 11 for Toxicological Information.			
Medical Conditions Aggravated by Exposure:	: None known.			

PolyOne.

# MATERIAL SAFETY DATA SHEET DMX1026BK BLACK SM1217

Version Number 1.1 Revision Date 06/01/2007 Page 2 of 7 Print Date 11/29/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>No data available</li> <li>No data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
1	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing

POLYONE CORPORATION

<u>PolyOne</u>.

# MATERIAL SAFETY DATA SHEET DMX1026BK BLACK SM1217

Version Number 1.1 Revision Date 06/01/2007 Page 3 of 7 Print Date 11/29/2011

Storage	Peri- accu : Kee and	e condensates may contain combustible or toxic residue. odically clean hoods, ducts, and other surfaces to minimize imulation of these materials. p containers dry and tightly closed to avoid moisture absorption contamination. Store in a cool dry place.
8. EXP	DSURE CO	ONTROLS / PERSONAL PROTECTION
Respiratory protection	: No p	personal respiratory protective equipment normally required.
Eye/Face Protection	: Safe	ty glasses with side-shields
Hand protection	: Prot	ective gloves
Skin and body protection	: Lon	g sleeved clothing
Additional Protective Measures	: Safe	ty shoes
General Hygiene Considerations		dle in accordance with good industrial hygiene and safety practice. h hands before breaks and at the end of workday.
Engineering measures		t only in areas with appropriate exhaust ventilation. Provide opriate exhaust ventilation at machinery.
Exposure limit(s)		

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: liqui
Appearance	: Visc
Color	: BLA
Odour	: Ver
Melting point/range	: Not
Boiling Point:	: Not
Water solubility	: Imn

#### quid iscous, liquid LACK ery faint ot applicable ot applicable nmiscible

### Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH

# Not established Not determined Not applicable Not determined Not determined Not applicable

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents., Avoid contact

# MATERIAL SAFETY DATA SHEET **DMX1026BK BLACK SM1217**

Version Number 1.1 Revision Date 06/01/2007 Page 4 of 7 Print Date 11/29/2011

with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition products
Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
85-68-7	1,2-Benzenedicarboxylic	Irritant	Eyes, Skin.
	acid, butyl		
	phenylmethylester		
		Systemic effects	Liver, reproductive system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
85-68-7	1,2-Benzenedicarboxylic	Oral LD50	2,330 mg/kg	rat
	acid, butyl	Dermal LD50	>10 gm/kg	rabbit
	phenylmethylester			

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

## **12. ECOLOGICAL INFORMATION**

Persistence and degradability

: Not readily biodegradable.

<u>PolyOne</u>

# MATERIAL SAFETY DATA SHEET DMX1026BK BLACK SM1217

Version Number 1.1 Revision Date 06/01/2007 Page 5 of 7 Print Date 11/29/2011

I Toxicity on Potential vice packaging ssification ng Name: ne: / Division	whole : No da : No da 13. DISI : Wher gener classi applid : Recyc has th and d and lo 14. TRA Environm 9 UN3082 III	e. ata available ata available <b>POSAL CON</b> re possible rec rator of waste fication, trans cable federal, cling is prefern re responsibili lisposal in acc ocal regulation	NSIDERAT ecycling is pr e material has asportation an , state/provin erred when po- lity for prope cordance wit ons.	eferred to dispo s the responsibi nd disposal in a ncial and local r pssible. The gen er waste classifi th applicable fea	osal or incine lity for prop ccordance w regulations. nerator of w ication, trans	eration. The per waste vith aste materia sportation
vice packaging ssification ng Name: ne: / Division	<ul> <li>No da</li> <li>13. DISI</li> <li>Wher gener classi applid</li> <li>Recyc has th and d and lo</li> <li>14. TRA</li> <li>Environm</li> <li>9 UN3082 III</li> </ul>	ata available <b>POSAL CON</b> re possible rec ator of waste fication, trans cable federal, cling is prefern ne responsibili lisposal in accu- pocal regulation <b>ANSPORT IN</b>	ecycling is pr e material ha isportation an , state/provin rred when po lity for prope cordance wit ons.	eferred to dispo s the responsibi nd disposal in a acial and local r ossible. The gen er waste classifi ch applicable feo <b>FION</b>	ility for prop ccordance w egulations. nerator of w ication, trans	er waste vith aste materia sportation
packaging ssification ng Name: ne: / Division	13. DISI         : Wher         gener         classi         applid         : Recyd         has th         and d         and d         and la         Environm         9         UN3082         III	POSAL CON re possible rec rator of waste fication, trans cable federal, cling is prefern re responsibili lisposal in acco ocal regulation	ecycling is pr e material ha isportation an , state/provin rred when po lity for prope cordance wit ons.	eferred to dispo s the responsibi nd disposal in a acial and local r ossible. The gen er waste classifi ch applicable feo <b>FION</b>	ility for prop ccordance w egulations. nerator of w ication, trans	er waste vith aste materia sportation
ssification ng Name: ne: / Division d	<ul> <li>Wher gener classi applic</li> <li>Recyclassi applic</li> <li>Recyclassi</li></ul>	re possible rec rator of waste fication, trans cable federal, cling is prefer- ne responsibili lisposal in acc- ocal regulation	ecycling is pr e material ha isportation an , state/provin rred when po lity for prope cordance wit ons.	eferred to dispo s the responsibi nd disposal in a acial and local r ossible. The gen er waste classifi ch applicable feo <b>FION</b>	ility for prop ccordance w egulations. nerator of w ication, trans	er waste vith aste materia sportation
ssification ng Name: ne: / Division d	gener classi applid : Recyc has th and d and lo 14. TRA Environm 9 UN3082 III	ator of waste fication, trans cable federal, cling is prefer- ne responsibili lisposal in accu- ocal regulation	e material has isportation an , state/provin erred when po- lity for prope cordance wit ons.	s the responsibind disposal in a disposal in a local responsible. The gener waste classifich applicable fea	ility for prop ccordance w egulations. nerator of w ication, trans	er waste vith aste materia sportation
ssification ng Name: ne: / Division d	has th and d and lo <b>14. TR</b> Environm 9 UN3082 III	ne responsibili disposal in acco ocal regulation	lity for prope cordance wit ons.	er waste classifi h applicable fea FION	ication, trans	sportation
ng Name: ne: / Division o d	Environm 9 UN3082 III					
ng Name: ne: / Division o d	9 UN3082 III	entally hazard	rdous substa	nces, liquid, n.o		
Division 2 d	UN3082 III			-	D.S.	
d		UN3082				
	111 9					
bstance antity:	Butyl benzyl phthalate 847 LB					
air)	Refer to s	pecific regula	ation.			
(maritime)	Refer to s	pecific regula	ation.			
	15. REG	ULATORY	INFORMA	TION		
is:						
Status	: Class	ified as hazar	rdous based	on components		
Status		-	f this produc	t are listed on o	r exempt fro	m the TSCA
CLA Hazardoı	us Substances	(40 CFR 302	2)			
al Name	CAS-No.	RQ for c				
	Status Status	s: Status : Class Status : All c Inven CLA Hazardous Substances	s: Status : Classified as haza Status : All components o Inventory.	s: Status : Classified as hazardous based Status : All components of this produc	Status       : Classified as hazardous based on components         Status       : All components of this product are listed on o Inventory.	s: Status : Classified as hazardous based on components. Status : All components of this product are listed on or exempt fro Inventory.

# MATERIAL SAFETY DATA SHEET DMX1026BK BLACK SM1217

Version Number 1.1 Revision Date 06/01/2007 Page 6 of 7 Print Date 11/29/2011

1,2-Benzenedicarb	85-68-7	100 lbs	847 LB
oxylic acid, butyl			
phenylmethylester			

California Proposition 65

: WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight %	NPRI ID#
1,2-Benzenedicarboxylic acid, butyl	85-68-7	10.00 - 30.00	37
phenylmethylester			

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.	
85-68-7	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Not determined

:

PolyOne

# MATERIAL SAFETY DATA SHEET DMX1026BK BLACK SM1217

Version Number 1.1 Revision Date 06/01/2007 Page 7 of 7 Print Date 11/29/2011

Philippines PICCS

: Not determined

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.