MATERIAL SAFETY DATA SHEET

DB4120 NEUTRAL

Version Number 1.0 Revision Date 10/04/2006 Page 1 of 7 Print Date 11/24/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:number	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	DB4120 NEUTRAL
Product code	FO20015104
Chemical Name	Mixture
CAS-No.	Mixture
Product Use	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Di(2-ethylhexyl)phthalate	117-81-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET **DB4120 NEUTRAL**

Version Number 1.0 Revision Date 10/04/2006 Page 2 of 7 Print Date 11/24/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available Not applicable Carbon dioxide blanket, water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all
	 6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



MATERIAL SAFETY DATA SHEET **DB4120 NEUTRAL**

fume condensates may contain combustible or toxic r Periodically clean hoods, ducts, and other surfaces to accumulation of these materials. Storage : Keep containers dry and tightly closed to avoid moist and contamination. Store in a cool dry place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection : No personal respiratory protective equipment normall Eye/Face Protection : Safety glasses with side-shields. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Handle in accordance with good industrial hygiene an Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilatio appropriate exhaust ventilation at machinery. Exposure limit(s) : Value Exposure time Exposure type Di(2-ethylhexyl)phthal 5 mg/m3 Time Weighted Average (TWA): Vapor. ate 5 mg/m3 Time Weighted Average (TWA): Vapor. Di 0 mg/m3 Short Term Exposure Limit (STEL): Short Term Exposure Limit (STEL): Short Term Exposure Limit (STEL): <th>Number 1.0 Date 10/04/2006</th> <th></th> <th></th> <th>Print</th> <th>Page 3 Date 11/24/2</th>	Number 1.0 Date 10/04/2006			Print	Page 3 Date 11/24/2
and contamination. Store in a cool dry place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection : No personal respiratory protective equipment normall Eye/Face Protection : Safety glasses with side-shields. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Handle in accordance with good industrial hygiene and Considerations Considerations : Heat only in areas with appropriate exhaust ventilation at machinery. Exposure limit(s) : Value Exposure time Exposure type Di(2-ethylhexyl)phthal 5 mg/m3 PEL: Vapor. ate : 10 mg/m3 Short Term Exposure Limit (STEL); 9. PHYSICAL AND CHEMICAL PROPERTIES		Р	eriodically clean hoods, duct	s, and other surfaces to i	
Respiratory protection : No personal respiratory protective equipment normall Eye/Face Protection : Safety glasses with side-shields. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Safety shoes. General Hygiene : Handle in accordance with good industrial hygiene and Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilatio appropriate exhaust ventilation at machinery. Exposure limit(s) : Value Exposure time Exposure type Di(2-ethylhexyl)phthal 5 mg/m3 PEL: Vapor. ite 10 mg/m3 Short Term Exposure Limit (STEL): 9. PHYSICAL AND CHEMICAL PROPERTIES	age				re absorption
Eye/Face Protection : Safety glasses with side-shields. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Mandle in accordance with good industrial hygiene and Considerations General Hygiene : Handle in accordance with good industrial hygiene and Considerations Engineering measures : Heat only in areas with appropriate exhaust ventilatio appropriate exhaust ventilation appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exposure type Di(2-ethylhexyl)phthal 5 mg/m3 PEL: Vapor. ite : 5 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Short Term Exposure Limit (STEL): 9. PHYSICAL AND CHEMICAL PROPERTIES	8. EXI	POSURE	CONTROLS / PERSONA	L PROTECTION	
Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : General Hygiene : Handle in accordance with good industrial hygiene and Considerations Engineering measures : Heat only in areas with appropriate exhaust ventilation appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation at machinery. Exposure limit(s) : Value Exposure time Exposure type Di(2-ethylhexyl)phthal 5 mg/m3 PEL: Vapor. ite 5 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Short Term Exposure Limit (STEL): 9. PHYSICAL AND CHEMICAL PROPERTIES	piratory protection	: N	lo personal respiratory protec	ctive equipment normally	y required.
Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Safety shoes. General Hygiene : Handle in accordance with good industrial hygiene and Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation at machinery. Exposure limit(s) : Value Exposure time Exposure type Di(2-ethylhexyl)phthal 5 mg/m3 PEL: Vapor. ite : 5 mg/m3 Time Weighted Average I0 mg/m3 Short Term Exposure Limit (STEL): 9. PHYSICAL AND CHEMICAL PROPERTIES	/Face Protection	: S	afety glasses with side-shield	ls.	
Additional Protective : Safety shoes. Measures : Handle in accordance with good industrial hygiene and Considerations General Hygiene : Handle in accordance with good industrial hygiene and Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation appropriate exhaust ventilation at machinery. Exposure limit(s) : <u>Components</u> Value Exposure time Exposure type Di(2-ethylhexyl)phthal 5 mg/m3 PEL: Vapor. ate 5 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Short Term Exposure Limit (STEL): 9. PHYSICAL AND CHEMICAL PROPERTIES	d protection	: P	rotective gloves.		
Measures General Hygiene Considerations : Handle in accordance with good industrial hygiene and Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation appropriate exhaust ventilation at machinery. Exposure limit(s) : Components Value Exposure time Exposure type Di(2-ethylhexyl)phthal 5 mg/m3 PEL: Vapor. ite 5 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Short Term Exposure Limit (STEL): 9. PHYSICAL AND CHEMICAL PROPERTIES	and body protection	: L	ong sleeved clothing.		
Considerations Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation appropriate exhaust ventilation at machinery. Exposure limit(s) Exposure time Exposure type Di(2-ethylhexyl)phthal 5 mg/m3 PEL: Vapor. ate 5 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Short Term Exposure Limit (STEL): 9. PHYSICAL AND CHEMICAL PROPERTIES Exposure Limit (STEL): Exposure Limit (STEL): Exposure Limit (STEL):		: S	afety shoes.		
appropriate exhaust ventilation at machinery. Exposure limit(s) Components Value Exposure time Exposure type Di(2-ethylhexyl)phthal 5 mg/m3 PEL: Vapor. dite 5 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Short Term Exposure Limit (STEL):					l safety practic
Components Value Exposure time Exposure type Di(2-ethylhexyl)phthal 5 mg/m3 PEL: Vapor. ate 5 mg/m3 Time Weighted Average (TWA): Vapor. 10 mg/m3 Short Term Exposure Limit (STEL): 9. PHYSICAL AND CHEMICAL PROPERTIES	ineering measures				n. Provide
Di(2-ethylhexyl)phthal 5 mg/m3 PEL: Vapor. ate 5 mg/m3 Time Weighted Average (TWA): Vapor. 10 mg/m3 Short Term Exposure Limit (STEL): 9. PHYSICAL AND CHEMICAL PROPERTIES	osure limit(s)				
ate 5 mg/m3 Time Weighted Average (TWA): 10 mg/m3 Short Term Exposure Limit (STEL): 9. PHYSICAL AND CHEMICAL PROPERTIES	Components	Value	Exposure time	Exposure type	List:
(TWA): 10 mg/m3 Short Term Exposure Limit (STEL): 9. PHYSICAL AND CHEMICAL PROPERTIES	• • •	mg/m3	PEL:	Vapor.	OSHA ZI
10 mg/m3 Short Term Exposure Limit (STEL): 9. PHYSICAL AND CHEMICAL PROPERTIES	5	mg/m3	.		MX OEL
	1) mg/m3	Short Term Exposure Limit	t	MX OEL
Form : liquid Evaporation rate . N	9	. PHYSIC	CAL AND CHEMICAL PR	OPERTIES	
		: liqui · Visc	1		ot established ot determined

Appearance Color Odor Melting point/range Boiling Point: Water solubility : Viscous, liquid
: NO PIGMENT
: Very faint
: Not applicable
: Not applicable
: Immiscible

Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH Not established
Not determined
Not applicable
Not determined
Not determined
Not applicable

10. STABILITY AND REACTIVITY

Stability

: Stable.



MATERIAL SAFETY DATA SHEET **DB4120 NEUTRAL**

Version Number 1.0 Revision Date 10/04/2006 Page 4 of 7 Print Date 11/24/2011

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
117-81-7	Di(2-ethylhexyl)phthalate	Systemic effects	Eyes, Respiratory system, Liver, central nervous system (CNS), Skin, digestive system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
117-81-7	Di(2-ethylhexyl)phthalate	Oral LD50	30 gm/kg	rat
		Dermal LD50	25 gm/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

	CAS-No.	Chemical Name	OSHA	IARC	NTP
--	---------	---------------	------	------	-----

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

PolyOne.

MATERIAL SAFETY DATA SHEET

DB4120 NEUTRAL

Version Number 1.0 Revision Date 10/04/2006 Page 5 of 7 Print Date 11/24/2011

Additional Health Hazard Information:

Di(2-ethylhexyl)phthalate 117-81-7 There is sufficient evidence for the carcinogenicity of di (2-ethylhexyl) phthalate in experimental animals. Administered in the feed this chemical caused an increase incidence of liver cancer in male and female rats and mice. The relevance of this finding to humans is uncertain.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification Proper Shipping Name: Technical Name:	_
Proper Shipping Name: Technical Name: Hazard Class / Division	14. TRANSPORT INFORMATION Environmentally hazardous substances, liquid, n.o.s. 9
Proper Shipping Name: Technical Name: Hazard Class / Division UN Number	14. TRANSPORT INFORMATION Environmentally hazardous substances, liquid, n.o.s. 9 UN3082
Proper Shipping Name: Technical Name: Hazard Class / Division UN Number Packing Group	14. TRANSPORT INFORMATION Environmentally hazardous substances, liquid, n.o.s. 9
Proper Shipping Name: Technical Name: Hazard Class / Division UN Number	14. TRANSPORT INFORMATION Environmentally hazardous substances, liquid, n.o.s. 9 UN3082 III
Proper Shipping Name: Technical Name: Hazard Class / Division UN Number Packing Group Label Required Hazardous Substance	14. TRANSPORT INFORMATION Environmentally hazardous substances, liquid, n.o.s. 9 UN3082 III 9 Diethylhexyl phthalate UN3082
Proper Shipping Name: Technical Name: Hazard Class / Division UN Number Packing Group Label Required Hazardous Substance Reportable quantity:	14. TRANSPORT INFORMATION Environmentally hazardous substances, liquid, n.o.s. 9 UN3082 III 9 Diethylhexyl phthalate 198 LB

MATERIAL SAFETY DATA SHEET **DB4120 NEUTRAL**

Version Numb	er 1.0
Revision Date	10/04/2006

Page 6 of 7 Print Date 11/24/2011

OSHA Status : Classified as hazardous based on components.

TSCA Status

All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

:

Chemical Name	CAS-No.	- x	RQ for Mixture/Product
Di(2-ethylhexyl)ph	117-81-7	100 lbs	198 LB
thalate			

California Proposition 65

: WARNING! This product contains a chemical known to the State of California to cause cancer., WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
DI(2-ETHYLHEXYL)PHTHALATE (DEHP)	117-81-7	30.00 - 60.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight %	NPRI ID#
Di(2-ethylhexyl)phthalate	117-81-7	30.00 - 60.00	25

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
117-81-7	

DSL

: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Listed

PolyOne

MATERIAL SAFETY DATA SHEET **DB4120 NEUTRAL**

Version Number 1.0 Revision Date 10/04/2006 Page 7 of 7 Print Date 11/24/2011

China IECS:ListedEurope EINECS:ListedJapan ENCS:ListedKorea KECI:ListedPhilippines PICCS:Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.