## MATERIAL SAFETY DATA SHEET **DB3839 RED**

Version Number 1.2 Revision Date 01/18/2007

Page 1 of 6 Print Date 11/26/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DB3839 RED
Product code	:	FO20015345
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

## 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	5 - 10

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion	
Acute exposure		
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.	
Ingestion	: May be harmful if swallowed.	
Eyes	: May cause eye/skin irritation.	
Skin	: Experience shows no unusual dermatitis hazard from routine handling.	
Chronic exposure	: Refer to Section 11 for Toxicological Information.	
Medical Conditions Aggravated by Exposure:	: None known.	

PolyOne.

# MATERIAL SAFETY DATA SHEET **DB3839 RED**

Version Number 1.2 Revision Date 01/18/2007 Page 2 of 6 Print Date 11/26/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If e irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists se medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits	
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Autoignition temperature	: Not applicable
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foam.
Suituble extinguishing media	. Carbon dioxide blanket, water spray, dry powder, roani.
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures	pressure mode should be worn to prevent inhalation of airborne
	contaminants.
Unusual Fire/Explosion	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) und
Hazards	fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxic of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	5. ACCIDENTAL RELEASE MEASURES
	XX7
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or t soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid bind universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



# MATERIAL SAFETY DATA SHEET **DB3839 RED**

			Print D	Page 3 ate 11/26/2
	Р	ume condensates may contain or eriodically clean hoods, ducts, ccumulation of these materials	and other surfaces to mi	
Storage	: Keep containers dry and tightly closed to avoid moisture absorpt and contamination. Store in a cool dry place.			e absorption
8. H	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	lo personal respiratory protecti	ve equipment normally r	equired.
Eye/Face Protection	: S	afety glasses with side-shields		
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations		: Handle in accordance with good industrial hygiene and safety practic Wash hands before breaks and at the end of workday.		
Engineering measures		: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.		
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Components Calcium carbonate	Value 5 mg/m3	Exposure time PEL:	Exposure type Respirable fraction.	
		PEL: PEL:		OSHA Z
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z
	5 mg/m3 15 mg/m3	PEL: PEL: Time Weighted Average	Respirable fraction.	OSHA Z OSHA Z MX OEL
	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit	Respirable fraction. Total dust.	OSHA Z OSHA Z MX OEL
Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSI	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Respirable fraction. Total dust.	OSHA Z OSHA Z MX OEL
Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liqui	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo	Respirable fraction. Total dust. DPERTIES ration rate : Not	OSHA Z OSHA Z MX OEL MX OEL
Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liqui	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo ous, liquid Specif	Respirable fraction.   Total dust.   DPERTIES   ration rate : Not   ic Gravity: : Not	OSHA Z OSHA Z MX OEL MX OEL established determined
Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liqui : Visc : RED	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo ous, liquid Specif Bulk d	Respirable fraction.   Total dust.   DPERTIES   ration rate : Not   ic Gravity: : Not   ensity : Not	OSHA Z OSHA Z MX OEL MX OEL established
Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liqui : Visc : RED : Very	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo ous, liquid Specific Bulk d y faint Vapor	Respirable fraction.   Total dust.   DPERTIES   ration rate : Not   ic Gravity: : Not   ensity : Not   pressure : Not	OSHA Z OSHA Z MX OEL MX OEL established determined applicable
Calcium carbonate Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIO : liqui : Visc : RED : Very : Not : Not	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo ous, liquid Specif b Bulk d v faint Vapor applicable Vapou applicable pH	Respirable fraction.   Total dust.   DPERTIES   ration rate : Not   ic Gravity: : Not   ensity : Not   pressure : Not   r density : Not	OSHA Z OSHA Z MX OEL MX OEL established determined applicable determined
Calcium carbonate Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIO : liqui : Visc : RED : Very : Not	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo ous, liquid Specif b Bulk d v faint Vapor applicable Vapou applicable pH	Respirable fraction.   Total dust.   DPERTIES   ration rate : Not   ic Gravity: : Not   ensity : Not   pressure : Not   r density : Not	OSHA Z OSHA Z MX OEL MX OEL MX OEL established determined applicable determined determined
Calcium carbonate Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liqui : Visc : RED : Very : Not : Imm	PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapo ous, liquid Specif b Bulk d v faint Vapor applicable Vapou applicable pH	Respirable fraction.   Total dust.   DPERTIES   ration rate : Not   ic Gravity: : Not   ensity : Not   r density : Not   : Not	OSHA Z OSHA Z MX OEL MX OEL MX OEL established determined applicable determined determined
Calcium carbonate Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liqui : Visc : RED : Very : Not : Imm 10. §	PEL:   PEL:   Time Weighted Average (TWA):   Short Term Exposure Limit (STEL):   CAL AND CHEMICAL PRO   d Evapo:   ous, liquid Specif   b Bulk d   v faint Vapou   applicable pH   iscible PRO	Respirable fraction.   Total dust.   DPERTIES   ration rate : Not   ic Gravity: : Not   ensity : Not   r density : Not   : Not	OSHA Z OSHA Z MX OEL MX OEL MX OEL established determined applicable determined determined
Calcium carbonate	5 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : liqui : Visc : RED : Very : Not : Imm 10. §	PEL:   PEL:   Time Weighted Average (TWA):   Short Term Exposure Limit (STEL):   CAL AND CHEMICAL PRO   d Evapo   ous, liquid Specific   y faint Vapor   applicable pH   iscible STABILITY AND REACTIV	Respirable fraction.   Total dust.   DPERTIES   ration rate : Not   ic Gravity: : Not   ensity : Not   r density : Not   : Not	OSHA ZI OSHA ZI MX OEL MX OEL MX OEL established determined applicable determined determined



## MATERIAL SAFETY DATA SHEET **DB3839 RED**

Version Number 1.2 Revision Date 01/18/2007 Page 4 of 6 Print Date *11/26/2011* 

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

## 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

### **12. ECOLOGICAL INFORMATION**

Additional advice	:	No data available
<b>Bioaccumulation Potential</b>	:	No data available
Environmental Toxicity	:	Environmental toxicity has not been established for this mixture as a whole.
Persistence and degradability	:	Not readily biodegradable.

Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

PolyOne.

# MATERIAL SAFETY DATA SHEET **DB3839 RED**

#### Version Number 1.2 Revision Date 01/18/2007

\_\_\_\_\_

Page 5 of 6 Print Date 11/26/2011

	14. TRANSPORT INFORMATION		
U.S. DOT Classification	Refer to specific regulation.		
ICAO/IATA (air)	Refer to specific regulation.		
IMO / IMDG (maritime)	Refer to specific regulation.		
]]	15. REGULATORY INFORMATION		
US Regulations:			
OSHA Status	Classified as hazardous based on components.		
TSCA Status	All components of this product are listed on or exempt from the TSCA Inventory.		
US. EPA CERCLA Hazardous Su	bstances (40 CFR 302)		
Not applicable			
California Proposition 5	Not applicable		
SARA Title III Section 302 Extrem	mely Hazardous Substance		
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation			
SARA Title III Section 313 Toxic Chemicals:			
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation			
Canadian Regulations:			
National Pollutant Release	Inventory (NPRI)		
Not applicable			
WHMIS Classification	Not controlled.		
DSL	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.		

PolyOne

## MATERIAL SAFETY DATA SHEET **DB3839 RED**

Version Number 1.2 Revision Date 01/18/2007 Page 6 of 6 Print Date 11/26/2011

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

## **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.