PolvOne

MATERIAL SAFETY DATA SHEET 10545UB UNDERBASE GRAY

Version Number 1.5 Revision Date 01/18/2008 Page 1 of 7 Print Date 12/3/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	10545UB UNDERBASE GRAY
Product code :	FO20015410
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Carbon	7440-44-0	5 - 10
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET 10545UB UNDERBASE GRAY

Version Number 1.5 Revision Date 01/18/2008 Page 2 of 7 Print Date 12/3/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET 10545UB UNDERBASE GRAY

Version Number 1.5 Revision Date 01/18/2008		Page 3 of 7 Print Date 12/3/2011
Handling	:	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue.
		Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXI	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

Components	Value	Exposure time	Exposure type	List:
Silica, amorphous	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance liquidViscous, liquid

Evaporation rate Specific Gravity Not establishedNot determined

MATERIAL SAFETY DATA SHEET 10545UB UNDERBASE GRAY

Version Number 1.5 Revision Date 01/18/2008

Color Odour Melting point/range Boiling Point: Water solubility	:	Ve No No	REY ery faint ot applicable ot applicable miscible	Bulk density Vapour pressure Vapour density pH	:	Not applicable Not determined Not determined Not applicable
		10	. STABILITY AND R	EACTIVITY		
Stability		:	Stable.			
Hazardous Polymerization		:	Will not occur.			
Conditions to avoid		:	Keep away from oxidiz decomposition, do not		lame.	To avoid thermal
Incompatible Materials		:	Incompatible with stro with acetal homopolyn	0	0	
Hazardous decomposition products		:	Carbon dioxide (CO2), (NOx), hydrogen chlor smoke are all possible. degradation. As a gene after one hour at 177 °C °F), and within 5 minu	ide (HCl), other hazard Prolonged heating ma eral rule of thumb, deg C (350 °F), after 10 mi	dous 1 ay res radati nutes	materials, and ult in product on begins to occur

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7440-44-0	Carbon	Systemic effects	Respiratory system, heart or
			circulatory system.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
7631-86-9	Silica, amorphous	Oral LD50Oral LD50	15,000 mg/kg22,500 mg/kg	mouserat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

Page 4 of 7 Print Date 12/3/2011

olvOn<u>e</u>



PolyOne.

MATERIAL SAFETY DATA SHEET 10545UB UNDERBASE GRAY

Version Number 1.5 Revision Date 01/18/2008 Page 5 of 7 Print Date 12/3/2011

CAS-No.		mical Name	OSHA	IARC	NTP	
13463-67-7	Titanium d	ioxide	no	2B	no	
IARC Carcinogen C 1 - The component i 2A - The component 2B - The component NTP Carcinogen Cla 1 - The component i 2 - The component i	s carcinogenic f is probably car is possibly car assifications: s known to be a s reasonably an	rcinogenic to huma cinogenic to human human carcinoger ticipated to be a hu	ns. 1. ıman carcinogen.			
	12	2. ECOLOGICAL	INFORMATION			
Persistence and degr	adability :	Not readily biode	gradable.			
Environmental Toxi	city :	Environmental to whole.	xicity has not been e	established for this	s mixture as a	
Bioaccumulation Po	tential :	No data available	;			
Additional advice	:	No data available	9			
	1.	3. DISPOSAL CO	NSIDERATIONS			
Product Contaminated packa	: ging ·	generator of wast classification, tra applicable federa	ecycling is preferred e material has the re nsportation and disp l, state/provincial an erred when possible.	sponsibility for pr osal in accordance d local regulation	oper waste with s.	
	<i>ы</i> ш <u>а</u> .	material has the r transportation and	esponsibility for pro d disposal in accorda nd local regulations.	per waste classific ance with applicab	cation,	
	1	4. TRANSPORT	INFORMATION			
U.S. DOT Classifica	tion :	Refer to specific	regulation.			
ICAO/IATA (air)	:	: Refer to specific regulation.				
IMO / IMDG (marit	ime) :	Refer to specific	regulation.			
	15	. REGULATORY	INFORMATION			
US Regulations:						

hlvUn<u>e</u>

MATERIAL SAFETY DATA SHEET 10545UB UNDERBASE GRAY

Version Number 1.5 Revision Date 01/18/2008 Page 6 of 7 Print Date 12/3/2011

TSCA Status All components of this product are listed on or exempt from the : TSCA Inventory. US. EPA CERCLA Hazardous Substances (40 CFR 302) Not applicable California Proposition : Not applicable 65 SARA Title III Section 302 Extremely Hazardous Substance Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation SARA Title III Section 313 Toxic Chemicals: Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation Canadian Regulations: National Pollutant Release Inventory (NPRI) Not applicable WHMIS Classification : D2A WHMIS Ingredient Disclosure List CAS-No. 7631-86-9 DSL All components of this product are on the Canadian Domestic : Substances List (DSL) or are exempt. National Inventories: Australia AICS : Not determined China IECS : Not determined Europe EINECS · Listed Japan ENCS Not determined :

PolyOne

MATERIAL SAFETY DATA SHEET 10545UB UNDERBASE GRAY

Version Number 1.5 Revision Date 01/18/2008 Page 7 of 7 Print Date 12/3/2011

Korea KECI

: Not determined

Philippines PICCS

: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.