### MATERIAL SAFETY DATA SHEET DB4086A ORANGE (SM1110-0037)

Version Number 1.7 Revision Date 03/12/2014 Page 1 of 7 Print Date 3/19/2014

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DB4086A ORANGE (SM1110-0037)
Product code	:	FO20015641
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
1,2-Benzenedicarboxylic acid, butyl	85-68-7	1 - 5
phenylmethylester		
Calcium carbonate	1317-65-3	5 - 10

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.		
Ingestion	: May be harmful if swallowed.		
Eyes	: May cause eye and skin irritation.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		

PolyOne

# MATERIAL SAFETY DATA SHEET **DB4086A ORANGE (SM1110-0037)**

Version Number 1.7 Revision Date 03/12/2014 Page 2 of 7 Print Date 3/19/2014

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: no data available
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media	<ul> <li>no data available</li> <li>no data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under</li> </ul>
Hazards	fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal.
	7. HANDLING AND STORAGE

PolyOne.

# MATERIAL SAFETY DATA SHEET **DB4086A ORANGE (SM1110-0037)**

ion Number 1.7 sion Date 03/12/2014				Prin	Page 3 t Date 3/19/2
Handling	ft P	ume condensates ma	ay contain o oods, ducts,	iate exhaust ventilation combustible or toxic rea and other surfaces to n	sidue.
Storage		Leep containers dry nd contamination.		closed to avoid moistu ool dry place.	re absorption
8. ]	EXPOSURE	CONTROLS/PE	RSONAL I	PROTECTION	
Respiratory protection	: N	lo personal respirate	ory protecti	ve equipment normally	required.
Eye/Face Protection	: S	afety glasses with s	ide-shields		
Hand protection	: P	rotective gloves			
Skin and body protection	: L	ong sleeved clothin	ıg		
Additional Protective Measures	: S	afety shoes			
General Hygiene Considerations				l industrial hygiene and eaks and at the end of v	
Engineering measures Exposure limit(s)		leat only in areas w ppropriate exhaust v		iate exhaust ventilation at machinery.	. Provide
Components	Value	Exposure ti	me	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:		Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:		Total dust.	OSHA ZI
	10 mg/m3	Time Weighted (TWA):	0	Total dust.	MX OEL
	20 mg/m3	Short Term Expos (STEL):			MX OEL
	9. PHYSI	CAL AND CHEM	ICAL PRO	PERTIES	
<b>F</b>	1	1	<b>F</b>		4 4 . 1. 12 . 1 1
Form	: liqui		Evapouration rate : Not established Specific Gravity : Not determined		
Appearance Colour		ous, liquid MGE	Bulk d		ot applicable
Odour		faint			ot determined
Melting point/range	•	pplicable	Vapour density : Not determined		
		pplicable	рH		ot applicable
			r		11
Boiling Point: Water solubility	: imm	iscible			
Boiling Point:	: imm	iscible STABILITY AND	REACTIV	<b>/ITY</b>	

# MATERIAL SAFETY DATA SHEET **DB4086A ORANGE (SM1110-0037)**

Version Number 1.7 Revision Date 03/12/2014 Page 4 of 7 Print Date 3/19/2014

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
85-68-7	1,2-Benzenedicarboxylic acid, butyl	Irritant	Eyes, Skin.
	phenylmethylester		
		Systemic effects	Liver, reproductive system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
85-68-7	1,2-Benzenedicarboxylic	Oral LD50	2,330 mg/kg	rat
	acid, butyl	Dermal LD50	> 10 gm/kg	rabbit
	phenylmethylester	Dermal LD50	6,700 mg/kg	rat
		Dermal LD50	6,700 mg/kg	mouse

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability

: Not readily biodegradable.

whole.

Environmental Toxicity

: Environmental toxicity has not been established for this mixture as a

PolyOne

# MATERIAL SAFETY DATA SHEET **DB4086A ORANGE (SM1110-0037)**

Version Number 1.7 Revision Date 03/12/2014 Page 5 of 7 Print Date 3/19/2014

	13. DISI	POSAL CONSIDERAT	IUNS	
Product	gener classi	ator of waste material has fication, transportation an	eferred to disposal or inciner the responsibility for prope d disposal in accordance wi cial and local regulations.	r waste
Contaminated packaging	mater transp	ial has the responsibility	ossible. The generator of wa for proper waste classification accordance with applicable f ations.	on,
	14. TRA	ANSPORT INFORMAT	TION	
U.S. DOT Classification	: Refer	to specific regulation.		
ICAO/IATA	: Refer	to specific regulation.		
IMO/IMDG (maritime)	: Refer	to specific regulation.		
	15. REG	ULATORY INFORMA	TION	
US Regulations:				
OSHA Status	: Class	ified as hazardous based o	on components.	
TSCA Status		omponents of this produc A Inventory.	t are listed on or exempt fro	m the
US. EPA CERCLA Hazard	ous Substances	(40 CFR 302)		
Chemical Name	CAS-No.	RQ for component	RQ for Mixture/Product	
1,2- Benzenedicarboxyl ic acid, butyl phenylmethylester	85-68-7	100 lbs	2,128 LB	

### MATERIAL SAFETY DATA SHEET DB4086A ORANGE (SM1110-0037)

Version Number 1.7 Revision Date 03/12/2014 Page 6 of 7 Print Date 3/19/2014

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Bis (2-ethylhexyl) adipate	103-23-1	10.00 - 30.00	
1,2-Benzenedicarboxylic acid, butyl	85-68-7	1.00 - 5.00	
phenylmethylester			

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.
103-23-1
85-68-7

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

:

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing,

PolyOne.

# MATERIAL SAFETY DATA SHEET **DB4086A ORANGE (SM1110-0037)**

Version Number 1.7 Revision Date 03/12/2014 Page 7 of 7 Print Date 3/19/2014

storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.