MATERIAL SAFETY DATA SHEET *M 012 DOWDIDE A (10%) SOLUTION

Version Number 1.0 Revision Date 02/16/2007 Page 1 of 6 Print Date 11/26/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone : Emergency telephone : number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	*M 012 DOWDIDE A (10%) SOLUTION
Product code	:	FO20015981
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
[1,1-Biphenyl]-2-ol, sodium salt, tetrahydrate	6152-33-6	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This product has not been evaluated as a whole for health effects. Information provided on the health effects of this product is based on individual components. In addition, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Skin contact, Inhalation, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	:
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne

MATERIAL SAFETY DATA SHEET *M 012 DOWDIDE A (10%) SOLUTION

Version Number 1.0 Revision Date 02/16/2007 Page 2 of 6 Print Date 11/26/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of vapors or fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Never give anything by mouth to an unconscious person. Seek medical attention if necessary. Do not induce vomiting without medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available No data available carbon dioxide (CO2), water, foam, dry chemical. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Cool closed containers exposed to fire with water spray Do not allow run-off from fire fighting to enter drains or water course Burning dry latex produces dense black smoke with the possibility of toxic vapors. Residual latex material contained in empty drums may decompose when burned producing toxic or irritating fumes. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Ensure response personnel are properly protected (see section 8 for respiratory or other protection guidelines.) Use caution as floors may be slippery.
Environmental precautions	: The product should not be allowed to enter drains, water courses or th soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binde universal binder, sawdust). Sweep up and shovel into suitable containers for disposal.

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET *M 012 DOWDIDE A (10%) SOLUTION

Version Number 1.0 Revision Date 02/16/2007 Page 3 of 6 Print Date 11/26/2011

	7. HANDLIN	G AND STORAGE
Handling	Prolonged hea	ea provided with appropriate exhaust ventilation. ting may result in product degradation. Material may torage. Careful mixing without introduction of air ma before use.
Storage	upright to pre	nich are opened must be carefully resealed and kept vent leakage. Keep in a dry, cool place. Keep from emperature extremes.
8. EXP	OSURE CONTROL	S / PERSONAL PROTECTION
Respiratory protection	areas of good processing eq	normally not required for routine handling of product general ventilation and adequate local exhaust at upment during routine operation. Airborne contamina be maintained below the occupational exposure
Eye/Face Protection		with side-shields. Wear goggles or face shield during t present a splash potential.
Hand protection	: Impervious gl	oves such as rubber or PVC
Skin and body protection	Where operation	shirts and long pants are adequate for normal handling ons present a splash or spill potential, employees shou lly resistant clothing, boots, apron, gloves, and eye/fac
Additional Protective Measures	: Safety shoes.	
General Hygiene Considerations		efore breaks and immediately after handling the produc ordance with good industrial hygiene and safety
Engineering measures		tilation and/or appropriate respiratory protection may sary to minimize employee exposure to processing
Exposure limit(s)		
9.	PHYSICAL AND C	CHEMICAL PROPERTIES
Form	: liquid	Evaporation rate : Slower than But
Appearance	: liquid	Acetate Specific Gravity: : Not determined

MATERIAL SAFETY DATA SHEET *M 012 DOWDIDE A (10%) SOLUTION

Version Number 1.0 Revision Date 02/16/2007

Color

Odor

Melting point/range Boiling Point: Water solubility	: N	ot applicable ot established ompletely miscible	Vapour density pH		Heavier than air. Not determined	
	1	0. STABILITY AND R	EACTIVITY			
Stability	:	Stable.				
Hazardous Polymerization	:	Will not occur.				
Conditions to avoid	:	Extremes of temperatu	re and direct sunlight.	Keer	p from freezing.	
Incompatible Materials	:	Acids, metal salts, and	solvents			
Hazardous decomposition products	:		, carbon monoxide (CC as materials, and smoke		e	

Bulk density

Vapor pressure

: NO PIGMENT

: Slight

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
	•		· · · ·

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
6152-33-6	[1,1-Biphenyl]-2-ol,	Oral LD50	1,049 mg/kg	rat
sodium salt, tetrahydrate				

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
6152-33-6	[1,1-Biphenyl]-2-ol, sodium	no	2B	no
	salt, tetrahydrate			

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:



:

:

Page 4 of 6

Print Date 11/26/2011

Not applicable

Not established

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET *M 012 DOWDIDE A (10%) SOLUTION

Version Number 1.0 Revision Date 02/16/2007 Page 5 of 6 Print Date 11/26/2011

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: No data available
Environmental Toxicity	: No data available
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSC. Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET *M 012 DOWDIDE A (10%) SOLUTION

Version Number 1.0 Revision Date 02/16/2007				Print Date	Page 6 of 6 11/26/2011
California Proposition 65	:	WARNING! This produ California to cause cance		mical known to the	State of
SARA Title III Section 302 Ex	rem	ely Hazardous Substance			
Unless specific chemicals are id	lenti	fied under this section, thi	s product is Not A	Applicable under th	is regulation
SARA Title III Section 313 To Unless specific chemicals are id			s product is Not /	Annlicable under th	nis regulation
Chemical Name	ienti	fied under this section, the	CAS-No.	Weight %	
SODIUM O-PHENYLPHEN	IOX	IDE	6152-33-6	5.00 - 10.00	
Not applicable WHMIS Classification DSL	:	Not controlled. All components of this p Substances List (DSL) or		canadian Domest	ic
National Inventories:					
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Not determined			
Japan ENCS	:	Not determined			
Korea KECI	:	Not determined			
Philippines PICCS	:	Listed			
		16. OTHER INFORM	ATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.