MATERIAL SAFETY DATA SHEET **DOP REDUCER**

Version Number 1.0 Revision Date 03/12/2007 Page 1 of 7 Print Date 11/26/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DOP REDUCER
Product code	:	FO20016113
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Di(2-ethylhexyl)phthalate	117-81-7	60 - 100

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET **DOP REDUCER**

Version Number 1.0 Revision Date 03/12/2007 Page 2 of 7 Print Date 11/26/2011

Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.	of
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If e irritation persists, seek medical attention.	eye
Skin	: Wash off with soap and plenty of water. If skin irritation persists se medical attention.	eel
	5. FIRE-FIGHTING MEASURES	
Flash point	: No data available	
Elemmedale Limite		
Flammable Limits Upper explosion limit	: No data available	
Lower explosion limit	: No data available	
Autoignition temperature	: Not applicable	
Suitable extinguishing media	••	
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foam.	
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positiv	'e
Procedures	pressure mode should be worn to prevent inhalation of airborne	
	contaminants.	
Unusual Fire/Explosion	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) und	dei
Hazards	fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxid	
	of nitrogen (NOx), other hazardous materials, and smoke are all	
	possible.	
	5. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: The product should not be allowed to enter drains, water courses or soil. Should not be released into the environment.	th
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid bind universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for prope disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing	5



MATERIAL SAFETY DATA SHEET **DOP REDUCER**

sion Date 03/12/2007			Print D	Page 0ate 11/26/	
	Р	ume condensates may contain eriodically clean hoods, duc ccumulation of these materia	ts, and other surfaces to m		
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.				
8. F	XPOSURE	CONTROLS / PERSONA	L PROTECTION		
Respiratory protection	: N	: No personal respiratory protective equipment normally required.			
Eye/Face Protection	: S	afety glasses with side-shiel	ds.		
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		landle in accordance with go Vash hands before breaks an		afety praction	
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
		PEL:			
Di(2-ethylhexyl)phthal ate	5 mg/m3	PEL:	Vapor.		
• • •	5 mg/m3	Time Weighted Average (TWA):	-	OSHA Z	
• • •		Time Weighted Average		OSHA Z MX OEI	
• • •	5 mg/m3 10 mg/m3	Time Weighted Average (TWA): Short Term Exposure Lim	it	OSHA Z MX OEI	
ate	5 mg/m3 10 mg/m3 9. PHYSIC	Time Weighted Average (TWA): Short Term Exposure Lim (STEL):	it ROPERTIES	OSHA Z MX OEI MX OEI	
• • •	5 mg/m3 10 mg/m3 9. PHYSIC : liqui : Visco	Time Weighted Average (TWA): Short Term Exposure Lim (STEL): CAL AND CHEMICAL PI d Evaj ous, liquid Spec	it ROPERTIES poration rate : Not	OSHA Z MX OEI MX OEI	
ate Form Appearance Color	5 mg/m3 10 mg/m3 9. PHYSIC : liquid : Visco : NO I	Time Weighted Average (TWA): Short Term Exposure Lim (STEL): CAL AND CHEMICAL PI d Evaj ous, liquid Spec PIGMENT Bull	it ROPERTIES poration rate : Not cific Gravity: : Not k density : Not	OSHA Z MX OEI MX OEI established determined applicable	
ate Form Appearance Color Odor	5 mg/m3 10 mg/m3 9. PHYSIC : liquid : Visc : NO I : Very	Time Weighted Average (TWA): Short Term Exposure Lim (STEL): CAL AND CHEMICAL PI d Evaj ous, liquid Spec PIGMENT Bull faint Vap	it ROPERTIES poration rate : Not cific Gravity: : Not k density : Not or pressure : Not	OSHA Z MX OEI MX OEI established determined applicable determined	
ate Form Appearance Color Odor Melting point/range	5 mg/m3 10 mg/m3 9. PHYSIC : liquic : Visc : NO I : Very : Not a	Time Weighted Average (TWA): Short Term Exposure Lim (STEL): CAL AND CHEMICAL PI d Eva ous, liquid Spec PIGMENT Bull faint Vap applicable Vap	it ROPERTIES poration rate : Not cific Gravity: : Not k density : Not or pressure : Not our density : Not	OSHA Z MX OEI MX OEI established determined applicable determined determined	
ate Form Appearance Color Odor	5 mg/m3 10 mg/m3 9. PHYSIC : liquic : Visc : NO I : Very : Not a	Time Weighted Average (TWA): Short Term Exposure Lim (STEL): CAL AND CHEMICAL Pl d Eva ous, liquid Spec PIGMENT Bull faint Vap applicable Vap	it ROPERTIES poration rate : Not cific Gravity: : Not k density : Not or pressure : Not our density : Not	OSHA Z MX OEI MX OEI established determined applicable determined	
ate Form Appearance Color Odor Melting point/range Boiling Point:	5 mg/m3 10 mg/m3 9. PHYSIC : liquid : Visco : NO I : Very : Not a : Not a : Imm	Time Weighted Average (TWA): Short Term Exposure Lim (STEL): CAL AND CHEMICAL Pl d Eva ous, liquid Spec PIGMENT Bull faint Vap applicable Vap	it ROPERTIES poration rate : Not cific Gravity: : Not k density : Not our density : Not : Not	OSHA Z MX OEI MX OEI established determined applicable determined determined	
ate Form Appearance Color Odor Melting point/range Boiling Point:	5 mg/m3 10 mg/m3 9. PHYSIC : liquid : Visc : NO I : Very : Not a : Imm 10. §	Time Weighted Average (TWA): Short Term Exposure Lim (STEL): CAL AND CHEMICAL PI d Evajous, liquid ous, liquid Spea PIGMENT Bull t faint Vap applicable pH scible PH	it ROPERTIES poration rate : Not cific Gravity: : Not k density : Not our density : Not : Not	OSHA Z MX OEI MX OEI established determined applicable determined determined	
ate Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	5 mg/m3 10 mg/m3 9. PHYSIC : liquid : Visc : NO I : Very : Not a : Imm 10. §	Time Weighted Average (TWA): Short Term Exposure Lim (STEL): CAL AND CHEMICAL PI d Evajous, liquid Spec PIGMENT Bull faint Vap applicable Vap applicable pH iscible	it ROPERTIES poration rate : Not cific Gravity: : Not k density : Not our density : Not : Not	OSHA Z MX OEI MX OEI established determined applicable determined determined	



MATERIAL SAFETY DATA SHEET **DOP REDUCER**

Version Number 1.0 Revision Date 03/12/2007

Page 4 of 7 Print Date 11/26/2011

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
117-81-7	Di(2-ethylhexyl)phthalate	Systemic effects	Eyes, Respiratory system, Liver, central nervous system (CNS), Skin, digestive system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
117-81-7	Di(2-ethylhexyl)phthalate	Oral LD50	30 gm/kg	rat
		Dermal LD50	25 gm/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No. Chemical Name	OSHA	IARC	NTP
-----------------------	------	------	-----

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

PolyOne

MATERIAL SAFETY DATA SHEET DOP REDUCER

Version Number 1.0 Revision Date 03/12/2007 Page 5 of 7 Print Date 11/26/2011

Additional Health Hazard Information: Di(2-ethylhexyl)phthalate 117-81-7 There is sufficient evidence for the carcinogenicity of di (2-ethylhexyl) phthalate in experimental animals. Administered in the feed this chemical caused an increase incidence of liver cancer in male and female rats and mice. The relevance of this finding to humans is uncertain.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. Th generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)

MATERIAL SAFETY DATA SHEET **DOP REDUCER**

Version Number 1.0 Revision Date 03/12/2007

Page 6 of 7 Print Date 11/26/2011

Chemical Name	CAS-No.		RQ for Mixture/Product
Di(2-ethylhexyl)ph thalate	117-81-7	100 lbs	100 LB

California Proposition 65

: WARNING! This product contains a chemical known to the State of California to cause cancer., WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight %
DI(2-ETHYLHEXYL)PHTHALATE (DEHP)	117-81-7	60.00 - 100.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Di(2-ethylhexyl)phthalate	117-81-7	60.00 - 100.00	25

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

S-No.	
7-81-7	
7-81-7	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed

:

China IECS : Listed



MATERIAL SAFETY DATA SHEET **DOP REDUCER**

Version Number 1.0 Revision Date 03/12/2007			Print Date	Page 7 of 7 11/26/2011
Europe EINECS	:	Listed		
Japan ENCS	:	Listed		
Korea KECI	:	Listed		
Philippines PICCS	:	Listed		
		16. OTHER INFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CET