PolyOne

MATERIAL SAFETY DATA SHEET DB4213 NEUTRAL PHOSPHATE EXTRA AL

Version Number 1.0 Revision Date 05/17/2007 Page 1 of 6 Print Date 11/28/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DB4213 NEUTRAL PHOSPHATE EXTRA AL
Product code	:	FO20016615
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Oxirane,	25085-99-8	1 - 5
2,2'-[(1-methylethylidene)bis(4,1-phenylene		
oxymethylene)]bis-, homopolymer		
Triphenyl phosphate	115-86-6	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET DB4213 NEUTRAL PHOSPHATE EXTRA AL

Version Number 1.0 Revision Date 05/17/2007 Page 2 of 6 Print Date 11/28/2011

Medical Conditions : None known. Aggravated by Exposure:		
	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.	
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.	
Skin : Wash off with soap and plenty of water. If skin irritation persists see medical attention.		
	5. FIRE-FIGHTING MEASURES	
Flash point	: No data available	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible. 	
	6. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.	
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	



MATERIAL SAFETY DATA SHEET DB4213 NEUTRAL PHOSPHATE EXTRA AL

sion Number 1.0 vision Date 05/17/2007		Prin	Page 3 o t Date 11/28/20	
Handling		Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.		
Storage		Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.		
8. 1	XPOSURI	E CONTROLS / PERSONAL PROTECTION		
Respiratory protection	:	No personal respiratory protective equipment normally required.		
Eye/Face Protection	:	Safety glasses with side-shields		
Hand protection	:	Protective gloves		
Skin and body protection	:	Long sleeved clothing		
Additional Protective Measures	:	Safety shoes		
General Hygiene Considerations		Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.		
Engineering measures		Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.		
Exposure limit(s)				
Components	Value	Exposure time Exposure type	List:	

Components	Value	Exposure time	Exposure type	List:
Triphenyl phosphate	3 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	3 mg/m3	PEL:		OSHA Z1
	3 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
	6 mg/m3	Short Term Exposure Limit		MX OEL
		(STEL):		

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range Boiling Point: Water solubility
- liquid
 Viscous, liquid
 NO PIGMENT
 Very faint
 Not applicable
 Not applicable
 Immiscible

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not established
Not determined
Not applicable
Not determined
Not determined
Not applicable

MATERIAL SAFETY DATA SHEET DB4213 NEUTRAL PHOSPHATE EXTRA AL

Version Number 1.0 Revision Date 05/17/2007

Page 4 of 6 Print Date 11/28/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
25085-99-8	Oxirane, 2,2'-[(1-methylethylidene) bis(4,1-phenyleneoxymeth ylene)]bis-, homopolymer	sensitizer	Skin.
115-86-6	Triphenyl phosphate	Systemic effects	Respiratory system, blood and blood forming system, central nervous system (CNS).

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
115-86-6	Triphenyl phosphate	Oral LD50	3,500 mg/kg	rat
		Dermal LD50	> 7,900 mg/kg	rabbit

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.

whole.

Environmental Toxicity

: Environmental toxicity has not been established for this mixture as a

4/6



MATERIAL SAFETY DATA SHEET DB4213 NEUTRAL PHOSPHATE EXTRA AL

Version Number 1.0 Revision Date 05/17/2007 Page 5 of 6 Print Date 11/28/2011

Bioaccumulation Potential	: No data available	
Additional advice : No data available		
	13. DISPOSAL CONSIDERATIONS	
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
Contaminated packaging	: Recycling is preferred when possible. The generator of waste mate has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
	14. TRANSPORT INFORMATION	
U.S. DOT Classification : Refer to specific regulation.		
ICAO/IATA (air) : Refer to specific regulation.		
IMO / IMDG (maritime)	: Refer to specific regulation.	
	15. REGULATORY INFORMATION	
US Regulations:		
OSHA Status	: Classified as hazardous based on components.	
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.		
US. EPA CERCLA Hazardou	Substances (40 CFR 302)	
Not applicable		
California Proposition 65	: Not applicable	
SARA Title III Section 302 E	tremely Hazardous Substance	

MATERIAL SAFETY DATA SHEET DB4213 NEUTRAL PHOSPHATE EXTRA AL

Version Number 1.0 Revision Date 05/17/2007 Page 6 of 6 Print Date 11/28/2011

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Not applicable

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS	S-No.	
115	-86-6	

DSL

All of the components of this product are listed on the Canadian Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL). Quantity use in Canada is restricted by regulations.

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

:

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.