PolyOne

MATERIAL SAFETY DATA SHEET MB2462 GREEN

Version Number 1.0 Revision Date 06/11/2007

Page 1 of 7 Print Date 11/29/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	MB2462 GREEN
Product code	:	FO20016776
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium oxide	1305-78-8	1 - 5
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Miscellaneous Barium Compounds	0-08-8	1 - 5
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **MB2462 GREEN**

Version Number 1.0 Revision Date 06/11/2007 Page 2 of 7 Print Date 11/29/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 No data available No data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	 May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or th soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.



MATERIAL SAFETY DATA SHEET **MB2462 GREEN**

Version Number 1.0 Revision Date 06/11/2007 Page 3 of 7 Print Date 11/29/2011

Handling	:	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXP	OSUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

MATERIAL SAFETY DATA SHEET **MB2462 GREEN**

Version Number 1.0 Revision Date 06/11/2007

Page 4 of 7 Print Date 11/29/2011

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average		MX OEL
	_	(TWA):		
	20 mg/m3	Short Term Exposure Limit		MX OEL
		(STEL):		
Calcium oxide	2 mg/m3	Time Weighted Average		ACGIH
	_	(TWA):		
	5 mg/m3	PEL:		OSHA Z1
	2 mg/m3	Time Weighted Average		MX OEL
	_	(TWA):		
Silica, amorphous,	0.8 mg/m3	Time Weighted Average		Z3
fumed, crystal-free		(TWA):		
	10 mg/m3	Time Weighted Average	Inhalable particulate.	MX OEL
		(TWA):		
	3 mg/m3	Time Weighted Average	Respirable dust.	MX OEL
		(TWA):		
Miscellaneous Barium	0.5 mg/m3	Time Weighted Average	as Ba	ACGIH
Compounds		(TWA):		
	0.5 mg/m3	PEL:	as Ba	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range Boiling Point: Water solubility
- liquid
 Viscous, liquid
 GREEN
 Very faint
 Not applicable
 Not applicable
 Immiscible

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH

degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F),

- Not establishedNot determined
- : Not applicable
- : Not determined
- : Not determined
- : Not applicable

10. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization Will not occur. : Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible Materials : Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing. Hazardous decomposition Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen : products (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product

PolvOne

MATERIAL SAFETY DATA SHEET MB2462 GREEN

Version Number 1.0 Revision Date 06/11/2007 Page 5 of 7 Print Date 11/29/2011

and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1305-78-8	Calcium oxide	Irritant	Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
		Corrosive	Skin.
112945-52-5	Silica, amorphous, fumed, crystal-free	Irritant	Eyes, Respiratory system.
0-08-8	Miscellaneous Barium Compounds	Irritant	Respiratory system, Eyes.
		Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
112945-52-5	Silica, amorphous, fumed, crystal-free	Oral LD50	3,160 mg/kg	rat
	12. ECOLOGICA	L INFORMATI	ON	

Environmental Toxicity	:	Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	:	No data available

Additional advice

: No data available

13. DISPOSAL CONSIDERATIONS

Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial

PolyOne.

MATERIAL SAFETY DATA SHEET **MB2462 GREEN**

ion Number 1.0 sion Date 06/11/2007				Print Da	Page 6 te 11/29/
	and local	regulations.			
		PORT INFORMA	TION		
	1.				
U.S. DOT Classification	: Refer to s	pecific regulation.			
ICAO/IATA (air)	: Refer to s	pecific regulation.			
IMO / IMDG (maritime)	: Refer to s	pecific regulation.			
	15. REGULA	TORY INFORM	ATION		
US Regulations:					
OSHA Status	: Classified	as hazardous based	on componen	ts.	
TSCA Status	: All comp Inventory	onents of this produce.	ct are listed on	or exempt fro	m the TSC
US. EPA CERCLA Hazardou	-				
Not applicable	() () () () () () () () () ()	,			
California Propositior 65	n : Not applic	cable			
SARA Title III Section 302 E	Extremely Hazardo	ous Substance			
	-		1		
TT 1 'C' 1 ' 1	identified under t	this section, this pro-	duct is Not Ar	plicable unde	r this reau
Unless specific chemicals are		_	r		r uns regu
Unless specific chemicals are		-	r		i unis regui
-	`oxic Chemicals:				i uns regu
Unless specific chemicals are SARA Title III Section 313 T Unless specific chemicals are		this section, this pro		plicable unde	
SARA Title III Section 313 T Unless specific chemicals are Chemical Name		CA	duct is Not Ap	Weight %	
SARA Title III Section 313 T Unless specific chemicals are			duct is Not Ap		
SARA Title III Section 313 T Unless specific chemicals are Chemical Name		CA	duct is Not Ap	Weight %	
SARA Title III Section 313 T Unless specific chemicals are Chemical Name BARIUM COMPOUNDS Canadian Regulations:	identified under t	CA 0-03	duct is Not Ap	Weight %	
SARA Title III Section 313 T Unless specific chemicals are Chemical Name BARIUM COMPOUNDS Canadian Regulations: National Pollutant Rel	identified under t	CA 0-08	duct is Not Ap AS-No. 8-8	Weight % 0.10 - 1.00	r this regul
SARA Title III Section 313 T Unless specific chemicals are Chemical Name BARIUM COMPOUNDS Canadian Regulations: National Pollutant Rel Chemical Name	identified under t	[PRI) CAS-No.	duct is Not Ap AS-No. 8-8 Weigh	Weight % 0.10 - 1.00 t % NP	r this regul
SARA Title III Section 313 T Unless specific chemicals are Chemical Name BARIUM COMPOUNDS Canadian Regulations: National Pollutant Rel	ease Inventory (N	CA 0-08	duct is Not Ap AS-No. 8-8	Weight % 0.10 - 1.00 t % NP 1.00 143	r this regul

MATERIAL SAFETY DATA SHEET MB2462 GREEN

Version Number 1.0 Revision Date 06/11/2007 Page 7 of 7 Print Date 11/29/2011

WHMIS Classification : D2B WHMIS Ingredient Disclosure List CAS-No. 1305-78-8 112945-52-5 0-08-8 DSL All components of this product are on the Canadian Domestic : Substances List (DSL) or are exempt. National Inventories: Australia AICS Not determined : China IECS Not determined : Europe EINECS Not determined : Japan ENCS Not determined : Korea KECI : Not determined **Philippines PICCS** Not determined •

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.