PolvOne

MATERIAL SAFETY DATA SHEET **MB2482 BLACK 50 TYPE**

Version Number 1.0 Revision Date 07/30/2007

Page 1 of 7 Print Date 11/30/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	MB2482 BLACK 50 TYPE
Product code	:	FO20017055
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium oxide	1305-78-8	1 - 5
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.		
Ingestion	: May be harmful if swallowed.		
Eyes	: May cause eye/skin irritation.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **MB2482 BLACK 50 TYPE**

Version Number 1.0 Revision Date 07/30/2007 Page 2 of 7 Print Date 11/30/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE

PolyOne.

MATERIAL SAFETY DATA SHEET **MB2482 BLACK 50 TYPE**

Version Number 1.0 Revision Date 07/30/2007	Page 3 of 7 Print Date 11/30/2011
Handling	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXPOSU	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	No personal respiratory protective equipment normally required.
Eye/Face Protection	Safety glasses with side-shields
Hand protection	Protective gloves
Skin and body protection	Long sleeved clothing
Additional Protective Measures	Safety shoes
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)	

PolyOne

MATERIAL SAFETY DATA SHEET **MB2482 BLACK 50 TYPE**

Version Number 1.0 Revision Date 07/30/2007 Page 4 of 7 Print Date *11/30/2011*

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Calcium oxide	2 mg/m3	Time Weighted Average (TWA):		ACGIH
	5 mg/m3	PEL:		OSHA Z1
	2 mg/m3	Time Weighted Average (TWA):		MX OEL
Silica, amorphous, fumed, crystal-free	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range Boiling Point: Water solubility
- liquid
 Viscous, liquid
 BLACK
 Very faint
 Not applicable
 Not applicable
 Immiscible

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not established
Not determined
Not applicable
Not determined
Not determined
Not determined
Not applicable

10. STABILITY AND REACTIVITY

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid		Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials		Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products		Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).
	11. T	OXICOLOGICAL INFORMATION

PolyOne

MATERIAL SAFETY DATA SHEET MB2482 BLACK 50 TYPE

Version Number 1.0 Revision Date 07/30/2007 Page 5 of 7 Print Date 11/30/2011

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1305-78-8	Calcium oxide	Irritant	Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
		Corrosive	Skin.
112945-52-5	Silica, amorphous, fumed,	Irritant	Eyes, Respiratory system.
	crystal-free		
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
112945-52-5	Silica, amorphous, fumed, crystal-free	Oral LD50	3,160 mg/kg	rat

Persistence and degradability	: Not readily biodegradable.
r ensistence und degradaenney	
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.

PolyOne.

MATERIAL SAFETY DATA SHEET **MB2482 BLACK 50 TYPE**

Version Number 1.0 Revision Date 07/30/2007 Page 6 of 7 Print Date 11/30/2011

ICAO/IATA (air)	:	Refer to specific regulation.
IMO / IMDG (maritime)	:	Refer to specific regulation.
	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Subs	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	Not applicable
SARA Title III Section 302 Ext	rem	ely Hazardous Substance
		fied under this section, this product is Not Applicable under this regulatior
Unless specific chemicals are id	lenti	fied under this section, this product is Not Applicable under this regulation
Unless specific chemicals are id SARA Title III Section 313 Tox	lenti kic C	fied under this section, this product is Not Applicable under this regulation
Unless specific chemicals are id SARA Title III Section 313 Tox Unless specific chemicals are id	lenti kic C	fied under this section, this product is Not Applicable under this regulation
Unless specific chemicals are id SARA Title III Section 313 Tox	lenti kic C lenti	fied under this section, this product is Not Applicable under this regulation Chemicals: fied under this section, this product is Not Applicable under this regulation
Unless specific chemicals are id SARA Title III Section 313 Tox Unless specific chemicals are id Canadian Regulations:	lenti kic C lenti	fied under this section, this product is Not Applicable under this regulation Chemicals: fied under this section, this product is Not Applicable under this regulation
Unless specific chemicals are id SARA Title III Section 313 Tox Unless specific chemicals are id Canadian Regulations: National Pollutant Relea	lenti kic C lenti	fied under this section, this product is Not Applicable under this regulation Chemicals: fied under this section, this product is Not Applicable under this regulation
Unless specific chemicals are id SARA Title III Section 313 Tox Unless specific chemicals are id Canadian Regulations: National Pollutant Relea Not applicable	lenti kic C lenti se Ir	fied under this section, this product is Not Applicable under this regulation Chemicals: fied under this section, this product is Not Applicable under this regulation eventory (NPRI)
Unless specific chemicals are id SARA Title III Section 313 Tox Unless specific chemicals are id Canadian Regulations: National Pollutant Relea Not applicable WHMIS Classification DSL	lenti kic C lenti se Ir	fied under this section, this product is Not Applicable under this regulation Chemicals: fied under this section, this product is Not Applicable under this regulation eventory (NPRI) Not controlled. All components of this product are on the Canadian Domestic
Unless specific chemicals are id SARA Title III Section 313 Tox Unless specific chemicals are id Canadian Regulations: National Pollutant Relea Not applicable WHMIS Classification	lenti kic C lenti se Ir	fied under this section, this product is Not Applicable under this regulation Chemicals: fied under this section, this product is Not Applicable under this regulation eventory (NPRI) Not controlled. All components of this product are on the Canadian Domestic

PolyOne

MATERIAL SAFETY DATA SHEET **MB2482 BLACK 50 TYPE**

Version Number 1.0 Revision Date 07/30/2007 Page 7 of 7 Print Date 11/30/2011

Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.