MATERIAL SAFETY DATA SHEET MB2485A BLACK RIGID

Version Number 1.0 Revision Date 08/22/2007

Page 1 of 6 Print Date 11/30/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

| Telephone Emergency telephone | : | Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
|----------------------------------|---|--|
| Product name | : | MB2485A BLACK RIGID |
| Product code | : | FO20017180 |
| Chemical Name | : | Mixture |
| CAS-No. | : | Mixture |
| Product Use | : | Industrial Applications |

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Skin contact, Ingestion |
|---|--|
| Acute exposure | |
| Inhalation | : Inhalation of airborne droplets may cause irritation of the respiratory tract. |
| Ingestion | : May be harmful if swallowed. |
| Eyes | : May cause eye/skin irritation. |
| Skin | : Experience shows no unusual dermatitis hazard from routine handling. |
| Chronic exposure | : Refer to Section 11 for Toxicological Information. |
| Medical Conditions Aggravated by Exposure: | : None known. |
| | 4. FIRST AID MEASURES |

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET **MB2485A BLACK RIGID**

| ion Number 1.0 sion Date 08/22/2007 | Page 2 Print Date 11/30/ |
|--|--|
| | |
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. |
| Eyes | : Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention. |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists see medical attention. |
| | 5. FIRE-FIGHTING MEASURES |
| Flash point | : No data available |
| Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards | No data available No data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible. |
| | 6. ACCIDENTAL RELEASE MEASURES |
| | 0. ACCIDENTAL RELEASE MEASURES |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. |
| Environmental precautions | : The product should not be allowed to enter drains, water courses or th soil. Should not be released into the environment. |
| Methods for cleaning up | : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods. |
| | 7. HANDLING AND STORAGE |
| Handling | : Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize |

PolyOne.

MATERIAL SAFETY DATA SHEET MB2485A BLACK RIGID

Version Number 1.0 Revision Date 08/22/2007 Page 3 of 6 Print Date 11/30/2011

| | | accumulation of these materials. | | |
|-----------------------------------|-----|---|---|---|
| Storage | : | Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place. | | |
| 8. EXPOS | SUF | RE CONTROLS / PERSONAL PROTECTION | + | • |
| Respiratory protection | : | No personal respiratory protective equipment normally required. | | |
| Eye/Face Protection | : | Safety glasses with side-shields | | |
| Hand protection | : | Protective gloves | | |
| Skin and body protection | : | Long sleeved clothing | | |
| Additional Protective Measures | : | Safety shoes | | |
| General Hygiene Considerations | : | Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. | | |
| Engineering measures | : | Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. | | |
| Exposure limit(s) | | | | |
| There are no known hazardous c | om | ponents above regulatory thresholds in this product. | | |
| 9. PI | IYS | SICAL AND CHEMICAL PROPERTIES | Ť | • |

Form Appearance Color Odour Melting point/range Boiling Point: Water solubility

_

liquid
Viscous, liquid
BLACK
Very faint
Not applicable
Not applicable
Immiscible

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not established
Not determined
Not applicable
Not determined
Not determined
Not applicable

| | 1 | 0. STABILITY AND REACTIVITY |
|--------------------------|---|---|
| Stability | : | Stable. |
| Hazardous Polymerization | : | Will not occur. |
| Conditions to avoid | : | Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. |
| Incompatible Materials | : | Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing. |

PolyOne.

MATERIAL SAFETY DATA SHEET **MB2485A BLACK RIGID**

| bon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen Dx), hydrogen chloride (HCl), other hazardous materials, and oke are all possible. Prolonged heating may result in product gradation. As a general rule of thumb, degradation begins to occur er one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F within 5 minutes at 232 °C (450 °F). ICOLOGICAL INFORMATION Its above regulatory thresholds in this product. COLOGICAL INFORMATION It readily biodegradable. Vironmental toxicity has not been established for this mixture as a ole. data available data available SPOSAL CONSIDERATIONS ere possible recycling is preferred to disposal or incineration. Th |
|---|
| nts above regulatory thresholds in this product. COLOGICAL INFORMATION t readily biodegradable. vironmental toxicity has not been established for this mixture as a ole. data available data available SPOSAL CONSIDERATIONS here possible recycling is preferred to disposal or incineration. Th |
| COLOGICAL INFORMATION t readily biodegradable. vironmental toxicity has not been established for this mixture as a ole. data available data available SPOSAL CONSIDERATIONS here possible recycling is preferred to disposal or incineration. Th |
| t readily biodegradable. vironmental toxicity has not been established for this mixture as a ole. data available data available SPOSAL CONSIDERATIONS ere possible recycling is preferred to disposal or incineration. Th |
| vironmental toxicity has not been established for this mixture as a ole. data available data available SPOSAL CONSIDERATIONS ere possible recycling is preferred to disposal or incineration. Th |
| ole. data available data available SPOSAL CONSIDERATIONS ere possible recycling is preferred to disposal or incineration. Th |
| data available SPOSAL CONSIDERATIONS ere possible recycling is preferred to disposal or incineration. Th |
| SPOSAL CONSIDERATIONS here possible recycling is preferred to disposal or incineration. Th |
| ere possible recycling is preferred to disposal or incineration. Th |
| |
| erator of waste material has the responsibility for proper waste ssification, transportation and disposal in accordance with licable federal, state/provincial and local regulations. cycling is preferred when possible. The generator of waste materi |
| the responsibility for proper waste classification, transportation disposal in accordance with applicable federal, state/provincial local regulations. |
| RANSPORT INFORMATION |
| er to specific regulation. |
| er to specific regulation. |
| Fer to specific regulation. |
| GULATORY INFORMATION |
| |
| |
| f |

blvU<u>ne</u>

MATERIAL SAFETY DATA SHEET MB2485A BLACK RIGID

Version Number 1.0 Revision Date 08/22/2007

Page 5 of 6 Print Date 11/30/2011

TSCA Status All components of this product are listed on or exempt from the TSCA : Inventory. US. EPA CERCLA Hazardous Substances (40 CFR 302) Not applicable California Proposition : Not applicable 65 SARA Title III Section 302 Extremely Hazardous Substance Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation SARA Title III Section 313 Toxic Chemicals: Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation Canadian Regulations: National Pollutant Release Inventory (NPRI) Not applicable WHMIS Classification : Not controlled. DSL All components of this product are on the Canadian Domestic · Substances List (DSL) or are exempt. National Inventories: Australia AICS : Not determined China IECS Not determined : Europe EINECS Not determined : Japan ENCS Not determined

Korea KECI Not determined : Philippines PICCS : Not determined

:

16. OTHER INFORMATION

PolyOne

MATERIAL SAFETY DATA SHEET MB2485A BLACK RIGID

Version Number 1.0 Revision Date 08/22/2007

Page 6 of 6 Print Date 11/30/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.