PolyOne

## MATERIAL SAFETY DATA SHEET **D4018 Black**

Version Number 1.3 Revision Date 10/16/2013

Page 1 of 6 Print Date 10/16/2013

POLYONE CORPORATI 8155 Cobb Center Drive,		raw, GA 30152
Telephone	:	1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	D4018 Black
Product code	:	FO20017586
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

Components	CAS-No.	Weight percent
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye and skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



# MATERIAL SAFETY DATA SHEET **D4018 Black**

Version Number 1.3 Revision Date 10/16/2013 Page 2 of 6 Print Date 10/16/2013

Aggravated by Exposure:				
	4. FIRST AID MEASURES			
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.			
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.			
	5. FIREFIGHTING MEASURES			
Flash point	: no data available			
Flammable Limits				
Upper explosion limit	: no data available			
Lower explosion limit	: no data available			
Auto-ignition temperature	: Not applicable			
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.			
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.			
Unusual Fire/Explosion Hazards	<ul> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>			
	6. ACCIDENTAL RELEASE MEASURES			
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.			
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal.			
	7. HANDLING AND STORAGE			



# MATERIAL SAFETY DATA SHEET **D4018 Black**

ion Number 1.3 sion Date 10/16/2013				Pri	Page int Date 10/10		
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.						
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.						
8. ]	EXPOSURE	CONTROLS/	PERSONAL	PROTECTION			
Respiratory protection	: N	lo personal respi	ratory protect	ive equipment norma	ally required.		
Eye/Face Protection	: S	afety glasses wit	h side-shields	3			
Hand protection	: P	rotective gloves					
Skin and body protection	: L	ong sleeved clot	hing				
Additional Protective Measures	: S	afety shoes					
General Hygiene Considerations		: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.					
Engineering measures		leat only in areas ppropriate exhau		iate exhaust ventilat at machinery.	ion. Provide		
Exposure limit(s)							
Components	Value	Value Exposure time E		Exposure type	List:		
Silica, amorphous, fumed, crystal-free	0.8 mg/m3	Time Weight (TW)	ed Average		Z3		
	10 mg/m3	Time Weight (TW)	A):	Inhalable particula	ate. MX OE		
	3 mg/m3	Time Weight (TW)	0	Respirable dust	MX OE		
	9. PHYSI	CAL AND CHE	MICAL PRO	OPERTIES			
Form	: liqui	d	Evapo	ouration rate :	Not established		
Appearance		ous, liquid			Not determine		
Colour	: BLA		Bulk density : Not applicable				
Odour	: very			1	Not determine		
Melting point/range		pplicable	-	~	Not determine		
Boiling Point: Water solubility		pplicable iscible	рН	:	Not applicable		
		STABILITY AN					



## MATERIAL SAFETY DATA SHEET **D4018 Black**

Version Number 1.3 Revision Date 10/16/2013 Page 4 of 6 Print Date 10/16/2013

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
112945-52-5	Silica, amorphous, fumed, crystal-free	Irritant	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
112945-52-5	Silica, amorphous, fumed, crystal-free	Oral LD50	3,160 mg/kg	rat

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
<b>Bioaccumulation Potential</b>	: no data available
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The



# MATERIAL SAFETY DATA SHEET **D4018 Black**

ion Number 1.3 sion Date 10/16/2013	Page 5 o Print Date 10/16/20
	generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)
not applicable	
California Propositio 65	n : Not applicable
SARA Title III Section 302 I	Extremely Hazardous Substance
Unless specific chemicals are	e identified under this section, this product is Not Applicable under this regulati
SARA Title III Section 313	Foxic Chemicals:
Unless specific chemicals are	e identified under this section, this product is Not Applicable under this regulati
Canadian Regulations:	

PolyOne.

## MATERIAL SAFETY DATA SHEET **D4018 Black**

Version Number 1.3 Revision Date 10/16/2013 Page 6 of 6 Print Date 10/16/2013

Chemical Name			CAS-No.	Weight	NPRI ID#			
2-Ethylhexanoic acid zinc salt				percent				
			136-53-8	0.10 - 1.00				
WHMIS Classification	:	Not controlled.						
DSL	:	All components	s of this product	are on the Canadia	an Domestic			
			All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.					
lational Inventories:								
Australia AICS	:	Not determined						
China IECS	:	Not determined						
Europe EINECS	:	Not determined						
Japan ENCS	:	Not determined						
Korea KECI	:	Not determined						
KUITA KLUI	•							
Philippines PICCS	:	Not determined						

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.