## MATERIAL SAFETY DATA SHEET **DM480 SILVER (9240-)**

Version Number 1.0 Revision Date 01/23/2008

Page 1 of 6 Print Date 12/3/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone : Emergency telephone :	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DM480 SILVER (9240- )
Product code	:	FO20018061
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Aluminum	7429-90-5	1 - 5

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

# MATERIAL SAFETY DATA SHEET **DM480 SILVER (9240- )**

Version Number 1.0 Revision Date 01/23/2008 Page 2 of 6 Print Date 12/3/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ol> <li>No data available</li> <li>No data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ol>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing

POLYONE CORPORATION

PolvOne.

## MATERIAL SAFETY DATA SHEET **DM480 SILVER (9240- )**

Version Number 1.0 Revision Date 01/23/2008 Page 3 of 6 Print Date 12/3/2011

fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Aluminum	10 mg/m3	Time Weighted Average (TWA):	Dust.	ACGIH
	5 mg/m3	Time Weighted Average (TWA):	Pyrophoric powder. as Al	ACGIH
	15 mg/m3	PEL:	Total dust. as Al	OSHA Z1
	5 mg/m3	PEL:	Respirable dust. as Al	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	Pyrophoric powder.	MX OEL
	10 mg/m3	Time Weighted Average (TWA):	Dust.	MX OEL

### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range Boiling Point: Water solubility
- liquid
  Viscous, liquid
  GREY
  Very faint
  Not applicable
  Not applicable
  Immiscible
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not established
  Not determined
  Not applicable
  Not determined
  Not determined
  Not applicable

PolyOne.

## MATERIAL SAFETY DATA SHEET **DM480 SILVER (9240- )**

Version Number 1.0 Revision Date 01/23/2008

\_

Page 4 of 6 Print Date 12/3/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	<ul> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).</li> </ul>

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

**Toxicity Overview** 

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

PolyOne.

# MATERIAL SAFETY DATA SHEET **DM480 SILVER (9240- )**

Version Number 1.0 Revision Date 01/23/2008			Page 5 c Print Date 12/3/20	
Contaminated packaging	: Recycling is preferred wh material has the responsib transportation and disposa state/provincial and local	ility for proper wa	aste classification,	
	14. TRANSPORT INFOR	MATION		]
U.S. DOT Classification	: Refer to specific regulation	n.		
ICAO/IATA (air)	: Refer to specific regulation	n.		
IMO / IMDG (maritime)	: Refer to specific regulation	'n.		
	<b>15. REGULATORY INFOR</b>	RMATION		]
US Regulations:				
OSHA Status	: Classified as hazardous ba	ased on componen	its.	
TSCA Status	: All components of this pr TSCA Inventory.	oduct are listed or	n or exempt from the	
US. EPA CERCLA Hazardous S	ubstances (40 CFR 302)			
Not applicable				
California Proposition 65	: Not applicable			
SARA Title III Section 302 Extre	emely Hazardous Substance			
Unless specific chemicals are ide	ntified under this section, this	product is Not Ap	oplicable under this regulati	on
SARA Title III Section 313 Toxi	c Chemicals:			
Unless specific chemicals are ide Chemical Name	ntified under this section, this	product is Not Ap CAS-No.	pplicable under this regulati Weight %	on
ALUMINUM (FUME OR DU	ST)	7429-90-5	1.00 - 5.00	
Canadian Regulations:				
National Pollutant Release	e Inventory (NPRI)			

PolyOne

## MATERIAL SAFETY DATA SHEET **DM480 SILVER (9240- )**

Version Number 1.0 Revision Date 01/23/2008 Page 6 of 6 Print Date 12/3/2011

Chemical Name			CAS-No.	Weight %	NPRI ID#
Aluminum		7429-90-5	1.00 - 5.00	12	
Ethoxylated octylphenol			9036-19-5	1.00 - 5.00	179
Miscellaneous Zinc Compour	nds		0-31-7	0.10 - 1.00	241
WHMIS Classification WHMIS Ingredient Disc	: losı				
CAS-No. 7429-90-5 9036-19-5					
DSL	:		s of this product a (DSL) or are exe	are on the Canadia empt.	n Domestic
National Inventories:					
Australia AICS	:	Not determined			
China IECS	:	Not determined			
Europe EINECS	:	Not determined			
Japan ENCS	:	Not determined			
Korea KECI	:	Not determined			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.