

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****PX1002 CLEAR PRIMER**Version Number 1.0
Revision Date 03/19/2008Page 1 of 8
Print Date 1/3/2012**1. PRODUCT AND COMPANY IDENTIFICATION****POLYONE CORPORATION**
8155 Cobb Center Drive, Kennesaw, GA 30152Telephone : Product Stewardship (770) 590-3500 x.3563
Emergency telephone : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**Product name : PX1002 CLEAR PRIMER
Product code : FO20018480
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications**2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS**

Components	CAS-No.	Weight %
2-Methoxy-1-methylethyl acetate	108-65-6	10 - 30
Phenol	108-95-2	0.1 - 1
Ethyl acetate	141-78-6	1 - 5
Toluene	108-88-3	5 - 10
Ethyl alcohol	64-17-5	10 - 30
Diacetone alcohol	123-42-2	30 - 60

3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

Flammable. May be harmful if inhaled. Harmful if swallowed. May cause skin irritation. Flammable liquid and vapor. Vapors may be irritating to eyes and respiratory tract. This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. In addition, heating or processing this material may result in product degradation or byproduct formation creating additional hazards. See Sections 8 and 11 for additional details.

POTENTIAL HEALTH EFFECTS**Routes of Exposure:** : Inhalation, Skin contact, Ingestion**Acute exposure**Inhalation : Excessive inhalation of product vapors may cause respiratory irritation, headaches, dizziness, and/or nausea.
Ingestion : May be harmful if swallowed. May cause nausea, abdominal spasms and irritation of the mucous membranes.
Eyes : Liquid, aerosol, or vapors of this product are irritating and may cause

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

PX1002 CLEAR PRIMER

Version Number 1.0
Revision Date 03/19/2008

Page 2 of 8
Print Date 1/3/2012

Skin : tearing, reddening, and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.
: Prolonged or repeated skin contact can cause de-fatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Chronic exposure : Refer to Section 11 for Toxicological Information.

Medical Conditions Aggravated by Exposure: : Individuals with chronic respiratory disorders (i.e. asthma, chronic bronchitis, etc.) may be adversely affected by any airborne contaminant.

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of vapours or decomposition products. Seek medical attention after significant exposure.

Ingestion : Do not induce vomiting without medical advice. If conscious, drink plenty of water. Seek medical attention if necessary.

Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : Less than 75 °F (24 °C)

Flammable Limits
Upper explosion limit : No data available
Lower explosion limit : No data available
Autoignition temperature : No data available
Suitable extinguishing media : Carbon dioxide blanket, Water, Foam, Dry chemical.

Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.

Unusual Fire/Explosion Hazards : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

PX1002 CLEAR PRIMER

Version Number 1.0
Revision Date 03/19/2008

Page 3 of 8
Print Date 1/3/2012

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

7. HANDLING AND STORAGE

Handling : Flammable liquid. Keep away from flames, hot surfaces, and sources of ignition. Use of non-sparking or explosion-proof equipment may be necessary. Never use compressed air for transferring product. Ensure all equipment is electrically grounded before beginning transfer operations. Take measures to prevent the build up of static electricity. Use only in area provided with appropriate exhaust ventilation.

Storage : Store below 120 °F (49 °C) Keep containers tightly closed in a cool, well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Flammable Liquid. Check local fire regulations for sprinkler or explosion proof storage location requirements.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection : Airborne contaminant levels should be maintained below the occupational exposure guidelines. When respiratory protection is required, use an approved air-purifying or positive pressure supplied-air respirator, depending upon potential airborne contaminant concentrations. Employees using respirators must be properly trained.

Eye/Face Protection : Wear goggles or face shield during operations that present a splash potential.

Hand protection : Protective gloves Protective gloves. Refer to equipment supplier to ensure protection.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Additional Protective Measures : Safety shoes

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Ensure adequate ventilation, especially in confined areas.

Engineering measures : Provide general and/or local exhaust ventilation to control airborne contaminant levels below the exposure guidelines.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

PX1002 CLEAR PRIMER

Version Number 1.0
Revision Date 03/19/2008

Page 4 of 8
Print Date 1/3/2012

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Toluene	20 ppm	Time Weighted Average (TWA):		ACGIH
	200 ppm	Time Weighted Average (TWA):		OSHA Z2
	300 ppm	Ceiling Limit Value:		OSHA Z2
	500 ppm	Maximum concentration:		OSHA Z2
	50 ppm 188 mg/m3	Time Weighted Average (TWA):		MX OEL
Ethyl alcohol	1,000 ppm	Time Weighted Average (TWA):		ACGIH
	1,000 ppm 1,900 mg/m3	PEL:		OSHA Z1
	1,000 ppm 1,900 mg/m3	Time Weighted Average (TWA):		MX OEL
Phenol	5 ppm	Time Weighted Average (TWA):		ACGIH
	5 ppm 19 mg/m3	PEL:		OSHA Z1
	5 ppm 19 mg/m3	Time Weighted Average (TWA):		MX OEL
	10 ppm 38 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Diacetone alcohol	50 ppm	Time Weighted Average (TWA):	Vapor.	ACGIH
	50 ppm 240 mg/m3	PEL:	Vapor.	OSHA Z1
	50 ppm 240 mg/m3	Time Weighted Average (TWA):		MX OEL
	75 ppm 360 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Ethyl acetate	400 ppm	Time Weighted Average (TWA):		ACGIH
	400 ppm 1,400 mg/m3	PEL:		OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: liquid	Evaporation rate	: Faster than Butyl Acetate
Appearance	: liquid	Specific Gravity	: Not determined
Color	: NO PIGMENT	Bulk density	: Not applicable

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

PX1002 CLEAR PRIMER

Version Number 1.0
Revision Date 03/19/2008

Page 5 of 8
Print Date 1/3/2012

Odour	: solvent	Vapour pressure	: Not determined
Melting point/range	: Not applicable	Vapour density	: Heavier than air.
Boiling Point:	: No data available	pH	: Not determined
Water solubility	: negligible		

10. STABILITY AND REACTIVITY

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : Keep away from oxidizing agents and open flame. Heat, flames and sparks.

Incompatible Materials : Incompatible with strong acids and oxidizing agents.

Hazardous decomposition products : Carbon dioxide (CO₂), carbon monoxide (CO), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
108-65-6	2-Methoxy-1-methylethyl acetate	Systemic effects	Liver, Kidney.
108-95-2	Phenol	Toxic	Refer to LC50 / LD50 Data on MSDS..
		Systemic effects	Kidney, central nervous system (CNS), Liver, Respiratory system.
		Corrosive	Eyes, Skin.
141-78-6	Ethyl acetate	Systemic effects	Eyes, Skin, Respiratory system.
108-88-3	Toluene	Systemic effects	central nervous system (CNS), Liver, Kidney, urinary system.
		Irritant	Skin, Eyes.
64-17-5	Ethyl alcohol	Systemic effects	Liver, heart or circulatory system, central nervous system (CNS), reproductive system.
123-42-2	Diacetone alcohol	Systemic effects	Eyes, Skin, Respiratory system, Liver, central nervous system (CNS).

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

PX1002 CLEAR PRIMER

Version Number 1.0
Revision Date 03/19/2008

Page 6 of 8
Print Date 1/3/2012

CAS-No.	Chemical Name	Route	Value	Species
108-65-6	2-Methoxy-1-methylethyl acetate	Oral LD50 Dermal LD50	8,532 mg/kg > 5 gm/kg	rat rabbit
108-95-2	Phenol	LC50 Oral LD50 Oral LD50 Oral LD50 Dermal LD50 Dermal LD50 Dermal LD50	316 mg/m3 270 mg/kg 270 mg/kg 317 mg/kg 630 mg/kg 850 mg/kg 669 mg/kg	rat mouse cat mouse rat rabbit rabbit rat
141-78-6	Ethyl acetate	LC50 Oral LD50	45 gm/m3 5,620 mg/kg	mouse rat
108-88-3	Toluene	LC50 LC50 LC50 Oral LD50 Oral LD50 Dermal LD50 Dermal LD50	49 gm/m3 636 mg/kg 2,600 - 7,500 mg/kg 14100 ul/kg 12,124 mg/kg	rat mouse mouse rat rat rabbit rabbit
64-17-5	Ethyl alcohol	LC50 Oral LD50	20000 ppm 3,450 mg/kg	rat mouse
123-42-2	Diacetone alcohol	Oral LD50 Dermal LD50	3,950 mg/kg 13,500 mg/kg	mouse rabbit

12. ECOLOGICAL INFORMATION

Persistence and degradability : No data available
Environmental Toxicity : No data available
Bioaccumulation Potential : No data available
Additional advice : No data available

13. DISPOSAL CONSIDERATIONS

Product : Dispose of properly. Do not dump into sewers, on the ground, or into any body of water. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal,

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

PX1002 CLEAR PRIMER

Version Number 1.0
Revision Date 03/19/2008

Page 7 of 8
Print Date 1/3/2012

state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification
Proper Shipping Name: Paint
Technical Name:
Hazard Class / Division 3
UN Number UN1263
Packing Group II
Label Required 3
Hazardous Substance Not applicable

ICAO/IATA (air) Refer to specific regulation.

IMO / IMDG (maritime) Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition 65 : WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	% in Product	RQ for component
Phenol	108-95-2	0.10 - 1.00	1,000 lbs

SARA Title III Section 313 Toxic Chemicals:

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****PX1002 CLEAR PRIMER**

Version Number 1.0

Revision Date 03/19/2008

Page 8 of 8

Print Date 1/3/2012

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight %
TOLUENE	108-88-3	5.00 - 10.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Methyl alcohol	67-56-1	0.10 - 1.00	
2-Propenoic acid, 2-methyl-, methyl ester	80-62-6	0.10 - 1.00	
Toluene	108-88-3	5.00 - 10.00	
Phenol	108-95-2	0.10 - 1.00	

WHMIS Classification : D1A

WHMIS Ingredient Disclosure List

CAS-No.
108-88-3
64-17-5
123-42-2
141-78-6

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Not determined

China IECS : Not determined

Europe EINECS : Not determined

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.