PolyOne

## MATERIAL SAFETY DATA SHEET **SX843A MAGENTA**

Version Number 1.3 Revision Date 03/20/2014

Page 1 of 6 Print Date 3/23/2014

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152				
Telephone	:	1 (440) 930-1000 or 1 (866) POLYONE		
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).		
Product name	:	SX843A MAGENTA		
Product code	:	FO20019518		
Chemical Name	:	Mixture		
CAS-No.	:	Mixture		
Product Use	:	Industrial Applications		

Components	CAS-No.	Weight percent	
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5	

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye and skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

## MATERIAL SAFETY DATA SHEET **SX843A MAGENTA**

Version Number 1.3 Revision Date 03/20/2014 Page 2 of 6 Print Date 3/23/2014

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: no data available
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>no data available</li> <li>no data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal.
	7. HANDLING AND STORAGE

POLYONE CORPORATION



# MATERIAL SAFETY DATA SHEET **SX843A MAGENTA**

ion Number 1.3 sion Date 03/20/2014				Print	Page 3 Date 3/23/2
Handling	fi P	ume condensates	may contain hoods, ducts	riate exhaust ventilation combustible or toxic res , and other surfaces to n s.	sidue.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.				
8.]	EXPOSURE	CONTROLS/I	PERSONAL	PROTECTION	
Respiratory protection	: N	lo personal respi	ratory protect	ive equipment normally	required.
Eye/Face Protection	: S	afety glasses wit	th side-shields	3	
Hand protection	: P	rotective gloves			
Skin and body protection	: L	ong sleeved clot	hing		
Additional Protective Measures	: S	afety shoes			
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures Exposure limit(s)		leat only in areas ppropriate exhau		riate exhaust ventilation at machinery.	. Provide
Components	Value	Exposur	e time	Exposure type	List:
Silica, amorphous,	0.8 mg/m3	Time Weight	ed Average		Z3
fumed, crystal-free	10 mg/m3	(TWA): mg/m3 Time Weighted Average (TWA):		Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):		Respirable dust.	MX OEL
	9. PHYSIC	CAL AND CHE	CMICAL PRO	OPERTIES	
Form	: liqui				t established
Appearance Colour	: visco : RED	ous, liquid		5	t determined
Odour	: KED : very				t applicable t determined
Melting point/range		pplicable			t determined
Boiling Point:		pplicable	pН	•	t applicable
Water solubility	: imm	iscible	_		
	10 0	STABILITY AN	ID DEACTI	VITV	
	10.0	SIADILIII AP	ID KLAUTT	V I I I	

P<u>olyOne</u>

#### MATERIAL SAFETY DATA SHEET SX843A MAGENTA

Version Number 1.3 Revision Date 03/20/2014 Page 4 of 6 Print Date 3/23/2014

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
112945-52-5	Silica, amorphous, fumed, crystal-free	Irritant	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
112945-52-5	Silica, amorphous, fumed, crystal-free	Oral LD50	3,160 mg/kg	rat

12. ECOLOGICAL INFORMATION				
Persistence and degradability	: Not readily biodegradable.			
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.			
Bioaccumulation Potential	: no data available			
Additional advice	: no data available			
	13. DISPOSAL CONSIDERATIONS			
Product	: Where possible recycling is preferred to disposal or incineration. The			

PolyOne.

# MATERIAL SAFETY DATA SHEET **SX843A MAGENTA**

sion Number 1.3 rision Date 03/20/2014	Page 5 of 6 Print Date 3/23/2014
	generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
not applicable	
California Propositior 65	: WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 E	stremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 T	oxic Chemicals:
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
Canadian Regulations:	

PolyOne.

## MATERIAL SAFETY DATA SHEET **SX843A MAGENTA**

Version Number 1.3 Revision Date 03/20/2014

\_

Page 6 of 6 Print Date 3/23/2014

Chemical Name			CAS-No.	Weight	NPRI ID#
				percent	
2-Ethylhexanoic acid zinc sal	2-Ethylhexanoic acid zinc salt			0.10 - 1.00	
WHMIS Classification	:	Not controlled.			
			s of this product (DSL) or are ex	are on the Canadia empt.	n Domestic
National Inventories:					
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Listed			
Japan ENCS	:	Not determined			
Korea KECI	:	Listed			
Philippines PICCS	:	Listed			
		16 OTHED D	NFORMATION	т	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.