

**POLYONE CORPORATION****MATERIAL SAFETY DATA SHEET****DB4477 Neutral**Version Number 1.2  
Revision Date 04/16/2009Page 1 of 8  
Print Date 1/7/2012**1. PRODUCT AND COMPANY IDENTIFICATION****POLYONE CORPORATION**  
8155 Cobb Center Drive, Kennesaw, GA 30152Telephone : Product Stewardship (770) 590-3500 x.3563  
Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).Product name : DB4477 Neutral  
Product code : FO20021108  
Chemical Name : Mixture  
CAS-No. : Mixture  
Product Use : Industrial Applications**2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS**

| Components                             | CAS-No.    | Weight % |
|--|------------|----------|
| Naphtha (petroleum), heavy alkylate    | 64741-65-7 | 1 - 5    |
| Naphtha, petroleum, hydrotreated heavy | 64742-48-9 | 1 - 5    |
| Miscellaneous Zinc Compounds           | 0-05-5     | 1 - 5    |
| Calcium oxide                          | 1305-78-8  | 1 - 5    |
| Stoddard solvent                       | 8052-41-3  | 1 - 5    |
| Miscellaneous Barium Compounds         | 0-08-8     | 1 - 5    |
| Alkanes, C14-17, chloro                | 85535-85-9 | 1 - 5    |

**3. HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

**POTENTIAL HEALTH EFFECTS****Routes of Exposure:** : Inhalation, Skin contact, Ingestion**Acute exposure**Inhalation : Inhalation of airborne droplets may cause irritation of the respiratory tract.  
Ingestion : May be harmful if swallowed.  
Eyes : May cause eye and skin irritation.  
Skin : Experience shows no unusual dermatitis hazard from routine handling.

**POLYONE CORPORATION****MATERIAL SAFETY DATA SHEET****DB4477 Neutral**Version Number 1.2  
Revision Date 04/16/2009Page 2 of 8  
Print Date 1/7/2012**Chronic exposure** : Refer to Section 11 for Toxicological Information.**Medical Conditions** : None known.**Aggravated by Exposure:****4. FIRST AID MEASURES****Inhalation** : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.**Ingestion** : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.**Eyes** : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.**Skin** : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.**5. FIRE-FIGHTING MEASURES****Flash point** : No data available**Flammable Limits**

Upper explosion limit : No data available

Lower explosion limit : No data available

**Autoignition temperature** : Not applicable**Suitable extinguishing media** : Carbon dioxide blanket, Water spray, Dry powder, Foam.**Special Fire Fighting Procedures** : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.**Unusual Fire/Explosion Hazards** : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), other hazardous materials, and smoke are all possible.**6. ACCIDENTAL RELEASE MEASURES****Personal precautions** : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.**Environmental precautions** : The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.**Methods for cleaning up** : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**DB4477 Neutral**

Version Number 1.2  
Revision Date 04/16/2009

Page 3 of 8  
Print Date 1/7/2012

appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

**7. HANDLING AND STORAGE**

- Handling : Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
- Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

- Respiratory protection : No personal respiratory protective equipment normally required.
- Eye/Face Protection : Safety glasses with side-shields
- Hand protection : Protective gloves
- Skin and body protection : Long sleeved clothing
- Additional Protective Measures : Safety shoes
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
- Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**DB4477 Neutral**

Version Number 1.2  
Revision Date 04/16/2009

Page 4 of 8  
Print Date 1/7/2012

| Components       | Value                          | Exposure time                                       | Exposure type                | List:    |         |
|------------------|--------------------------------|---|------------------------------|----------|---------|
| Calcium oxide    | 2 mg/m3                        | Time Weighted Average (TWA):                        |                              | ACGIH    |         |
|                  | 2 mg/m3                        | Recommended exposure limit (REL):                   |                              | NIOSH    |         |
|                  | 5 mg/m3                        | PEL:  |                              | OSHA Z1  |         |
|                  | 5 mg/m3                        | Time Weighted Average (TWA):                        |                              | OSHA Z1A |         |
|                  | 2 mg/m3                        | Time Weighted Average (TWA):                        |                              | MX OEL   |         |
| Stoddard solvent | 100 ppm                        | Time Weighted Average (TWA):                        |                              | ACGIH    |         |
|                  | 350 mg/m3                      | Recommended exposure limit (REL):                   |                              | NIOSH    |         |
|                  | 1,800 mg/m3                    | Ceiling Limit Value and Time Period (if specified): |                              | NIOSH    |         |
|                  | 500 ppm<br>2,900 mg/m3         | PEL:  |                              | OSHA Z1  |         |
|                  | 100 ppm<br>525 mg/m3           | Time Weighted Average (TWA):                        |                              | OSHA Z1A |         |
|                  | 100 ppm<br>523 mg/m3           | Time Weighted Average (TWA):                        |                              | MX OEL   |         |
|                  | 200 ppm<br>1,050 mg/m3         | Short Term Exposure Limit (STEL):                   |                              | MX OEL   |         |
|                  | Miscellaneous Barium Compounds | 0.5 mg/m3   | Time Weighted Average (TWA): | as Ba    | ACGIH   |
|                  |                                | 0.5 mg/m3   | PEL:                         | as Ba    | OSHA Z1 |

**9. PHYSICAL AND CHEMICAL PROPERTIES**

|                     |                   |                  |                   |
|---------------------|-------------------|------------------|-------------------|
| Form                | : liquid          | Evaporation rate | : Not established |
| Appearance          | : Viscous, liquid | Specific Gravity | : Not determined  |
| Color               | : NO PIGMENT      | Bulk density     | : Not applicable  |
| Odour               | : Very faint      | Vapour pressure  | : Not determined  |
| Melting point/range | : Not applicable  | Vapour density   | : Not determined  |
| Boiling Point:      | : Not applicable  | pH               | : Not applicable  |
| Water solubility    | : Immiscible      |                  |                   |

**10. STABILITY AND REACTIVITY**

|                          |  |
|--------------------------|--|
| Stability                | : Stable.  |
| Hazardous Polymerization | : Will not occur.  |
| Conditions to avoid      | : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. |

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**DB4477 Neutral**

Version Number 1.2  
Revision Date 04/16/2009

Page 5 of 8  
Print Date 1/7/2012

Incompatible Materials : Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition products : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

**11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No.   | Chemical Name                  | Effect           | Target Organ                                 |
|-----------|--------------------------------|------------------|--|
| 0-05-5    | Miscellaneous Zinc Compounds   | Systemic effects | Eyes, Skin, Respiratory system.              |
| 1305-78-8 | Calcium oxide                  | Irritant         | Skin.  |
|           |                                | Systemic effects | Eyes, Skin, Respiratory system.              |
|           |                                | Corrosive        | Skin.  |
| 8052-41-3 | Stoddard solvent               | Systemic effects | Kidney, Liver, central nervous system (CNS). |
|           |                                | Irritant         | Eyes, Skin, Respiratory system.              |
| 0-08-8    | Miscellaneous Barium Compounds | Irritant         | Respiratory system, Eyes.                    |
|           |                                | Systemic effects | Respiratory system.                          |

**LC50 / LD50**

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No.   | Chemical Name    | Route       | Value         | Species |
|-----------|------------------|-------------|---------------|---------|
| 8052-41-3 | Stoddard solvent | Oral LD50   | > 5,000 mg/kg | rat     |
|           |                  | Dermal LD50 | > 3,000 mg/kg | rabbit  |

**Carcinogenicity**

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|---------|---------------|------|------|-----|
|---------|---------------|------|------|-----|

**IARC Carcinogen Classifications:**

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**DB4477 Neutral**

Version Number 1.2  
Revision Date 04/16/2009

Page 6 of 8  
Print Date 1/7/2012

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

**12. ECOLOGICAL INFORMATION**

- Persistence and degradability : Not readily biodegradable.
- Environmental Toxicity : Environmental toxicity has not been established for this mixture as a whole.
- Bioaccumulation Potential : No data available
- Additional advice : No data available

**13. DISPOSAL CONSIDERATIONS**

- Product : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
- Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

**14. TRANSPORT INFORMATION**

- U.S. DOT Classification : Refer to specific regulation.
- ICAO/IATA (air) : Refer to specific regulation.
- IMO / IMDG (maritime) : Refer to specific regulation.

**15. REGULATORY INFORMATION**

US Regulations:

- OSHA Status : Classified as hazardous based on components.
- TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**DB4477 Neutral**

Version Number 1.2  
Revision Date 04/16/2009

Page 7 of 8  
Print Date 1/7/2012

California Proposition 65 : WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

| Chemical Name    | CAS-No. | Weight %    |
|------------------|---------|-------------|
| ZINC COMPOUNDS   | 0-05-5  | 0.10 - 1.00 |
| BARIUM COMPOUNDS | 0-08-8  | 0.10 - 1.00 |

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name                | CAS-No. | Weight %    | NPRI ID# |
|------------------------------|---------|-------------|----------|
| Miscellaneous Zinc Compounds | 0-05-5  | 0.10 - 1.00 | 241      |

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

|           |
|-----------|
| CAS-No.   |
| 1305-78-8 |
| 8052-41-3 |
| 0-08-8    |

DSL : DSL status has not been determined. Quantity use in Canada may be restricted by regulations.

National Inventories:

Australia AICS : Not determined

China IECS : Not determined

Europe EINECS : Not determined

Japan ENCS : Not determined

Korea KECI : Not determined



**POLYONE CORPORATION**

**MATERIAL SAFETY DATA SHEET**

**DB4477 Neutral**

Version Number 1.2  
Revision Date 04/16/2009

Page 8 of 8  
Print Date 1/7/2012

Philippines PICCS : Not determined

**16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.