## MATERIAL SAFETY DATA SHEET STAN-TONE VC-31757 RED/BROWN

Version Number 1.0 Revision Date 09/03/2009 Page 1 of 6 Print Date 1/9/2012

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	STAN-TONE VC-31757 RED/BROWN
Product code	:	FO20022862
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Iron oxide	1309-37-1	10 - 30
Mica	12001-26-2	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

## MATERIAL SAFETY DATA SHEET STAN-TONE VC-31757 RED/BROWN

Version Number 1.0 Revision Date 09/03/2009 Page 2 of 6 Print Date 1/9/2012

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	: :	not applicable not applicable Not relevant Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume



## MATERIAL SAFETY DATA SHEET STAN-TONE VC-31757 RED/BROWN

Version Number 1.0 Revision Date 09/03/2009 Page 3 of 6 Print Date 1/9/2012

condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. Keep containers dry and tightly closed to avoid moisture absorption Storage : and contamination. Keep in a dry, cool place. 8. EXPOSURE CONTROLS/PERSONAL PROTECTION Respiratory protection No personal respiratory protective equipment normally required. If : dusty conditions occur wear appropriate respiratory protection. **Eye/Face Protection** : Safety glasses with side-shields Hand protection Protective gloves : Skin and body protection : Long sleeved clothing Additional Protective Safety shoes : Measures General Hygiene : Handle in accordance with good industrial hygiene and safety Considerations practice. Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Iron oxide	5 mg/m3	Time Weighted Average	Respirable fraction.	ACGIH
		(TWA):		
	10 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
Mica	3 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	3 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	OSHA Z1A
	3 mg/m3	Time Weighted Average (TWA):		MX OEL

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form

: solid

Evaporation rate

: Not applicable

# MATERIAL SAFETY DATA SHEET STAN-TONE VC-31757 RED/BROWN

Version Number 1.0 Revision Date 09/03/2009

Appearance

Colour

Melting point/range Boiling Point:	: ve : N : no	ery faint ot determined ot applicable soluble	Vapour pressure Vapour density pH	: : :	not applicable not applicable not applicable
	1	). STABILITY AND RE	EACTIVITY		
Stability	:	Stable			
Hazardous Polymerization	:	Will not occur.			
Conditions to avoid	:	To avoid thermal decon oxidizing agents and op	-	eat.	Keep away from
Incompatible Materials	:	Incompatible with stron with acetal homopolym			
Hazardous decomposition products	:	Carbon dioxide (CO2), (NOx), hydrogen chlori smoke are all possible. or more) above 392 °F °C) may result in produ monoxide and hydrogen	de (HCl), other hazardo Prolonged heating (app (200 °C) or short term h ct decomposition and e	ous i prox neati	materials, and imately 30 minutes ing at 482 °F (250

: powder, granular

: BROWN

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

**Toxicity Overview** 

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Cl	nemical Name	Effect	Target Organ
1309-37-1	Iron oxide		Systemic effects	Respiratory system.
12001-26-2	Mica		Systemic effects	Respiratory system.
		12. ECOLOGIC	AL INFORMATION	I
Persistence and degrad	ability	: Not readily bio	odegradable.	
Environmental Toxicit	у	: Adverse ecolog use.	gical impact is not kno	own or expected under normal
Bioaccumulation Poter	ntial	: no data availab	ble	
Additional advice		: no data availab	ble	
		13. DISPOSAL (	CONSIDERATIONS	



Specific Gravity

Bulk density

Page 4 of 6 Print Date 1/9/2012

: Not determined

: Not determined

PolyOne.

# MATERIAL SAFETY DATA SHEET STAN-TONE VC-31757 RED/BROWN

sion Number 1.0	Page 5 of
ision Date 09/03/2009	Print Date 1/9/201
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG (maritime)	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	us Substances (40 CFR 302)
not applicable	
California Propositior 65	: Not applicable
SARA Title III Section 302 E	Extremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 T	'oxic Chemicals:
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation

PolvOne

## MATERIAL SAFETY DATA SHEET STAN-TONE VC-31757 RED/BROWN

Version Number 1.0 Revision Date 09/03/2009 Page 6 of 6 Print Date 1/9/2012

National Pollutant Release Inventory (NPRI) Chemical Name			CAS-No.	Weight percent	NPRI ID#
Miscellaneous Zinc Compoun	ds		Not Available	0.10 - 1.00	241
WHMIS Classification	:	Not controlled.			
DSL	:		s of this product are (DSL) or are exem		n Domestic
ational Inventories:					
Australia AICS	:	Not determined			
China IECS	:	Not determined			
Europe EINECS	:	Not determined			
Japan ENCS	:	Not determined			
Korea KECI	:	Not determined			
Philippines PICCS	:	Not determined			

#### 16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.