MATERIAL SAFETY DATA SHEET **DB3611 BLUE PMS 281U**

Version Number 1.0 Revision Date 09/23/2009

Page 1 of 7 Print Date 1/9/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

| Telephone:Emergency telephone: | Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
|--------------------------------|--|
| Product name : | DB3611 BLUE PMS 281U |
| Product code : | FO20022980 |
| Chemical Name : | Mixture |
| CAS-No. : | Mixture |
| Product Use : | Industrial Applications |

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

| Components | CAS-No. | Weight percent |
|------------------|------------|----------------|
| Stoddard solvent | 8052-41-3 | 0.1 - 1 |
| Titanium dioxide | 13463-67-7 | 0.1 - 1 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Skin contact, Ingestion |
|---|--|
| Acute exposure | |
| Inhalation | : Inhalation of airborne droplets may cause irritation of the respiratory tract. |
| Ingestion | : May be harmful if swallowed. |
| Eyes | : May cause eye and skin irritation. |
| Skin | : Experience shows no unusual dermatitis hazard from routine handling. |
| Chronic exposure | : Refer to Section 11 for Toxicological Information. |
| Medical Conditions Aggravated by Exposure: | : None known. |

PolyOne.

MATERIAL SAFETY DATA SHEET **DB3611 BLUE PMS 281U**

Version Number 1.0 Revision Date 09/23/2009 Page 2 of 7 Print Date 1/9/2012

| | 4. FIRST AID MEASURES |
|--|--|
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice. |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. |
| Eyes | : Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention. |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists seek medical attention. |
| | 5. FIRE-FIGHTING MEASURES |
| Flash point | : no data available |
| Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards | no data available no data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. |
| | 6. ACCIDENTAL RELEASE MEASURES |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. |
| Environmental precautions | : The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment. |
| Methods for cleaning up | : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods. |
| | 7. HANDLING AND STORAGE |
| Handling | : Heat only in areas with appropriate exhaust ventilation. Processing |

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **DB3611 BLUE PMS 281U**

Version Number 1.0 Revision Date 09/23/2009

Storage

Page 3 of 7 Print Date 1/9/2012

fume condensates may contain combustible or toxic residue.
Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

| Eye/Face Protection:Safety glasses with side-shieldsHand protection:Protective glovesSkin and body protection:Long sleeved clothingAdditional Protective Measures:Safety shoesGeneral Hygiene Considerations:Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.Engineering measures:Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. | Respiratory protection | : | No personal respiratory protective equipment normally required. |
|--|--------------------------|---|---|
| Skin and body protection: Long sleeved clothingAdditional Protective Measures: Safety shoesGeneral Hygiene Considerations: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.Engineering measures: Heat only in areas with appropriate exhaust ventilation. Provide | Eye/Face Protection | : | Safety glasses with side-shields |
| Additional Protective Measures:Safety shoesGeneral Hygiene Considerations:Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.Engineering measures:Heat only in areas with appropriate exhaust ventilation. Provide | Hand protection | : | Protective gloves |
| MeasuresGeneral Hygiene Considerations: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.Engineering measures: Heat only in areas with appropriate exhaust ventilation. Provide | Skin and body protection | : | Long sleeved clothing |
| Considerationspractice. Wash hands before breaks and at the end of workday.Engineering measures: Heat only in areas with appropriate exhaust ventilation. Provide | | : | Safety shoes |
| | | : | e .e . |
| | Engineering measures | : | v 11 1 |

Exposure limit(s)

<u>PolyOne</u>.

MATERIAL SAFETY DATA SHEET **DB3611 BLUE PMS 281U**

Version Number 1.0 Revision Date 09/23/2009 Page 4 of 7 Print Date 1/9/2012

| Components | Value | Exposure time | Exposure type | List: |
|------------------|-----------|--------------------------------------|---------------|----------|
| Stoddard solvent | 100 ppm | Time Weighted Average (TWA): | | ACGIH |
| | 350 | Recommended exposure | | NIOSH |
| | mg/m3 | limit (REL): | | |
| | 1,800 | Ceiling Limit Value and | | NIOSH |
| | mg/m3 | Time Period (if specified): | | |
| | 500 ppm | PEL: | | OSHA Z1 |
| | 2,900 | | | |
| | mg/m3 | | | |
| | 100 ppm | Time Weighted Average | | OSHA Z1A |
| | 525 mg/m3 | (TWA): | | |
| | 100 ppm | Time Weighted Average | | MX OEL |
| | 523 mg/m3 | (TWA): | | |
| | 200 ppm | Short Term Exposure Limit | | MX OEL |
| | 1,050 | (STEL): | | |
| | mg/m3 | | | |
| Titanium dioxide | 10 mg/m3 | Time Weighted Average (TWA): | | ACGIH |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| | 10 mg/m3 | Time Weighted Average (TWA): | Total dust. | OSHA Z1A |
| | 10 mg/m3 | Time Weighted Average (TWA): | as Ti | MX OEL |
| | 20 mg/m3 | Short Term Exposure Limit (STEL): | as Ti | MX OEL |

9. PHYSICAL AND CHEMICAL PROPERTIES

Form:Appearance:Colour:Odour:Melting point/range:Boiling Point::Water solubility:

_

- liquid
 viscous, liquid
 BLUE
 very faint
 not applicable
 not applicable
 immiscible
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not established
 Not determined
 Not applicable
 Not determined
 Not determined
 Not determined
 Not applicable

| | 1 | 0. STABILITY AND REACTIVITY |
|--------------------------|---|---|
| Stability | : | Stable |
| Hazardous Polymerization | : | Will not occur. |
| Conditions to avoid | : | Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. |
| Incompatible Materials | : | Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing. |

MATERIAL SAFETY DATA SHEET **DB3611 BLUE PMS 281U**

Version Number 1.0 Revision Date 09/23/2009 Page 5 of 7 Print Date 1/9/2012

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|------------|------------------|------------------|--|
| 8052-41-3 | Stoddard solvent | Systemic effects | Kidney, Liver, central nervous system (CNS). |
| | | Irritant | Eyes, Skin, Respiratory system. |
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. |

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No. | Chemical Name | Route | Value | Species |
|-----------|------------------|-------------|---------------|---------|
| 8052-41-3 | Stoddard solvent | Oral LD50 | > 5,000 mg/kg | rat |
| | | Dermal LD50 | > 3,000 mg/kg | rabbit |

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|------------|------------------|------|------|-----|
| 13463-67-7 | Titanium dioxide | no | 2B | no |

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability : Not rea

: Not readily biodegradable.

Environmental Toxicity

ty : Environmental toxicity has not been established for this mixture as a

PolyOne.

MATERIAL SAFETY DATA SHEET **DB3611 BLUE PMS 281U**

Version Number 1.0 Revision Date 09/23/2009 Page 6 of 7 Print Date 1/9/2012

| | whole. |
|------------------------------|---|
| Bioaccumulation Potential | : no data available |
| Additional advice | : no data available |
| | 13. DISPOSAL CONSIDERATIONS |
| Product | : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| Contaminated packaging | : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| | 14. TRANSPORT INFORMATION |
| U.S. DOT Classification | : Refer to specific regulation. |
| ICAO/IATA | : Refer to specific regulation. |
| IMO / IMDG (maritime) | : Refer to specific regulation. |
| | 15. REGULATORY INFORMATION |
| US Regulations: | |
| OSHA Status | : Classified as hazardous based on components. |
| TSCA Status | : All components of this product are listed on or exempt from the TSCA Inventory. |
| US. EPA CERCLA Hazardou | s Substances (40 CFR 302) |
| not applicable | |
| California Proposition 65 | : Not applicable |
| SARA Title III Section 302 E | xtremely Hazardous Substance |
| | |

PolyOne

MATERIAL SAFETY DATA SHEET **DB3611 BLUE PMS 281U**

Version Number 1.0 Revision Date 09/23/2009 Page 7 of 7 Print Date 1/9/2012

| SARA Title III Section 313 Tox | 10 C | chemicals: |
|----------------------------------|-------|--|
| Unless specific chemicals are id | enti | fied under this section, this product is Not Applicable under this regula |
| Canadian Regulations: | | |
| National Pollutant Release | se Ir | nventory (NPRI) |
| not applicable | | |
| WHMIS Classification | : | D2A |
| DSL | : | All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt. |
| National Inventories: | | |
| Australia AICS | : | Not determined |
| China IECS | : | Not determined |
| Europe EINECS | : | Listed |
| Japan ENCS | : | Not determined |
| Korea KECI | : | Not determined |
| Philippines PICCS | : | Not determined |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.