PolvOne

MATERIAL SAFETY DATA SHEET MM487 HOT MELT

Version Number 1.1 Revision Date 10/20/2009

Page 1 of 7 Print Date 1/9/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	MM487 HOT MELT
Product code	:	FO20023091
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Calcium carbonate	471-34-1	1 - 5
Miscellaneous Zinc Compounds	Not Available	1 - 5
Miscellaneous Barium Compounds	Not Available	1 - 5
Calcium carbonate	1317-65-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye and skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET *MM487 HOT MELT*

Version Number 1.1 Revision Date 10/20/2009 Page 2 of 7 Print Date 1/9/2012

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If e irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: no data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 no data available no data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne
Unusual Fire/Explosion Hazards	 contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) und fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSD for proper disposal methods.

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET MM487 HOT MELT

Version Number 1.1 Revision Date 10/20/2009 Page 3 of 7 Print Date 1/9/2012

	7.	HANDLING AND STORAG	E		
Handling	fi P	leat only in areas with appropri ume condensates may contain of eriodically clean hoods, ducts, ccumulation of these materials.	combustible or toxic resi and other surfaces to mi	due.	
Storage		: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.			
8.	EXPOSURE	CONTROLS/PERSONAL I	PROTECTION		
Respiratory protection	: N	lo personal respiratory protecti	ve equipment normally	required.	
Eye/Face Protection	: S	afety glasses with side-shields			
Hand protection	: P	rotective gloves			
Skin and body protection	1 : L	: Long sleeved clothing			
Additional Protective Measures	: S	afety shoes			
General Hygiene Considerations		landle in accordance with good ractice. Wash hands before bro			
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1	
	15 mg/m3	PEL:	Total dust.	OSHA Z1	
	10 mg/m3	Time Weighted Average (TWA):		MX OEL	
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL	
Miscellaneous Barium Compounds	0.5 mg/m3	Time Weighted Average (TWA):	as Ba	ACGIH	
1	0.5 mg/m3	PEL:	as Ba	OSHA Z1	

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour
- : liquid: viscous, liquid: WHITE: very faint
- Evaporation rate Specific Gravity Bulk density Vapour pressure
- Not establishedNot determinedNot applicableNot determined

MATERIAL SAFETY DATA SHEET MM487 HOT MELT

Version Number 1.1 Revision Date 10/20/2009

_

Melting point/range Boiling Point: Water solubility	not applicablenot applicableimmiscible	Vapour density pH	Not determinedNot applicable
	10. STABILITY ANI	O REACTIVITY	
Stability	: Stable		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from ox decomposition, do	kidizing agents and open f not overheat.	lame. To avoid thermal
Incompatible Materials	-	strong acids and oxidizing olymers and acetal copoly	
Hazardous decomposition products	(NOx), hydrogen cl smoke are all possi degradation. As a g after one hour at 17	D2), carbon monoxide (C0 hloride (HCl), other hazar ble. Prolonged heating m general rule of thumb, deg 7 °C (350 °F), after 10 m inutes at 232 °C (450 °F)	dous materials, and ay result in product gradation begins to occur inutes at 204 °C (400

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
471-34-1	Calcium carbonate	Irritant	Eyes, Skin.
Not Available	Miscellaneous Zinc	Systemic effects	Eyes, Skin, Respiratory
	Compounds		system.
	Miscellaneous Barium	Irritant	Respiratory system, Eyes.
	Compounds		
		Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
471-34-1	Calcium carbonate	Oral LD50Oral LD50	6,450 mg/kg6,450 mg/kg	ratrat

PolyOne

Page 4 of 7 Print Date 1/9/2012

PolyOne.

MATERIAL SAFETY DATA SHEET MM487 HOT MELT

Version Number 1.1 Revision Date 10/20/2009 Page 5 of 7 Print Date 1/9/2012

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: no data available
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
not applicable	
California Proposition	: Not applicable

MATERIAL SAFETY DATA SHEET MM487 HOT MELT

Version Number 1.1 Revision Date 10/20/2009 Page 6 of 7 Print Date 1/9/2012

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent
ZINC COMPOUNDS	Not Available	1.00 - 5.00
BARIUM COMPOUNDS		1.00 - 5.00
ZINC COMPOUNDS		0.10 - 1.00

Canadian Regulations:

 National Pollutant Release Inventory (NPRI)

 Chemical Name
 CAS-No.
 Weight percent
 NPRI ID#

 Miscellaneous Zinc Compounds
 Not Available
 1.00 - 5.00
 241

 0.10 - 1.00
 241

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.
Not Available

DSL

DSL status has not been determined. Quantity use in Canada may be restricted by regulations.

National Inventories:

Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

:

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET MM487 HOT MELT

Version Number 1.1 Revision Date 10/20/2009 Page 7 of 7 Print Date 1/9/2012

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.