Valspar 70 Base

Version Number 1.5 Revision Date 06/07/2016

'nе

Page 1 of 20 Print Date 06/09/2016

SAFETY DATA SHEET

Valspar 70 Base

Section 1. Identificati	on	
GHS product identifier Chemical name CAS number Other means of identification Product type		Valspar 70 Base Mixture FO20023141 liquid
	stance :	e or mixture and uses advised against Industrial applications. Plastics.
Supplier's details	:	POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A

GHS label elements

Valspar 70 Base

<u>PolyOne</u>

Version Number	er 1.5
Revision Date	06/07/2016

Page 2 of 20 Print Date 06/09/2016

Hazard pictograms	:	
Signal word Hazard statements	:	Danger May cause an allergic skin reaction. May cause cancer.
Precautionary statements		
General	:	Not applicable.
Prevention	:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Avoid breathing vapor. Contaminated work clothing must not be allowed out of the workplace.
Response	:	IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention.
Storage	:	Store in a well-ventilated place.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known.

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	FO20023141

CAS number/other identifiers

Ingredient name	%	CAS number
Titanium dioxide	10 - 25	13463-67-7
Diisodecyl phthalate (mixed isomers)	5 - 6.8	68515-49-1
Bisphenol A - Epichlorohydrin polymer	1 - 1.5	25068-38-6



Valspar 70 Base

Version Number 1.5 Revision Date 06/07/2016 Page 3 of 20 Print Date 06/09/2016

Antimony trioxide	1 - 1.5	1309-64-4
Silica, cristobalite	0.3 - 1	14464-46-1
Naphthalene	0.3 - 1	91-20-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting

Valspar 70 Base

Version Number 1.5 Revision Date 06/07/2016



Page 4 of 20 Print Date 06/09/2016

unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects		
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	May cause an allergic skin reaction.
Ingestion	:	No known significant effects or critical hazards.
Over-exposure signs/symptoms		
Eye contact	:	No specific data.
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following:
		irritation
		redness
Ingestion	:	No specific data.
Indication of immediate medical atten	ntio	n and special treatment needed, if necessary
Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Valspar 70 Base



Version Number 1.5 Revision Date 06/07/2016	Page 5 of 20 Print Date 06/09/2016
Suitable extinguishing media Unsuitable extinguishing media Specific hazards arising from the	
chemical Hazardous thermal	may burst. May emit Hydrogen Chloride (HCl).
decomposition products	Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides
Special protective actions for fire- fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for : fire-fighters	

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containme	nt a	nd cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Valspar 70 Base

vOne.

Version Number 1.5	Page 6 of 20
Revision Date 06/07/2016	Print Date 06/09/2016
Large spill :	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to

local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection



Valspar 70 Base

Version Number 1.5 Revision Date 06/07/2016 Page 7 of 20 Print Date 06/09/2016

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Titanium dioxide	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 15 mg/m3 Form: Total dust NIOSH REL (1994-06-01)
	ACGIH TLV (1996-05-18) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 10 mg/m3
Diisodecyl phthalate (mixed isomers)	
Bisphenol A - Epichlorohydrin polymer	
Antimony trioxide	OSHA PEL (1993-06-30) expressed as Sb PEL: Permissible Exposure Level 0.5 mg/m3 NIOSH REL (1994-06-01) expressed as Sb Time Weighted Average (TWA) 0.5 mg/m3 OSHA PEL 1989 (1989-03-01) expressed as Sb PEL: Permissible Exposure Level 0.5 mg/m3 ACGIH TLV (1994-09-01)
Silica, cristobalite	OSHA PEL 1989 (1989-03-01) Calculated as Quartz PEL: Permissible Exposure Level 0.05 mg/m3 Form: Respirable dust OSHA - PEL Z3 (1997-09-03) Time Weighted Average (TWA) Form: Respirable Time Weighted Average (TWA) 10 mg/m3 Form: Respirable Time Weighted Average (TWA) 30 mg/m3 Form: Total dust NIOSH REL (1994-06-01) Time Weighted Average (TWA) 0.05 mg/m3 Form: Respirable dust
	ACGIH TLV (2005-12-09) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 0.025 mg/m3 Form: Respirable fraction





Version Number 1.5 Revision Date 06/07/2016 Page 8 of 20 Print Date 06/09/2016

Naphthalene		OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 50 mg/m3 10 ppm Short Term Exposure Limit value for a 15-minute reference period expressed in parts per million or in mg/m3. 75 mg/m3 15 ppm OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 50 mg/m3 10 ppm NIOSH REL (1994-06-01) Time Weighted Average (TWA) 50 mg/m3 10 ppm Short Term Exposure Limit value for a 15-minute reference period expressed in parts per million or in mg/m3. 75 mg/m3 15 ppm ACGIH TLV (1996-05-18) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 52 mg/m3 10 ppm
Appropriate engineering controls Environmental exposure controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures Eye/face protection	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products

Valspar 70 Base



Version Number 1.5 Revision Date 06/07/2016	Page 9 of 20 Print Date 06/09/2016
	if a risk assessment indicates this is necessary. Considering the
	parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection :	Personal protective equipment for the body should be selected based

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

- Other skin protection: Appropriate footwear and any additional skin protection measures
should be selected based on the task being performed and the risks
involved and should be approved by a specialist before handling this
product.Respiratory protection: Use a properly fitted, air-purifying or air-fed respirator complying
 - : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state	•	liquid [liquid]
Color	- ÷	NO PIGMENT
Odor		Not available.
Odor threshold	:	Not available.
pH	:	Not available.
Melting point	:	Not available.
		Not available.
Boiling point	:	not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n-	:	Not available.
octanol/water		



Valspar 70 Base

Version Number 1.5 Revision Date 06/07/2016 Page 10 of 20 Print Date 06/09/2016

Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	Dynamic: Not available.
-		Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Avoid contact with acetal homopolymers and acetyl homopolymers during processing.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Titanium dioxide				
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-
Diisodecyl phthalate (mixed i	somers)			·
	LD50 Oral	Rat	60,000 mg/kg	-
	LD50 Dermal	Rabbit	16,000 mg/kg	-
Bisphenol A - Epichlorohydri	n polymer			
	LD50 Oral	Rat	13,600 mg/kg	-
	LD50 Oral	Rat	11,400 mg/kg	-
	LD50 Oral	Rat	11,400 mg/kg	-
	LD50 Oral	Rat	30,000 mg/kg	-
	LD50 Oral	Rat	30,000 mg/kg	-
	LD50 Oral	Rat	30,000 mg/kg	-



Valspar 70 Base

Version Number 1.5 Revision Date 06/07/2016

Page 11 of 20 Print Date 06/09/2016

	LD50 Oral	Rat	30,000 mg/kg	-
	LD50 Oral	Rat	13,600 mg/kg	-
Antimony trioxide				
	LD50 Oral	Rat	34,600 mg/kg	-
	LD50 Oral	Rat	34,000 mg/kg	-
Silica, cristobalite				
Naphthalene				
	LD50 Oral	Rat	490 mg/kg	-
	LD50 Dermal	Rabbit	20,000 mg/kg	-
Conclusion/Summary	: Mixtu	re.Not fully tested.		

Conclusion/Summary

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium dioxide	Skin - Mild irritant	Human		72 hrs	-
Diisodecyl phthalate (mixed isomers)	Eyes - Mild irritant	Rabbit			-
Bisphenol A - Epichlorohydrin polymer	Eyes - Mild irritant	Rabbit			-
	Eyes - Mild irritant	Rabbit			-
	Skin - Moderate irritant	Rabbit		24 hrs	-
	Skin - Severe irritant	Rabbit		24 hrs	-
	Eyes - Mild irritant	Rabbit			-
Antimony trioxide	Eyes - Mild irritant	Rabbit			-
Naphthalene	Skin - Severe irritant	Rabbit		24 hrs	-
	Skin - Mild irritant	Rabbit			-
Conclusion/Summary Skin Eyes		ixture.Not fu ixture.Not fu			

Respiratory

Mixture.Not fully tested. Mixture.Not fully tested.

Sensitization

Conclusion/Summary		
Skin	:	Mixture.Not fully tested.
Respiratory	:	Mixture.Not fully tested.
		11/20

:

<u>PolyOne</u>

Valspar 70 Base

Version Number 1.5 Revision Date 06/07/2016 Page 12 of 20 Print Date 06/09/2016

<u>Mutagenicity</u>				
Conclusion/Summary	:	Mixture.Not fu	lly tested.	
Carcinogenicity				
Conclusion/Summary	:	Mixture.Not fu	lly tested.	
Classification	OCILA	LADC	NTOD	
Product/ingredient	OSHA	IARC	NTP	
name Titanium dioxide		20		
		2B		
Antimony trioxide		2B		
Silica, cristobalite		1		
Naphthalene		2B		
<u>Reproductive toxicity</u>				
Conclusion/Summary	:	Mixture.Not fu	lly tested.	
Teratogenicity				
Conclusion/Summary	:	Mixture.Not fu	lly tested.	
Specific target organ toxicity Not available.	y (single expo	osure)		
Specific target organ toxicity Not available.	y (repeated e	<u>xposure)</u>		
Aspiration hazard Not available.				
Information on the likely rou exposure	ites of :	Not available.		
Potential acute health effects				
Eye contact		No known sign	ificant effects or critical hazards.	
Inhalation	:		ificant effects or critical hazards.	
Skin contact			illergic skin reaction.	
	:			
Ingestion	:	INO KHOWH SIGN	ificant effects or critical hazards.	

Symptoms related to the physical, chemical and toxicological characteristics



Valspar 70 Base

Version Number 1.5	Page 13 of 20
Revision Date 06/07/2016	Print Date 06/09/2016

Eye contact Inhalation Skin contact	:	No specific data. No specific data. Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Delayed and immediate effects and a	lso (chronic effects from short and long term exposure
Short term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Long term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.
General	:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	No known significant effects or critical hazards.
Developmental effects	:	No known significant effects or critical hazards.
Fertility effects	:	No known significant effects or critical hazards.
Numerical measures of toxicity		

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
	40/00		



Valspar 70 Base

Version Number 1.5 Revision Date 06/07/2016

Page 14 of 20 Print Date 06/09/2016

Titanium dioxide			
	Acute LC50 > 1,000,000 µg/l Marine water	Fish - Fish	96 h
	Acute LC50 > 1,000 mg/l Fresh water	Fish - Fish	96 h
	Acute LC50 13 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
	Acute LC50 6.5 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
	Acute LC50 3 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute LC50 15.9 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute LC50 3.6 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute LC50 11 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute LC50 13.4 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute EC50 27.8 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
	Acute EC50 19.3 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
	Acute EC50 35.306 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
Antimony trioxide	Water	Duphinu	
	Acute LC50 > 530 mg/l Fresh water	Fish - Fish	96 h
	Acute LC50 > 1,000,000 µg/l Marine water	Fish - Fish	96 h
	Acute EC50 423,450 µg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
	Acute EC50 560 mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
	Acute EC50 730 µg/l Fresh water	Aquatic plants - Algae	72 h
	Acute EC50 760 µg/l Fresh water	Aquatic plants - Algae	96 h
	Acute EC50 740 µg/l Fresh water	Aquatic plants - Algae	96 h
	Acute NOEC 200 µg/l Fresh water	Aquatic plants - Algae	4 d
Naphthalene			
	Acute LC50 372 µg/l Fresh water	Fish - Fish	96 h
	Acute LC50 315 µg/l Fresh water	Fish - Fish	96 h
	Acute LC50 313 µg/l Fresh water	Fish - Fish	96 h
	Acute LC50 213 µg/l Fresh water	Fish - Fish	96 h
	Acute LC50 438 µg/l Fresh water	Fish - Fish	96 h



Valspar 70 Base

Version Number 1.5 Revision Date 06/07/2016 Page 15 of 20 Print Date 06/09/2016

Acute LC50 2,160 µg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
Acute EC50 1.96 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
Acute EC50 2.550 Mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
Acute EC50 1,600 µg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
Acute EC50 2,194 µg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
Acute LC50 2,800 µg/l Marine water	Aquatic invertebrates. Crustaceans	48 h
Acute LC50 2.6 mg/l Marine water	Aquatic invertebrates. Crustaceans	48 h
Acute EC50 5,960 µg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
Acute LC50 3,930 µg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
Acute LC50 2,350 µg/l Marine water	Aquatic invertebrates. Crustaceans	48 h
Acute EC50 1.6 mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h

Conclusion/Summary

: Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Titanium dioxide		352.00	low
Diisodecyl phthalate (mixed	8.8	0.10	low
isomers)			
Bisphenol A -	2.64 - 3.78	31.00	low
Epichlorohydrin polymer			
Naphthalene	3.4	36.50	low

Mobility in soil

Soil/water partition coefficient	:	Not available.
(KOC)		
Other adverse effects	:	No known significant effects or critical hazards.

Valspar 70 Base

Version Number 1.5 Revision Date 06/07/2016

<u>PolyOne</u>

Page 16 of 20 Print Date 06/09/2016

Section 13. Disposal considerations

•

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA	:	Consult mode specific transport rules
IMO/IMDG (maritime)	:	Consult mode specific transport rules

Section 15. Regulatory information

United States - TSCA 4(a) - Final Test Rules: Listed Diisodecyl phthalate
United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not
listed United States - TSCA 5(a)2 - Proposed significant new use rules:
 Not listed

Valspar 70 Base

Version I	Numb	er 1.5
Revision	Date	06/07/2016

PolyOne

Page 17 of 20 Print Date 06/09/2016

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Listed Lead

United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined United States - TSCA 8(a) - Preliminary assessment report (PAIR): Listed Naphthalene

United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Vinyl chloride monomer Lead Arsenic Diisodecyl phthalate Miscellaneous Zinc Compounds Zinc Naphthalene

United States - EPA Clean water act (CWA) section 311 -Hazardous substances: Listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed

Clean Air Act Section 112(b)	:
Hazardous Air Pollutants (HAPs)	
Clean Air Act Section 602 Class I	:
Substances	
Clean Air Act Section 602 Class II	:
Substances	
DEA List I Chemicals (Precursor	:
Chemicals)	
DEA List II Chemicals (Essential	:
Chemicals)	

- Listed
- Not listed

Antimony trioxide

- Not listed
- : Not listed
- : Not listed



Valspar 70 Base

Version Number 1.5 Revision Date 06/07/2016 Page 18 of 20 Print Date 06/09/2016

US. EPA CERCLA Hazardous Substances (40 CFR 302)

:

Chemical Name	CAS-No.	RQ for component
Naphthalene	91-20-3	100 lb(s) 45.4 kg

SARA 311/312

Classification

Immediate (acute) health hazard Delayed (chronic) health hazard

Composition/information on ingredients

Name	%	Classification
Diisodecyl phthalate (mixed isomers)	5 - 6.8	АН
Bisphenol A - Epichlorohydrin polymer	1 - 1.5	АН
Antimony trioxide	1 - 1.5	АН, СН
Silica, cristobalite	0.3 - 1	СН
Naphthalene	0.3 - 1	АН, СН

SARA 313

	Product name	CAS number	%
Form R - Reporting	Naphthalene	91-20-3	0.3 - 1
requirements			
	Antimony trioxide	1309-64-4	1 - 1.5
Supplier notification	Naphthalene	91-20-3	0.3 - 1
	Antimony trioxide	1309-64-4	1 - 1.5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations		
Massachusetts	:	Т

The following components are listed: Antimony trioxide Silica, amorphous

Valspar 70 Base



Dago 10 of 20
Page 19 of 20
Print Date 06/09/2016

		Bis (2-ethylhexyl) adipate Titanium dioxide
New York	:	The following components are listed: Antimony trioxide Naphthalene
New Jersey	:	The following components are listed: Silica, cristobalite Antimony trioxide Bis (2-ethylhexyl) adipate Titanium dioxide Ethene, chloro-, homopolymer Naphthalene
Pennsylvania	:	The following components are listed: Titanium dioxide
		Bis (2-ethylhexyl) adipate
		Silica, amorphous
		Antimony trioxide
		Aluminum hydroxide
		Silica, cristobalite
		Naphthalene

<u>California Prop. 65</u> WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

United States inventory (TSCA 8b)	:	All components are listed or exempted.
Canada inventory	:	All components are listed or exempted.
International regulations		
International lists	:	 Australia inventory (AICS): Not determined. Taiwan inventory (CSNN): Not determined. Malaysia Inventory (EHS Register): Not determined. EINECS: All components are listed or exempted. Japan inventory: Not determined. China inventory (IECSC): Not determined. Korea inventory: Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined.
		19/20

Valspar 70 Base

Version Number 1.5 Revision Date 06/07/2016



Page 20 of 20 Print Date 06/09/2016

Chemical Weapons Convention	:	Not listed
List Schedule I Chemicals		
Chemical Weapons Convention	:	Not listed
List Schedule II Chemicals		
Chemical Weapons Convention	:	Not listed
List Schedule III Chemicals		

Section 16. Other information

<u>History</u>		
Date of printing	:	06/09/2016
Date of issue/Date of revision	:	06/07/2016
Date of previous issue	:	01/14/2014
Version	:	1.5
Key to abbreviations	:	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
References	:	Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.