

AM100 AZTEC GREEN 567C MATTE HV

Version Number 1.5 Revision Date 04/19/2018 Page 1 of 17 Print Date 04/29/2018

SAFETY DATA SHEET

AM100 AZTEC GREEN 567C MATTE HV

Section 1. Identification

GHS product identifier : AM100 AZTEC GREEN 567C MATTE HV

Chemical name: MixtureCAS number: MixtureOther means of identification: FO20023551Product type: liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number (with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2

EYE IRRITATION - Category 2A

GHS label elements



AM100 AZTEC GREEN 567C MATTE HV

Version Number 1.5 Page 2 of 17 Revision Date 04/19/2018 Print Date 04/29/2018

Hazard pictograms

Signal word : Danger

Hazard statements : Highly flammable liquid and vapor.

Causes serious eye irritation. Causes skin irritation.

Precautionary statements

General : Not applicable.

Prevention: Wear protective gloves. Wear eye or face protection. Keep away from

heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container

tightly closed. Wash hands thoroughly after handling.

Response : IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye

irritation persists: Get medical attention.

Storage : Store in a well-ventilated place. Keep cool.

Disposal : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Supplemental label elements : None known. **Hazards not otherwise classified** : None known.

Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: FO20023551

CAS number/other identifiers

Ingredient name	%	CAS number
Methyl ethyl ketone	50 - 75	78-93-3



AM100 AZTEC GREEN 567C MATTE HV

Version Number 1.5 Page 3 of 17 Revision Date 04/19/2018 Print Date 04/29/2018

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses.

Continue to rinse for at least 10 minutes. Get medical attention.

Remove victim to fresh air and keep at rest in a position comfortable Inhalation

for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

Loosen tight clothing such as a collar, tie, belt or waistband.

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get

medical attention. Wash clothing before reuse. Clean shoes thoroughly

Wash out mouth with water. Remove dentures if any. Remove victim **Ingestion**

> to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.

Maintain an open airway. Loosen tight clothing such as a collar, tie,

belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Skin contact



AM100 AZTEC GREEN 567C MATTE HV

Version Number 1.5 Page 4 of 17 Revision Date 04/19/2018 Print Date 04/29/2018

Causes serious eye irritation. Eye contact

No known significant effects or critical hazards. Inhalation

Skin contact Causes skin irritation.

Ingestion No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact Adverse symptoms may include the following:

pain or irritation

watering

redness

Inhalation No specific data.

Skin contact Adverse symptoms may include the following:

irritation redness

No specific data. Ingestion

Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically. Contact poison treatment specialist Notes to physician

immediately if large quantities have been ingested or inhaled.

Specific treatments No specific treatment.

Protection of first-aiders No action shall be taken involving any personal risk or without

suitable training. It may be dangerous to the person providing aid to

give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media

Use dry chemical, CO₂, water spray (fog) or foam.

Do not use water jet.

Specific hazards arising from the chemical

Highly flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion

May emit Hydrogen Chloride (HCl).

Hazardous thermal decomposition products

Decomposition products may include the following materials:

carbon dioxide



AM100 AZTEC GREEN 567C MATTE HV

Version Number 1.5 Revision Date 04/19/2018 Page 5 of 17 Print Date 04/29/2018

carbon monoxide halogenated compounds

Special protective actions for firefighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-

proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal

container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-

proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or



AM100 AZTEC GREEN 567C MATTE HV

Version Number 1.5 Revision Date 04/19/2018 Page 6 of 17 Print Date 04/29/2018

diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits



AM100 AZTEC GREEN 567C MATTE HV

Version Number 1.5 Revision Date 04/19/2018

Ingredient name

Page 7 of 17 Print Date 04/29/2018

ingi culciit name		L'Apostit Chines
Methyl ethyl ketone		OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 590 mg/m3 200 ppm Short-term exposure limit (STEL). A limit value beyond which there should be no exposure and which refers to a period of fifteen minutes, unless otherwise stated. 885 mg/m3 300 ppm OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 590 mg/m3 200 ppm NIOSH REL (1994-06-01) Time Weighted Average (TWA) 590 mg/m3 200 ppm Short-term exposure limit (STEL). A limit value beyond which there should be no exposure and which refers to a period of fifteen minutes, unless otherwise stated. 885 mg/m3 300 ppm ACGIH TLV (1994-09-01) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 590 mg/m3 200 ppm TLV-STEL: Threshold Limit Value - Short Time Exposure Level 885 mg/m3 300 ppm
Appropriate engineering controls Environmental exposure controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

7/17

Exposure limits



AM100 AZTEC GREEN 567C MATTE HV

Version Number 1.5 Revision Date 04/19/2018 Page 8 of 17 Print Date 04/29/2018

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved

standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves

cannot be accurately estimated.

Body protection: Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be approved by a specialist before handling this product., When there is a risk of ignition from static electricity, wear anti-static protective clothing., For the greatest protection from static discharges, clothing

should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that

meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state
Color
GREEN
Odor
Not available.
Odor threshold
pH
Not available.
Melting point
Not available.
Not available.
Not available.
Not available.
Not available.
Not available.

Flash point : Closed cup: -9 °C (16 °F)

Burning time: Not available.Burning rate: Not available.Evaporation rate: Not available.Flammability (solid, gas): Not available.

Lower and upper explosive : **Lower:** Not available.



AM100 AZTEC GREEN 567C MATTE HV

Version Number 1.5 Page 9 of 17 Revision Date 04/19/2018 Print Date 04/29/2018

Upper: Not available. (flammable) limits

Not available. Vapor pressure Not available. Vapor density Not available. **Relative density** Solubility Not available. Solubility in water Not available. Partition coefficient: n-Not available.

octanol/water

Auto-ignition temperature Not available. Not available. **Decomposition temperature** Not available. **SADT**

Dynamic: Not available. Viscosity

Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will

not occur.

Avoid all possible sources of ignition (spark or flame). Do not **Conditions to avoid**

pressurize, cut, weld, braze, solder, drill, grind or expose containers to

heat or sources of ignition.

Incompatible materials Avoid contact with acetal homopolymers and acetyl homopolymers

during processing.

Reactive or incompatible with the following materials:

oxidizing materials

Under normal conditions of storage and use, hazardous decomposition **Hazardous decomposition** products

products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Methyl ethyl ketone				
	LD50 Oral	Rat	2,737 mg/kg	=



AM100 AZTEC GREEN 567C MATTE HV

Version Number 1.5 Page 10 of 17 Revision Date 04/19/2018 Print Date 04/29/2018

Remarks - Inhalation:	No applicable toxicity data			
	LD50 Dermal	Rabbit	6,480 mg/kg	=

Conclusion/Summary : Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Methyl ethyl ketone	Skin - Mild irritant	Rabbit		24 hrs	-
	IIIItaiit				
	Skin -	Rabbit		24 hrs	-
	Moderate				
	irritant				
	Skin - Mild	Rabbit		24 hrs	-
	irritant				

Conclusion/Summary

Skin: Mixture.Not fully tested.Eyes: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin:Mixture.Not fully tested.Respiratory:Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)



AM100 AZTEC GREEN 567C MATTE HV

Version Number 1.5 Page 11 of 17 Revision Date 04/19/2018 Print Date 04/29/2018

Not available.

Aspiration hazard

Not available.

Information on likely routes of

exposure

Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes skin irritation.

Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain or irritation

watering

redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

irritation

redness

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary : Mixture. Not fully tested.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.

11/17



AM100 AZTEC GREEN 567C MATTE HV

 Version Number 1.5
 Page 12 of 17

 Revision Date 04/19/2018
 Print Date 04/29/2018

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	5,143.3 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Methyl ethyl ketone			
	Acute LC50 3,220 Mg/l Fresh water	Fish - Fish	96 h
Remarks - Acute - Fish:	Acute		
	Acute EC50 5.091 Mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
Remarks - Acute - Aquatic invertebrates.:	Acute		
	Acute EC50 > 500 Mg/l Marine water	Aquatic plants - Algae	96 h
Remarks - Acute - Aquatic plants:	Acute		
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic - Aquatic invertebrates.:	No applicable toxicity data		

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential



AM100 AZTEC GREEN 567C MATTE HV

Version Number 1.5 Revision Date 04/19/2018 Page 13 of 17 Print Date 04/29/2018

2-Butanone	0.29	-	low
------------	------	---	-----

Mobility in soil

Soil/water partition coefficient

(KOC)

Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Listed

Ingredient	CAS#	Status	Reference number
Methyl ethyl ketone	78-93-3	Listed	

Section 14. Transport information

U.S.DOT 49CFR

Ground/Air/WaterProper

Resin solution

3

Shipping Name: Technical Name:

Hazard Class / Division



AM100 AZTEC GREEN 567C MATTE HV

Version Number 1.5 Revision Date 04/19/2018 Page 14 of 17 Print Date 04/29/2018

UN Number UN1866
Packing Group II
Label Required 3

International Air ICAO/IATA

Proper Shipping Name: Resin solution

Technical Name:

Hazard Class / Division 3

UN Number UN1866 Packing Group II

Label Required 3

International Water

IMO/IMDG

Proper Shipping Name: Resin solution

Technical Name:

Hazard Class / Division 3

UN Number UN1866
Packing Group II
Label Required 3

Section 15. Regulatory information

U.S. Federal regulations

United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not

determined

United States - TSCA 8(a) - Preliminary assessment report

(**PAIR**): Not listed

United States - TSCA 8(c) - Significant adverse reaction (SAR):

Not listed



AM100 AZTEC GREEN 567C MATTE HV

Version Number 1.5 Revision Date 04/19/2018

Page 15 of 17 Print Date 04/29/2018

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Vinyl chloride monomer

Phthalocyanine green

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

United States - Department of commerce - Precursor chemical:

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

Substances

Clean Air Act Section 602 Class II

Substances

DEA List I Chemicals (Precursor

Chemicals)

DEA List II Chemicals (Essential

Chemicals)

Listed

Not listed

Not listed

Not listed

Listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component
Methyl ethyl ketone	78-93-3	5,000 lb(s)
		2,270 kg
		2,270 kg
		5,000 lb(s)

SARA 311/312

Classification Fire hazard

Immediate (acute) health hazard

Composition/information on ingredients

Name	%	Classification
Methyl ethyl ketone	50 - 75	F, AH



AM100 AZTEC GREEN 567C MATTE HV

Version Number 1.5 Page 16 of 17 Revision Date 04/19/2018 Print Date 04/29/2018

SARA 313

Not applicable.

State regulations

Massachusetts: None of the components are listed.New York: The following components are listed:

Methyl ethyl ketone

New Jersey : The following components are listed:

Methyl ethyl ketone

Ethene, chloro-, homopolymer

Pennsylvania : The following components are listed:

Methyl ethyl ketone

California Prop. 65

This product may contain a trace (<0.001%) amount of a chemical known to the State of California to cause cancer.

United States inventory (TSCA 8b) : All components are listed or exempted.

Canada inventory : All components are listed or exempted.

International regulations

Inventory list

Australia: All components are listed or exempted.Canada: All components are listed or exempted.China: All components are listed or exempted.Europe inventory: All components are listed or exempted.Japan: All components are listed or exempted.New Zealand: All components are listed or exempted.

Philippines : Not determined.

Republic of Korea : Not determined.

Taiwan : All components are listed or exempted.

Turkey : Not determined.

United States : All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

lth	/	2
nmability		3
sical hazards		0
icai nazarus		



AM100 AZTEC GREEN 567C MATTE HV

Version Number 1.5 Revision Date 04/19/2018 Page 17 of 17 Print Date 04/29/2018

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

Date of printing: 04/29/2018Date of issue/Date of revision: 04/19/2018Date of previous issue: 04/17/2017

Version : 1.5

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.