PolvOne

## MATERIAL SAFETY DATA SHEET **FB561 BLUE TEXTURE**

Version Number 1.4 Revision Date 03/29/2014 Page 1 of 6 Print Date 4/5/2014

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152			
Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).	
Product name	:	FB561 BLUE TEXTURE	
Product code	:	FO20025672	
Chemical Name	:	Mixture	
CAS-No.	:	Mixture	
Product Use		Industrial Applications	

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Calcium carbonate	1317-65-3	5 - 10

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion			
Acute exposure				
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.			
Ingestion	: May be harmful if swallowed.			
Eyes	: May cause eye and skin irritation.			
Skin	: Experience shows no unusual dermatitis hazard from routine handling.			
Chronic exposure	: Refer to Section 11 for Toxicological Information.			

PolyOne.

# MATERIAL SAFETY DATA SHEET **FB561 BLUE TEXTURE**

Version Number 1.4 Revision Date 03/29/2014 Page 2 of 6 Print Date 4/5/2014

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: no data available
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>no data available</li> <li>no data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal.
	7. HANDLING AND STORAGE

PolyOne.

# MATERIAL SAFETY DATA SHEET **FB561 BLUE TEXTURE**

ion Number 1.4 sion Date 03/29/2014					Print	Page 3 t Date 4/5/
Handling	fi P	leat only in areas with a ume condensates may c eriodically clean hoods ccumulation of these m	ontain c , ducts,	combustible or tox and other surfaces	ic resi	due.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.				absorption	
8. ]	EXPOSURE	CONTROLS/PERSO	)NAL I	PROTECTION		
Respiratory protection	: N	lo personal respiratory	protecti	ve equipment norr	mally r	equired.
Eye/Face Protection	: S	afety glasses with side-	shields			
Hand protection	: P	rotective gloves				
Skin and body protection	: L	ong sleeved clothing				
Additional Protective Measures	: S	afety shoes				
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.					
Engineering measures Exposure limit(s)		leat only in areas with a ppropriate exhaust vent			ation.	Provide
Components	Value	Exposure time		Exposure typ	)e	List:
Calcium carbonate	5 mg/m3	PEL:		Respirable fract		OSHA ZI
	15 mg/m3	PEL:		Total dust.		OSHA Z
	10 mg/m3	Time Weighted Ave (TWA):	erage			MX OEL
	20 mg/m3	Short Term Exposure (STEL):	Limit			MX OEL
	9. PHYSI	CAL AND CHEMICA	L PRO	PERTIES		
Form	: liqui	d	Evanor	uration rate :	Not	established
FUIII		ous, liquid				determined
	: viscous, liquidSpecific Gravity: Not determined: BLUEBulk density: Not applicable					
Appearance Colour		E	Bulk d			
Appearance				r pressure :	Not	determined
Appearance Colour Odour Melting point/range	: BLU : very : not a	faint pplicable	Vapou		Not	determined
Appearance Colour Odour Melting point/range Boiling Point:	: BLU : very : not a : not a	faint pplicable pplicable	Vapou	r pressure :	Not	
Appearance Colour Odour Melting point/range	: BLU : very : not a	faint pplicable pplicable	Vapou Vapou	r pressure :	Not	determined
Appearance Colour Odour Melting point/range Boiling Point:	: BLU : very : not a : not a : imm	faint pplicable pplicable	Vapou Vapou pH	r pressure : r density :	Not	determined

PolyOne

## MATERIAL SAFETY DATA SHEET **FB561 BLUE TEXTURE**

Version Number 1.4 Revision Date 03/29/2014 Page 4 of 6 Print Date 4/5/2014

Stability	: The product is stable if stored and handled as prescribed.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid therma decomposition, do not overheat.	al
Incompatible Materials	: Incompatible with strong acids and oxidizing agents., Avoid contac with acetal homopolymers and acetal copolymers during processing	
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).	ur

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: no data available
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification,

blvU<u>ne</u>

### MATERIAL SAFETY DATA SHEET FB561 BLUE TEXTURE

Version Number 1.4 Revision Date 03/29/2014 Page 5 of 6 Print Date 4/5/2014

 transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

 14. TRANSPORT INFORMATION

 U.S. DOT Classification
 : Refer to specific regulation.

 ICAO/IATA
 : Refer to specific regulation.

 IMO/IMDG (maritime)
 : Refer to specific regulation.

 US Pagelations:
 15. REGULATORY INFORMATION

**US Regulations:** 

OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Miscellaneous Zinc Compounds	0-05-5	0.10 - 1.00	241

PolyOne.

## MATERIAL SAFETY DATA SHEET **FB561 BLUE TEXTURE**

Version Number 1.4 Revision Date 03/29/2014 Page 6 of 6 Print Date 4/5/2014

WHMIS Classificati	on :	Not controlled.
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.